



ELECTRICAL CHARACTERISTICS: < FOR 1034AH V.90, MEET IEC 950 >

1. D.C.R. : PIN 1-2 = 135 OHM MAX. PIN 3-4 = 160 OHM MAX.
2. INDUCTANCE (@1KHZ, 1Vrms LP) : PIN 1-2 = 2.5Hy MIN.
3. INSERTION LOSS (@ 1KHZ, 0dBm) PIN 1-2 = 3.0 dB MAX.
4. FREQ. RESP.(REF, 1KHZ) : @200HZ-4KHZ = +/-0.15dB
5. RETURN LOSS (REF, 600 OHM) : @ 200HZ = 30dB MIN. @1KHZ = 30dB MIN. @4KHZ = 20dB MIN.
6. TURNS RATIO : PIN 1-2 : PIN4-3 = 1+/-1%
7. LONGITUDINAL BAL. = 60dB MIN.(@200-4KHZ)
8. T.H.D. (@600HZ, -10dBm) = -78dB MAX.
9. HI-POT (@1650VAC, 1mA, 2SEC.) PRI. - SEC.

					Atech®		TITLE 1034AH TRANSFORMER	
B	ADD BAPT NO.	06/30/99	PAIR		SUEBY	Atech Technology Co., Ltd.		DWG. NO.
A	DIM 16.9 MAX.	12/17/98	PAIR		SUEBY	TEL:(02)2784-0687 FAX:(02)2784-8004		ATS-329
	RELEASE	11/17/98	PAIR		SUEBY	UNITS: M/M	SAFETY	
NO.	DESCRIPTION	DATE	BY	CHK	APPD	DATE	SHEET 1 OF 1	
REVISIONS						11/17/98	CRC.0127	
								DRAW <i>Pair</i>