

AZ21501P

50 AMP MINIATURE LATCHING POWER RELAY

FEATURES

- 1 Form A, B and C contacts available
- Single coil latching
- Lower cost 30A & 40A contacts available
- Class F high temperature standard
- Epoxy sealed versions available
- UL, CUR E44211



CONTACTS

Arrangement	SPST (1 Form A, or B) SPDT (1 Form C)
Ratings	Resistive load: Max. switched power: 1200 W or 13850 VA Max. switched current: 50 A Max. switched voltage: 277 VAC, 110 VDC
UL, CUR	30A / 40A / 50A at 277VAC, 6k cycles, 25°C
Material	silver tin oxide

COIL

Power At Pickup Voltage (typical)	30A, 40A : 576mW 50A : 960mW
Max. Temperature	Max. 155°C (311°F) Class F

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 1 x 10 ⁶ See contact ratings.
Set Time	15ms
Reset Time	15ms
Dielectric Strength (at sea level for 1 min.)	1500 Vrms contact to contact 2500 Vrms contact to coil
Insulation Resistance	1000 megohms min. at 20°C, 500 VDC 50% RH
Ambient Temperature Operating	-40°C (-40°F) to 85°C (185°F)
Vibration	0.059" DA at 10-55 Hz
Shock	20 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.,
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	28 grams

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.




AZ21501P

RELAY ORDERING DATA

COIL SPECIFICATIONS – SINGLE COIL LATCHING					ORDER NUMBER*
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance $\pm 10\%$		
			30A, 40A	50A	
5	4.0	6.0	28	16.7	AZ21501P-1A-5D
12	9.6	14.4	160	96	AZ21501P-1A-12D
24	19.2	28.8	640	384	AZ21501P-1A-24D
48	38.4	57.6	2560	1536	AZ21501P-1A-48D

*Substitute “-1B” or “-1C” in place of “-1A” for 1 Form B or 1 Form C respectively. For 30A version, add “H” after “-1A”, “-1B”, or “-1C”. For 40A version, add “J” after “-1A”, “-1B”, or “-1C”. Substitute “DE” in place of “D” for epoxy sealed version.

MECHANICAL DATA

Outline Dimensions	PC Board Layout
	
	Mounting (Bottom view)

Tolerance: $\pm .010"$

AMERICAN ZETTLER, INC.

3/13/18

PHONE: (949) 831-5000

www.azettler.com

E-MAIL: SALES@AZETTLER.COM

This specification provides an overview of the most significant part features. Any individual applications and operating conditions are not taken into consideration. It is recommended to test the product under application conditions. Responsibility for the application remains with the customer. Proper operation and service life cannot be guaranteed if the part is operated outside the specified limits.