

# AZ767

## SPDT SUBMINIATURE POWER RELAY

### FEATURES

www.datasheet4u.com

- Low cost
- 10 Amp switching
- Epoxy sealed version available
- UL, CUR file E44211



### CONTACTS

<b>Arrangement</b>	SPST (1 Form A) SPDT (1 Form C)
<b>Ratings</b>	Resistive Load:  Max. switched power: 150 W or 1250 VA Max. switched current: 5 ADC or 10 AAC  Sensitive coil Max. switched power: 90 W or 750 VA Max. switched current: 3 A  SPDT Max. switched power: 90 W or 750 VA Max. switched current: 3 A  Max. switched voltage: 150 VDC* or 380 VAC  * Note: If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory
<b>Rated Load UL, CUR</b>	Form A 10 A at 125 VAC, Res., 30k cycles 5 A at 30 VDC / 250 VAC, 100k cycles 10 A LRA / 1.5 A FLA at 120 VAC, 100k cycles 1/10 HP at 125 VAC, 100k cycles 1/6 HP at 250 VAC, 100k cycles  Sensitive coil 5 A at 125 VAC, Res., 100k cycles 3 A at 30 VDC / 250 VAC, 100k cycles  Form C 3 A at 30 VDC / 250 VAC, 100k cycles
<b>Material</b>	Silver cadmium oxide
<b>Resistance</b>	< 100 milliohms initially

### COIL

<b>Power</b>	
<b>At Pickup Voltage (typical)</b>	253 mW standard coil 113 mW sensitive coil
<b>Max. Continuous Dissipation</b>	1.25 W at 20°C (68°F) ambient
<b>Temperature Rise (at nominal voltage)</b>	41°C (74°F) standard coil 22°C (40°F) sensitive coil
<b>Temperature</b>	Max. 130°C (266°F)

### GENERAL DATA

<b>Life Expectancy</b>	Minimum operations
<b>Mechanical</b>	1 x 10 <sup>7</sup>
<b>Electrical</b>	1 x 10 <sup>5</sup> at 5 A 250 VAC Res.
<b>Operate Time (typical)</b>	8 ms at nominal coil voltage
<b>Release Time (typical)</b>	5 ms at nominal coil voltage (with no coil suppression)
<b>Dielectric Strength (at sea level for 1 min.)</b>	2500 Vrms coil to contact 1000 Vrms between open contacts
<b>Insulation Resistance</b>	1000 megohms min. at 20°C 500 VDC 50% RH
<b>Dropout</b>	Greater than 5% of nominal coil voltage
<b>Ambient Temperature Operating</b>	At nominal coil voltage -40°C (-40°F) to 70°C (158°F) standard -40°C (-40°F) to 85°C (185°F) sensitive
<b>Storage</b>	-40°C (-40°F) to 105°C (221°F)
<b>Vibration</b>	0.062" (1.5 mm) DA at 10–50 Hz
<b>Shock</b>	10 g operating, 100 g damage
<b>Enclosure</b>	P.B.T. polyester
<b>Terminals</b>	Tinned copper alloy, P.C.
<b>Max. Solder Temp.</b>	270°C (518°F)
<b>Max. Solder Time</b>	5 seconds
<b>Max. Solvent Temp.</b>	80°C (176°F)
<b>Max. Immersion Time</b>	30 seconds
<b>Weight</b>	6 grams
<b>Packing unit in pcs</b>	50 per plastic tray / 500 per carton box

### NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.

**ZETTLER electronics GmbH**

Junkersstrasse 3, D-82178 Puchheim, Germany

Tel. +49 89 800 97 0  
Fax +49 89 800 97 200

office@ZETTLERelectronics.com

www.ZETTLERelectronics.com  
www.DataSheet4U.com

2005-03-08

# AZ767

## RELAY ORDERING DATA

STANDARD RELAYS					
COIL SPECIFICATIONS				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance Ohm $\pm 10\%$	Form A (SPST)	Form C (SPDT)
3	2.25	5.0	20	AZ767-1A-3D	AZ767-1C-3D
5	3.75	8.3	55	AZ767-1A-5D	AZ767-1C-5D
6	4.5	10.0	80	AZ767-1A-6D	AZ767-1C-6D
9	6.75	15.0	180	AZ767-1A-9D	AZ767-1C-9D
12	9.0	20.0	320	AZ767-1A-12D	AZ767-1C-12D
18	13.5	30.0	720	AZ767-1A-18D	AZ767-1C-18D
24	18.0	40.0	1,280	AZ767-1A-24D	AZ767-1C-24D

SENSITIVE RELAYS					
COIL SPECIFICATIONS				ORDER NUMBER*	
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance Ohm $\pm 10\%$	Form A (SPST)	
3	2.25	7.5	45	AZ767-1A-3DS	
5	3.75	12.5	125	AZ767-1A-5DS	
6	4.5	15.0	180	AZ767-1A-6DS	
9	6.75	22.4	400	AZ767-1A-9DS	
12	9.0	30.0	720	AZ767-1A-12DS	
18	13.5	44.7	1,600	AZ767-1A-18DS	
24	18.0	59.2	2,800	AZ767-1A-24DS	

\* Add suffix "E" for epoxy sealed version.

## MECHANICAL DATA

Top view dimensions: .740 MAX. [18.80] width, .417 MAX. [10.59] height.

Side view dimensions: .614 MAX. [15.59] height, .147 [3.73] terminal height, .073 [1.85] terminal width.

### PC BOARD LAYOUT

Dimensions: .073 [1.85], .059 [1.50], .100 [2.54], .058 [1.49], .300 [7.62], 5 x  $\varnothing$  .052 [ $\varnothing$ 1.3], .441 [11.20].

FORM C ONLY

Viewed toward terminals

---

### WIRING DIAGRAMS

Form A

Form C

Viewed toward terminals

Dimensions in inches with metric equivalents in parentheses. Tolerance:  $\pm .010$ "

## ZETTLER electronics GmbH

Junkersstrasse 3, D-82178 Puchheim, Germany

Tel. +49 89 800 97 0

Fax +49 89 800 97 200

office@ZETTLERelectronics.com

www.ZETTLERelectronics.com

www.DataSheet4U.com

2005-03-08