

AZ9731F

30 AMP MINI-ISO AUTOMOTIVE RELAY WITH FUSE

FEATURES

- Quick connect terminals
- 30 Amp contact rating (30A Fuse)
- Blade fuse design
- Steel mounting bracket
- ISO/TS 16949, ISO14001



CONTACTS

Arrangement	SPST (1 Form A)
Ratings	Resistive load: Max. switched power: 420 W Max. switched current: 30 A Max. switched voltage: 75 VDC
Material	Silver tin oxide
Resistance	< 50 milliohms initially (24 V, 1 A voltage drop method)

COIL

Power	
At Pickup Voltage (typical)	760 mW
Max. Continuous Dissipation	3.0 W at 20°C (68°F)
Temperature Rise	70°C (126°F) at nominal coil voltage (30A)
Temperature	Max. 105°C (311°F)

RELAY ORDERING DATA

COIL SPECIFICATIONS			
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance ± 10%
6	3.9	7.8	20
12	7.8	15.6	80
24	15.6	31.2	320

GENERAL DATA

Life Expectancy Mechanical Electrical	Minimum operations 1 x 10 ⁷ 1 x 10 ⁵ at 30 A 14 VDC Res.
Operate Time (max.)	7 ms at nominal coil voltage
Release Time (max.)	5 ms at nominal coil voltage
Dielectric Strength (at sea level for 1 min.)	50Hz 750 Vrms coil to contact 50Hz 500 Vrms contact to contact
Insulation Resistance	100 megohms min. at 500 VDC, 20°C 50% RH
Dropout	Greater than 20% of nominal coil voltage
Ambient Temperature Operating Storage	At nominal coil voltage -40°C (-40°F) to 85°C (185°F) -55°C (-67°F) to 155°C (311°F)
Vibration	1.27mm DA at 10-40 Hz
Shock Resistance	147m/s ² 11ms
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy 0.25 Quick Connect Note: Allow suitable slack on leads when wiring, and do not subject the terminals to excessive force.
Weight	32 grams

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.


AMERICAN ZETTLER, INC. www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM


6/11/14

AZ9731F

RELAY ORDERING DATA



MECHANICAL DATA



NOTES: Dimension are in millimeters. Inch equivalents are given for general information only. Tolerance: $\pm .010$ "

AMERICAN ZETTLER, INC. www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM