

B28 FEMALE HEADER (1.27mm * 1.27mm)

PITCH: 1.27mm




SPECIFICATIONS

Material



Insulator : LCP, glass reinforced, rated UL 94V-0
Contact : Phosphor Bronze

Electrical

Current Rating : 1 Amp DC
Contact Resistance : 30 mΩ max.
Insulation Resistance : 1000 MΩ min.
Dielectric Withstanding Voltage : 250V AC for 1minute
Operating Temperature : -40°C to +105°C
• Mating Suggestion : C11, C12 series.



TYPE	X	Y
A	3.4	3.6
B	4.3	4.5



HOW TO ORDER:

B28 - 1 - 2 - 3 - 4 - 5 - 6 - 7

1.NO. OF CONTACT	2.CONTACT MATERIAL	3.CONTACT PLATING	4.MOUNTING TYPE
DUAL ROW 2*5 - 2*50	B: PHOSPHOR BRONZE	T: TIN PLATED S: SELECTIVE G: GOLD FLASH O: 3u" INCH GOLD A: 5u" INCH GOLD B: 10u" INCH GOLD C: 15u" INCH GOLD D: 30u" INCH GOLD	A: THROUGH HOLE B: SMT TYPE
5. INSULATOR HEIGHT	6.SPECIAL FUNCTION	7.INSULATOR COLOR	
A: 3.4mm B: 4.3mm	A: W POLARIZATION PEG B: W/O POLARIZATION PEG	1. BLACK	