



## Metallized Polyester (MKT/MFT)

**Series/Type:**        **B32582**

[www.DataSheet4U.com](http://www.DataSheet4U.com)


The following products presented in this data sheet are being withdrawn.

Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B32582		30.08.2002	31.10.2002	31.03.2003
B32583		30.08.2002	31.10.2002	31.03.2003
B32584		30.08.2002	31.10.2002	31.03.2003

For further information please contact your nearest EPCOS sales office, which will also support you in selecting a suitable substitute. The addresses of our worldwide sales network are presented at [www.epcos.com/sales](http://www.epcos.com/sales).

**MFT pulse capacitors with highest possible contact reliability**
**Construction**

- Dielectric: polyethylene terephthalate (polyester)
- Wound capacitor technology
- Metallized film and metal foils internally connected in series
- Plastic case (UL 94 V-0)
- Epoxy resin sealing



Dimensions in mm

**Features**

- Very high pulse strength
- Highest possible contact reliability
- Self-healing properties
- Perfectly adapted to - and tested with - 1 kV and 3 kV EPCOS switching spark gaps<sup>1)</sup>
- High operation temperature

Lead spacing $e \pm 0,4$	Diameter $d_1$	Type
15,0	0,8	B 32 582
22,5	0,8	B 32 583
27,5	0,8	B 32 584

**Typical applications**

- Ignition devices for gas discharge lamp appliances used in car headlight systems, video projection systems and backlight-TV systems

**Terminals**

- Parallel wire leads, tinned

**Marking**

Manufacturer's logo,  
lot number, style and type (FT5xx),  
rated capacitance (coded),  
capacitance tolerance (code letter),  
rated dc voltage,  
date of manufacture (coded)


**Delivery mode**

Bulk (untaped)

Taped (Ammo pack or reel)

For notes on taping, refer to chapter "Taping and packing", page 274.

1) Special MKT capacitors (stacked-film technology) optimized for ignition circuits using lower switching voltages are available on request.




**B 32 582 ...**

**B 32 584**

**Overview of available types**

Lead spacing	15 mm	22,5 mm	27,5 mm
Type	B 32 582	B 32 583	B 32 584
1,5 nF	3000 Vdc		
2,2 nF			
3,3 nF			
4,7 nF			
6,8 nF		3000 Vdc	
10 nF			
15 nF			
22 nF			
33 nF			
47 nF			1250 Vdc
56 nF			
68 nF			


**Ordering codes and packing units, lead spacing 15 mm**

$V_R$ ( $V_{rms}$ , $f \leq 60$ Hz)	$C_R$	Maximum dimensions $b \times h \times l$ (mm)	Ordering code <sup>1)</sup>	Packing units (pcs)		
				Ammo pack	Reel	Untaped
3000 Vdc	1,5 nF	7,0 × 12,5 × 18	B32582-A9152-+***	830	900	1000
	2,2 nF	7,0 × 12,5 × 18	B32582-A9222-+***	830	900	1000
	3,3 nF	8,5 × 14,5 × 18	B32582-A9332-+***	680	700	500
	4,7 nF	9,0 × 17,5 × 18	B32582-A9472-+***	640	700	500

**Ordering codes and packing units, lead spacing 22,5 mm**

$V_R$ ( $V_{rms}$ , $f \leq 60$ Hz)	$C_R$	Maximum dimensions $b \times h \times l$ (mm)	Ordering code <sup>1)</sup>	Packing units (pcs)		
				Ammo Pack	Reel	Untaped
3000 Vdc	6,8 nF	8,5 × 16,5 × 26,5	B32583-A9682-+***	480	500	510
	10 nF	10,5 × 16,5 × 26,5	B32583-A9103-+***	390	400	540

**Ordering codes and packing units, lead spacing 27,5 mm**


$V_R$ ( $V_{rms}$ , $f \leq 60$ Hz)	$C_R$	Maximum dimensions $b \times h \times l$ (mm)	Ordering code <sup>1)</sup>	Packing units (pcs)		
				Ammo Pack	Reel	Untaped
1250 Vdc	47 nF	11,0 × 21,0 × 31,5	B32584-A7473-+***	–	350	320
	56 nF	11,0 × 21,0 × 31,5	B32584-A7563-+***	–	350	320
	68 nF	11,0 × 21,0 × 31,5	B32584-A7683-+***	–	350	320

Capacitance tolerance:  $\pm 10\% \hat{=} K$ ,  $\pm 5\% \hat{=} J$

1) + Code letter for capacitance tolerance

\*\*\* Code number for packing: Ammo pack = 289, reel = 189

The ordering code for untaped components ends after the tolerance code letter.




B 32 582 ...

B 32 584

### Technical data


Climatic category in accordance with IEC 60068-1	40/120/56
Lower category temperature $T_{\min}$	- 40 °C
Upper category temperature $T_{\max}$	+ 120 °C
Damp heat test	56 days/40 °C/93 % relative humidity
Limit values after damp heat test	Capacitance change $ \Delta C/C $ ≤ 5 % Dissipation factor change $\Delta \tan \delta$ ≤ $5 \cdot 10^{-3}$ (at 1 kHz) Insulation resistance $R_{is}$ ≥ 50 % of minimum as-delivered values
Reliability:	
Reference conditions	$0,5 \cdot V_R$ ; 40 °C
Failure rate	$2 \cdot 10^{-9}/h = 2$ fit  For a conversion table for other operating conditions and temperatures, refer to chapter "Quality assurance", page 327.
Service life	200 000 h
Failure criteria:	
Total failure	Short circuit or open circuit
Failure due to variation of parameters	Capacitance change $ \Delta C/C $ > 10 % Dissipation factor $\tan \delta$ > 4 · upper limit value Insulation resistance $R_{is}$ < 1500 M $\Omega$
DC test voltage	$1,6 \cdot V_R$ , 2 s
Category voltage $V_C$	$T \leq 85$ °C: $V_C = 1,0 \cdot V_R$ or $1,0 \cdot V_{rms}$
Operation with dc voltage or ac voltage $V_{rms}$ up to 60 Hz	$T = 100$ °C: $V_C = 0,8 \cdot V_R$ or $0,8 \cdot V_{rms}$ $T = 120$ °C: $V_C = 0,5 \cdot V_R$ or $0,5 \cdot V_{rms}$
Category voltage for short operating periods	$T \leq 100$ °C: $V_C = 1,25 \cdot V_R$ or $1,0 \cdot V_{rms}$ for max. 2000 h $T \leq 125$ °C: $V_C = 0,6 \cdot V_R$ or $0,5 \cdot V_{rms}$ for max. 1000 h
Dissipation factor $\tan \delta$ (in $10^{-3}$ ) at 20 °C (upper limit values)	at 1 kHz: $8 \cdot 10^{-3}$ at 10 kHz: $15 \cdot 10^{-3}$ at 100 kHz: $25 \cdot 10^{-3}$
Insulation resistance $R_{is}$ at 20 °C, rel. humidity ≤ 65 % (minimum as-delivered values)	> 10 G $\Omega$

Impedance  $Z$   
versus  
frequency  $f$   
(typical values)



### Pulse handling capability

The capacitors are especially manufactured and tested to suit their intended applications. Typical permissible loads:



$V_R$	Max. rate of voltage rise $V_{pp}/\tau$ in $\text{V}/\mu\text{s}$ (for $V_{pp} = V_R$ )		
	Lead spacing		
	15 mm	22,5 mm	27,5 mm
1250 Vdc	—	—	10 000
3000 Vdc	20 000	20 000	—

Capability of 100 000 switches (ON/OFF).

**Herausgegeben von EPCOS AG**

**Marketing Kommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND**

© EPCOS AG 2000. Alle Rechte vorbehalten. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Mit den Angaben in dieser Broschüre werden die Bauelemente spezifiziert, keine Eigenschaften zugesichert. Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland.

Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

**Published by EPCOS AG**

**Marketing Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2000. All Rights Reserved. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

The information contained in this brochure describes the type of component and shall not be considered as guaranteed characteristics. Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.