



SAW Components

SAW Duplexer

Cellular / WCDMA Band V

Series/type:	B7663
Ordering code:	B39881B7663P310
Date:	March 22, 2007
Version:	2.0



Preliminary Data




Application

- Low-loss RF duplexer for mobile telephone cellular / WCDMA Band V systems
- Very small size and low height




Features

- Package size 3.0 x 2.5 x 0.68 mm³
- Package code QCS9F
- RoHS compatible
- Approx. weight 0.021 g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- ESD sensitive device



Pin configuration

- 1 TX input
- 3 RX output
- 6 Antenna
- 2,4,5 Ground
- 7,8,9 Ground





SAW Components

B7663

SAW Duplexer

836.5 / 881.5 MHz

Preliminary Data



Characteristics

Operating temperature range: T = -30 °C to +80 °C
 ANT terminating impedance: Z_{ANT} = 50 Ω
 RX terminating impedance: Z_{RX} = 50 Ω
 TX terminating impedance: Z_{TX} = 50 Ω

Characteristics TX-ANT				min.	typ. @ 25 °C	max.	
Center frequency			f _C	—	836.5	—	MHz
Maximum insertion attenuation	824.0 ... 849.0		α _{max}	—	1.7	2.5 ¹⁾	dB
Amplitude ripple (p-p)	824.0 ... 849.0		Δα	—	0.5	1.4	dB
Return loss							
TX port	824.0 ... 849.0			10.0	12	—	dB
ANT port	824.0 ... 849.0			10.0	12	—	dB
Attenuation			α				
	0.3 ... 779.0			20	32	—	dB
	779.0 ... 804.0			24	36	—	dB
	869.0 ... 894.0			45	47	—	dB
	894.0 ... 1570.0			20	33	—	dB
	1570.0 ... 1580.0			35	37	—	dB
	1580.0 ... 3000.0			32	37	—	dB
	3000.0 ... 6000.0			15	35	—	dB

¹⁾ Including estimated loss of 0.2 dB of matching element.



SAW Components

B7663

SAW Duplexer

836.5 / 881.5 MHz

Preliminary Data



Characteristics

Operating temperature range: T = -30 °C to +80 °C
 ANT terminating impedance: Z_{ANT} = 50 Ω
 RX terminating impedance: Z_{RX} = 50 Ω
 TX terminating impedance: Z_{TX} = 50 Ω

Characteristics ANT-RX					min.	typ. @ 25 °C	max.	
Center frequency				f _C	—	881.5	—	MHz
Maximum insertion attenuation	869.0 ... 894.0			α _{max}	—	2.1	3.5 ¹⁾	dB
Amplitude ripple (p-p)	869.0 ... 894.0			Δα	—	0.7	2.2	dB
Return loss								
TX port	869.0 ... 894.0				10.0	13	—	dB
ANT port	869.0 ... 894.0				8.5	13	—	dB
Attenuation				α				
	0.3 ... 824.0				35	43	—	dB
	434.0 ... 447.0				42	50	—	dB
	824.0 ... 849.0				54	58	—	dB
	954.0 ... 2485.0				30	46	—	dB
	2485.0 ... 6000.0				20	24	—	dB

¹⁾ Including estimated loss of 0.2 dB of matching element.



SAW Components

B7663

SAW Duplexer

836.5 / 881.5 MHz

Preliminary Data



Characteristics

Operating temperature range: $T = -30\text{ °C to }+80\text{ °C}$
ANT terminating impedance: $Z_{ANT} = 50\ \Omega$
RX terminating impedance: $Z_{RX} = 50\ \Omega$
TX terminating impedance: $Z_{TX} = 50\ \Omega$

Characteristics TX-RX	min.	typ. @ 25 °C	max.	
Isolation between RX and TX				
824.0 ... 849.0 MHz	56	59	—	dB
869.0 ... 894.0 MHz	45	48	—	dB
1648.0 ... 1698.0 MHz	45	60	—	dB



SAW Components

B7663

SAW Duplexer

836.5 / 881.5 MHz

Preliminary Data



Maximum ratings

Operating temperature range ¹⁾	T	-30/+80	°C	
Operable temperature range ²⁾	T _{stg}	-40/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	100 ³⁾	V	machine model, 10 pulses
Input Power at				source and load impedance 50Ω
824.0 ... 849.0 MHz	P _{IN}	31	dBm	continuous wave, 55 °C, 10000h
elsewhere	P _{IN}	10	dBm	continuous wave, 55 °C, 10000h

¹⁾ Defines the temperature range in which the specification values are guaranteed.

²⁾ Defines the temperature range in which the SAW device keeps its typical characteristics, however the specification values are not guaranteed.

³⁾ acc. to JESD22-A115A (machine model), 10 negative & 10 positive pulses.




Preliminary Data



Matching circuit to terminating impedances

(Element values depend upon PCB layout)




$L_{p1} = 8.2 \text{ nH}$




Preliminary Data



Frequency Response TX-ANT



Frequency Response TX-ANT (wideband)







Preliminary Data



Frequency Response RX-ANT



Frequency Response RX-ANT (wideband)




Please read *cautions and warnings* and *important notes* at the end of this document.




Preliminary Data



Frequency Response TX-RX



Frequency Response TX-RX (wideband)



Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

B7663

SAW Duplexer

836.5 / 881.5 MHz

Preliminary Data









Return Loss: S_{11} TX-port

S_{22} ANT-port

S_{33} RX-port

EPCOS confidential
proprietary



Please read *cautions and warnings* and *important notes* at the end of this document.



SAW Components **B7663**

SAW Duplexer **836.5 / 881.5 MHz**

Preliminary Data



References

Type	B7663
Ordering code	B39881B7663P310
Marking and package	C61157-A3-A16
Packaging	F61074-V8156-Z000
Date codes	L_1126
S-parameters	B7663_NB.s3p B7663_WB.s3p
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

**Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2007. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. The warnings, cautions and product-specific notes must be observed.
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as "hazardous")**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, CeraDiode, CSSP, PhaseCap, PhaseMod, SIFI, SIKOREL, Silver-Cap, SIMID, SIOV, SIP5D, SIP5K, TOPcap, UltraCap, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.