Band Switching Diodes - Dual, Series in SOT-323

Description

The main purpose of the BA892V-04W is the Band Switching. Biased with a DC forward current for signals at frequencies over 100 MHz up to 3 GHz this diode behaves like a current controlled resistor and not as a diode any more.

Depending on the forward current the forward resistance rf can be switched far below 1 Ω, so that the Switch is closed.

To open the Switch, the BA892V-04W has to be driven in the reverse mode where the BA892V-04W behaves like a small capacitor with high isolation.

So typical applications for this Band Switching Diode are mobile and TV-applications.



Features

- Low forward resistance
- Small reverse capacitance
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

Applications

Band switching up to 3 GHz

Low loss band-switching in TV/VTR tuners

Mechanical Data

Case: SOT-323 Plastic case

Weight: approx. 6.0 mg

Packaging Codes/Options:

GS08 / 3 k per 7" reel (8 mm tape), 3 k/box

Parts Table

Part	Ordering code	Marking	Remarks
BA892V-04W	BA892V-04W-GS08	AW4	Tape and Reel

Absolute Maximum Ratings

T_{amb} = 25 °C, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Reverse voltage		V_R	35	V
Forward current		I_F	100	mA
Junction temperature		T_j	150	°C
Storage temperature range		T_{stg}	-55 to +150	°C

Thermal Characteristics

T_{amb} = 25 °C, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Junction soldering point		R_{thJS}	100	K/W

Electrical Characteristics

T_{amb} = 25 °C, unless otherwise specified

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Reverse voltage	I_R = 10 μA	V_R	35			V
Reverse current	V_R = 20 V	I_R			20	nA
Forward voltage	I_F = 100 mA	V_F			1.1	V
Diode capacitance	f = 1 MHz, V_R = 0	C_D		1.1		pF
	f = 1 MHz, V_R = 1 V	C_D		0.9	1.2	pF
	f = 1 MHz, V_R = 3 V	C_D		0.85	1.1	pF
Forward resistance	f = 100 MHz, I_F = 1 mA	r_f		0.6		Ω
	f = 100 MHz, I_F = 3 mA	r_f		0.45	0.7	Ω
	f = 100 MHz, I_F = 10 mA	r_f		0.34	0.5	Ω
Charge carrier life time	I_F = 10 mA, I_R = 6 mA, i_R = 3 mA	t_{rr}		90		ns

Typical Characteristics (Tamb = 25 °C unless otherwise specified)



Figure 1. Forward Resistance vs. Forward Current



Figure 3. Forward Current vs. Forward Voltage



Figure 2. Diode Capacitance vs. Reverse Voltage



Figure 4. Reverse Voltage vs. Reverse Current



Figure 5. Typical Charge Recovery Curve

Package Dimensions in mm (Inches)



Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany

Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.