

## High Voltage Switching Diode


**Lead free product**

**Halogen-free type**

### FETURE

- We declare that the material of product compliance with RoHS requirements.

**BAS21GH**



### MAXIMUM RATINGS

| Rating                     | Symbol          | Value | Unit |
|----------------------------|-----------------|-------|------|
| Continuous Reverse Voltage | $V_R$           | 250   | Vdc  |
| Peak Forward Current       | $I_F$           | 200   | mAdc |
| Peak Forward Surge Current | $I_{FM(surge)}$ | 625   | mAdc |

### THERMAL CHARACTERISTICS

| Characteristic  | Symbol          | Max         | Unit                 |
|---|-----------------|-------------|----------------------|
| Total Device Dissipation FR-5 Board, (1)<br>$T_A = 25^\circ\text{C}$        | $P_D$           | 225         | mW                   |
| Derate above $25^\circ\text{C}$   |                 | 1.8         | mW/ $^\circ\text{C}$ |
| Thermal Resistance, Junction to Ambient                                     | $R_{\theta JA}$ | 556         | $^\circ\text{C/W}$   |
| Total Device Dissipation<br>Alumina Substrate, (2) $T_A = 25^\circ\text{C}$ | $P_D$           | 300         | mW                   |
| Derate above $25^\circ\text{C}$   |                 | 2.4         | mW/ $^\circ\text{C}$ |
| Thermal Resistance, Junction to Ambient                                     | $R_{\theta JA}$ | 417         | $^\circ\text{C/W}$   |
| Junction and Storage Temperature  | $T_J, T_{stg}$  | -55 to +150 | $^\circ\text{C}$     |

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic | Symbol | Min | Max | Unit |
|----------------|--------|-----|-----|------|
|----------------|--------|-----|-----|------|


### OFF CHARACTERISTICS

|  |            |     |              |                 |
|--|------------|-----|--------------|-----------------|
| Reverse Voltage Leakage Current<br>( $V_R = 200\text{Vdc}$ )<br>( $V_R = 200\text{Vdc}, T_J = 150^\circ\text{C}$ ) | $I_R$      | —   | 0.1<br>100   | $\mu\text{Adc}$ |
| Reverse Breakdown Voltage<br>( $I_{BR} = 100\ \mu\text{Adc}$ )   | $V_{(BR)}$ | 250 | —            | Vdc             |
| Forward Voltage<br>( $I_F = 100\ \text{mAdc}$ )<br>( $I_F = 200\ \text{mAdc}$ )                                    | $V_F$      | —   | 1000<br>1250 | mV              |
| Diode Capacitance<br>( $V_R = 0, f = 1.0\ \text{MHz}$ )  | $C_D$      | —   | 5.0          | pF              |
| Reverse Recovery Time<br>( $I_F = I_R = 30\text{mAdc}, R_L = 100\ \Omega$ )  | $t_{rr}$   | —   | 50           | ns              |

1. FR-5 = 1.0 x 0.75 x 0.062 in.

2. Alumina = 0.4 x 0.3 x 0.024 in. 99.5% alumina.

**Figure 1. Recovery Time Equivalent Test Circuit**



- Notes:
1. A 2.0 kΩ variable resistor adjusted for a Forward Current ( $I_F$ ) of 30 mA.
  2. Input pulse is adjusted so  $I_{R(\text{peak})}$  is equal to 30 mA.
  3.  $t_p \gg t_{rr}$

## DEVICE MARKING AND ORDERING INFORMATION

| Device  | Marking | Reel | Reel (pcs) | Carton (pcs)      | Packaging |
|---------|---------|------|------------|-------------------|-----------|
| BAS21GH | JS      | 7"   | 3,000      | 60,000<br>120,000 | SOT-23    |

## PACKAGE DIMENSIONS

SOT-23

Unit : mm

