



BAS299

DIODE

HIGH SPEED DOUBLE DIODES

DESCRIPTION



The UTC **BAS299** is schottky barrier diode, it uses UTC's advanced technology to provide customers with low forward voltage, etc.

The UTC **BAS299** is suitable for ultra high-speed switching, protection circuits, voltage clamping and blocking diodes.

FEATURES

- * High switching speed: 6ns (max.)
- * Continuous reverse voltage: 100V (max.)
- * Repetitive peak reverse voltage: 100V (max.)
- * Repetitive peak forward current: 900mA (max.)

SYMBOL




ORDERING INFORMATION

| Ordering Number | | Package | Pin Assignment | | | Packing |
|-----------------|---------------|---------|----------------|---|-----|-----------|
| Lead Free | Halogen Free | | 1 | 2 | 3 | |
| BAS299L-AE3-R | BAS299G-AE3-R | SOT-23 | A | K | COM | Tape Reel |

Note: Pin Assignment: A: Anode K: Cathode COM: Common Connection

| | |
|---|---|
| <p>BAS299G-AE3-R</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Green Package</p> | <p>(1) R: Tape Reel</p> <p>(2) AE3: SOT-23</p> <p>(3) G: Halogen Free and Lead Free, L: Lead Free</p> |
|---|---|

MARKING



■ ABSOLUTE MAXIMUM RATINGS

| PARAMETER | SYMBOL | RATINGS | UNIT |
|---|-----------|--------------------|--------------------|
| Repetitive peak reverse voltage | V_{RRM} | 100 | V |
| Continuous Reverse Voltage | V_R | 100 | V |
| Continuous Forward Current (single diode loaded) | I_F | 430 | mA |
| Continuous Forward Current (double diode loaded) | | 250 | mA |
| Repetitive peak forward current | I_{FRM} | 900 | mA |
| Non-Repetitive Peak Forward Current @Square Wave, $T_J=125^{\circ}\text{C}$ Prior to Surge | I_{FSM} | $t_p=1\mu\text{s}$ | A |
| | | $t_p=1\text{ms}$ | A |
| | | $t_p=1\text{s}$ | A |
| Power Dissipation (Note 2) | P_D | 250 | mW |
| Operating Junction Temperature | T_J | +150 | $^{\circ}\text{C}$ |
| Storage Temperature | T_{STG} | -65 ~ +150 | $^{\circ}\text{C}$ |

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Device mounted on an FR-4 PCB.

■ THERMAL CHARACTERISTICS




| PARAMETER | SYMBOL | RATINGS | UNIT |
|---------------------|---------------|---------|-----------------------------|
| Junction to Ambient | θ_{JA} | 500 | $^{\circ}\text{C}/\text{W}$ |

Note: Device mounted on an FR-4 PCB.

■ ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--------------------------|----------|--|-----|-----|------|---------------|
| Forward Voltage | V_F | $I_F=1\text{mA}$ | | | 715 | mV |
| | | $I_F=10\text{mA}$ | | | 855 | mV |
| | | $I_F=50\text{mA}$ | | | 1 | V |
| | | $I_F=150\text{mA}$ | | | 1.2 | V |
| | | $I_F=300\text{mA}$ | | | 1.25 | V |
| Reverse Current (Note) | I_R | $V_R=25\text{V}$ | | | 100 | nA |
| | | $V_R=100\text{V}$ | | | 1 | μA |
| | | $V_R=25\text{V}$ ($T_J=150^{\circ}\text{C}$) | | | 30 | μA |
| | | $V_R=100\text{V}$ ($T_J=150^{\circ}\text{C}$) | | | 50 | μA |
| Diode Capacitance | C_D | $V_R=0\text{V}$, $f=1\text{MHz}$ | | | 3 | pF |
| Reverse recovery time | t_{rr} | When Switched From $I_F=10\text{mA}$ to $I_R=10\text{mA}$, $R_L=100\Omega$, Measured at $I_R=1\text{mA}$ | | | 6 | ns |
| Forward recovery voltage | V_{fr} | When Switched From $I_F=10\text{mA}$ to $t_r=20\text{ns}$ | | | 1.75 | V |

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.