

**SURFACE MOUNT  
FAST SWITCHING DIODE**

**REVERSE VOLTAGE – 75 Volts  
FORWARD CURRENT – 0.25 Ampere**


**FEATURES**

- Fast switching speed
- Low reverse leakage current

**MECHANICAL DATA**

- Case: SOD-523 Plastic
- Case material: “Green” molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl)
- Moisture sensitivity: Level 1 per J-STD-020D
- Lead free in RoHS 2002/95/EC compliant

**SOD-523**



SOD-523		
Dim.	Min.	Max.
A	0.50	0.77
b	0.25	0.35
c	0.07	0.20
D	1.10	1.30
E	0.70	0.90
H	1.50	1.70
Dimensions in millimeter		

**Maximum Ratings & Thermal Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified**


Characteristic	Symbol	BAS516	Units
Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	85	V
Continuous Reverse Voltage	V <sub>R</sub>	75	V
Forward Continuous Current @ Ts=90°C (Note1)	I <sub>FM</sub>	250	mA
Peak Forward Surge Current @t=1s	I <sub>FSM</sub>	0.5	A
Repetitive Peak Forward Current	I <sub>FRM</sub>	0.5	A
Total Power dissipation @ Ts=90°C (Note1)	P <sub>tot</sub>	500	mW
Junction Temperature	T <sub>J</sub>	150	°C
Storage Temperature Range	T <sub>STG</sub>	-55~+150	°C

Note: Ts is the temperature at the soldering point of the cathode tab.


**Electrical Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified**

Characteristic	Test Condition	Symbol	BAS516	Unit
Maximum Forward Voltage	I <sub>F</sub> = 150mA	V <sub>F</sub>	1.25	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	V <sub>R</sub> = 75V	I <sub>R</sub>	1	uA
Typical Diode Capacitance	V <sub>R</sub> = 0V, f = 1MHz	C <sub>D</sub>	1	pF
Reverse Recovery time	V <sub>R</sub> = 6V, I <sub>R</sub> = I <sub>F</sub> = 10mA R <sub>L</sub> = 100Ω	trr	4	ns


**Fig.1 Maximum continuous forward current vs.soldering point temperature**




**Fig.2 Typical Forward Characteristics**




**Fig.3 Non-repetitive peak forward current**





**Fig.4 Reverse Current Characteristics**



**Fig.5 Capacitance Characteristics**



**Fig.6 Reverse recovery voltage test circuit and waveforms.**





(1)  $I_R = 1 \text{ mA}$ .

Input signal: reverse pulse rise time  $t_r = 0.6 \text{ ns}$ ; reverse voltage pulse duration  $t_p = 100 \text{ ns}$ ; duty factor  $\delta = 0.05$ ;

Oscilloscope: rise time  $t_r = 0.35 \text{ ns}$ .

**Fig.7 Forward recovery voltage test circuit and waveforms.**



Input signal: forward pulse rise time  $t_r = 20 \text{ ns}$ ; forward current pulse duration  $t_p \geq 100 \text{ ns}$ ; duty factor  $\delta \leq 0.005$ .

**Device Marking:**

Device P/N	Marking code	Equivalent Circuit Diagram
BAS516	6	1  2

## **Important Notice and Disclaimer**

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.