

**SOD-523 Plastic-Encapsulate Diodes****BAS516** Switching Diodes

## FEATURES

- Small surface mounting type
- High switching speed

Marking: 61

Maximum Ratings and Electrical Characteristics, Single Diode @T<sub>A</sub>=25°C

Parameter	Symbol	Limits	Unit
DC reverse voltage	V <sub>R</sub>	75	V
Mean rectifying current	I <sub>O</sub>	250	mA
Peak forward surge current	I <sub>FSM</sub>	0.5	A
Junction temperature	T <sub>j</sub>	150	°C
Storage temperature	T <sub>stg</sub>	-65~+150	°C

Electrical Ratings @T<sub>A</sub>=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V <sub>F</sub>			0.715 0.855 1 1.25	V	I <sub>F</sub> =1mA I <sub>F</sub> =10mA I <sub>F</sub> =50mA I <sub>F</sub> =150mA
Reverse current	I <sub>R</sub>			0.03 1	μA	V <sub>R</sub> =25V V <sub>R</sub> =75V
Capacitance between terminals	C <sub>T</sub>			1	pF	V <sub>R</sub> =0, f=1MHZ
Reverse recovery time	t <sub>rr</sub>			4	ns	I <sub>F</sub> =10mA, R <sub>L</sub> =100Ω






Fig.2 Maximum permissible continuous forward current as a function of soldering point temperature.



- (1)  $T_j = 150^\circ\text{C}$ ; typical values.
- (2)  $T_j = 25^\circ\text{C}$ ; typical values.
- (3)  $T_j = 25^\circ\text{C}$ ; maximum values.

Fig.3 Forward current as a function of forward voltage.



Based on square wave currents;  $T_j = 25^\circ\text{C}$  prior to surge.

Fig.4 Maximum permissible non-repetitive peak forward current as a function of pulse duration.





Fig.5 Reverse current as a function of junction temperature.



$f = 1$  MHz;  $T_j = 25$  °C.

Fig.6 Diode capacitance as a function of reverse voltage; typical values.