

### SOT-23




### Features

- ✧ Low turn-on voltage
- ✧ Fast switching
- ✧ PN junction guard ring for transient

### Mechanical Data

- ✧ Case: SOT-23, Molded plastic
- ✧ Weight: 0.008 gram (approx.)



### Dimensions in inches and (millimeters)



### Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise specified

Type Number	Symbol	Value	Units
Peak Repetitive Reverse Voltage	VRRM	30	V
Working Peak Reverse Voltage	VRWM		
DC Blocking Voltage	VR		
Forward Continuous Current	IF	200	mA
Repetitive Peak Forward Current	IFM	300	mA
Forward Surge Current @ t=1.0s	IFSM	600	mA
Power Dissipation (Note 1)	Pd	200	mW
Thermal Resistance Junction to Ambient Air	R <sub>θJA</sub>	500	°C/W
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-65 to +125	°C

### Electrical Characteristics

Type Number	Symbol	Min	Typ	Max	Units
Reverse Breakdown Voltage (Note 1)	V <sub>(BR)R</sub>	30	-	-	V
Reverse Leakage Current (Note 1) VR=25V	I <sub>R</sub>	-	-	2.0	uA
Forward Voltage (Note 1)	V <sub>F</sub>	-	-	240 320 400 500 1000	mV
Junction Capacitance VR=0, f=1.0MHz	C <sub>j</sub>	-	-	10	pF
Reverse Recovery Time (Note 2)	trr	-	-	5.0	nS

- Notes:
1. Short Duration Pulse Test used to Minimize Self-Heating Effect.
  2. Reverse Recovery Test Conditions: IF=10mA through IR=10mA to IR=1.0mA, RL=100Ω.

### RATINGS AND CHARACTERISTIC CURVES (BAT54 / A / C / S)

FIG.1- POWER DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS




FIG.5- TYPICAL TOTAL CAPACITANCE VS REVERSE VOLTAGE




FIG.6- TYPICAL TRANSIENT THERMAL CHARACTERISTICS

