


SCHOTTKY BARRIER DIODE

Features

- Low forward voltage

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Applications

- Ultra high-speed switching
- Voltage clamping
- Protection circuits

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Reverse Voltage	V_R	30	V
Forward Current	I_F	200	mA
Repetitive Peak Forward Current	I_{FRM}	300	mA
Peak Forward Surge Current ($t_p = 10 \text{ ms}$)	I_{FSM}	600	mA
Power Dissipation	P_D	200	mW
Thermal Resistance from Junction Ambient	R_{thJA}	500	K/W
Junction Temperature	T_J	125	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 65 to + 150	$^\circ\text{C}$

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min	Max.	Unit
Forward Voltage at $I_F = 0.1 \text{ mA}$ at $I_F = 1 \text{ mA}$ at $I_F = 10 \text{ mA}$ at $I_F = 30 \text{ mA}$ at $I_F = 100 \text{ mA}$	V_F	- - - - -	0.24 0.32 0.4 0.5 0.8	V
Reverse Breakdown Voltage at $I_R = 10 \mu\text{A}$	$V_{(BR)R}$	30	-	V
Reverse Current at $V_R = 25 \text{ V}$	I_R	-	2	μA
Total Capacitance at $V_R = 1 \text{ V}, f = 1 \text{ MHz}$	C_T	-	10	pF
Reverse Recovery Time at $I_F = 10 \text{ mA}, V_R = 6 \text{ V}, I_R = 10 \text{ mA}, R_L = 100 \Omega$	t_{rr}	-	6	ns




Figure 1. Typical Forward Voltage Forward Current at Various Temperatures




Figure 3. Typical Variation of Reverse Current at Various Temperatures





Figure 2. Typical Capacitance °C vs. Reverse Applied Voltage V_R

PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

SOD-523



UNIT	A	b _p	C	D	E	H _E	V	
mm	0.70 0.60	0.4 0.3	0.135 0.100	1.25 1.15	0.85 0.75	1.7 1.5	0.1	5°