

Small-Signal Schottky Diodes

VOLTAGE RANGE 10 Volts

FEATURES

- * High current rectifier Schottky diode with low VF drop
- * Low voltage, low inductance
- * For power supply
- * For detection and step-up-conversion

MECHANICAL DATA



- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Weight: 0.004 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.



SOD-323



Dimensions in inches and (millimeters)

MAXIMUM RATINGS (@ $T_A=25^\circ\text{C}$ unless otherwise noted)

RATINGS	SYMBOL	BAT60B	UNITS
Non-Repetitive Peak Reverse Voltage	V_{RM}	10	Volts
Maximum Forward Continuous Current	I_{FM}	3	Amps
Forward Surge Current @ $t=10\text{ms}$	I_{FSM}	5	Amps
Junction Capacitance (Note 1)	CT	30	pF
Maximum Power Dissipation (Note 2)	P_{tot}	250	mW
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature Range	TSTG	-65 to + 150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (@ $T_A=25^\circ\text{C}$ unless otherwise noted)

CHARACTERISTICS	SYMBOL	BAT60B	UNITS
Maximum Instantaneous Forward Voltage	@ $I_F=10\text{mA}$	300	mVolts
	@ $I_F=100\text{mA}$	380	
	@ $I_F=500\text{mA}$	500	
	@ $I_F=1000\text{mA}$	600	
Maximum Instantaneous Peverse Current	@ $V_R=5\text{V}$	15	uAmps
	@ $V_R=8\text{V}$	25	

NOTES : 1. Measured at 1MHz and applied reverse voltage of 5 volts.
2. Part mounted on FR-4 PC board with minimum recommended pad layout.

2008-12
REV: A

RATING AND CHARACTERISTICS CURVES (BAT60B)




Figure 1




Figure 2




Figure 3





Figure 4

RATING AND CHARACTERISTICS CURVES (BAT60B)



DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.