



# 1N4148WS,1N4448WS,BAV16WS

SURFACE MOUNT SWITCHING DIODES

Voltage Range 100 Volts  
Power 200mWatts

## Features


- \* Fast switching speed.
- \* Surface mount package Ideally Suited for Automatic insertion
- \* Electrically Identical to Standard JEDEC
- \* High Conductance
- \* Pb free product are available : 99% Sn above can meet Rohs environment substance directive request

## Mechanical Data

Case: SOD-323, Plastic

Terminals: Solderable per MIL-STD-202G, Method 208

Approx. Weight: 4.1mg



Dimensions in millimeters

## Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. For capacitive load, derate current by 20%.

PARAMETER	SYMBOL	1N4148WS	1N4448WS	BAV16WS	UNITS
Marking Code		A2	A3	A6	
Reverse Voltage	$V_R$		75		V
Peak Reverse Voltage	$V_{RM}$		100		V
RMS Voltage	$V_{RMS}$		50		V
Maximum DC Blocking Voltage	$V_{DC}$		75		V
Maximum Average Forward Current at $T_a=25^\circ C$	$I_{AV}$		200		mA
Peak Forward Surge Current, 1.0us	$I_{FSM}$	2	4	2	A
Power Dissipation Derate Above 25°C	$P_{TOT}$		200		mW
Maximum Forward Voltage	$V_F$	0.715 @ 0.001A 0.855 @ 0.01A 1.0 / 0.05A 1.25 @ 0.15A	0.72 @ 0.005A 1.0 @ 0.1A	0.855 @ 0.01A	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	$I_R$	0.025 @ 20V 2.5 @ 75V	2.5 @ 75V	1.0 @ 75V	uA
Junction Capacitance( Notes1)	$C_J$	1.5	4.0	20	pF
Maximum Reverse Recovery (Notes2)	$T_{RR}$	4	4	6	ns
Maximum Thermal Resistance	$R_{\theta JA}$		640		°C / W
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$		-55 TO +150		°C

## NOTES:

1.CJ at  $V_R=0$ ,  $f=1MHz$

2.From  $I_F=10mA$  to  $I_R=1mA$ ,  $V_R=6Volts$ ,  $R_L=100\Omega$



# 1N4148WS,1N4448WS,BAV16WS

SURFACE MOUNT SWITCHING DIODES

Voltage Range 100 Volts  
Power 200mWatts




Fig.1 Typical Forward Characteristic




Fig.2 Typical Reverse Characteristics




Fig.3 Power Derating Curve