



BAV74 SWITCHING DIODE

FEATURES

- Fast Switching Speed
- Surface Mount Package Ideally Suited for Automatic Insertion
- For General Purpose Switching Applications
- High Conductance

SOT-23



Marking: JA

Maximum Ratings @ $T_A=25^\circ\text{C}$

Parameter	Symbol	Value	Unit
Non-Repetitive Peak reverse voltage	V_{RM}	50	V
DC Blocking Voltage	V_R		
Average Rectified Output Current	I_O	200	mA
Power Dissipation	P_D	225	mW
Thermal Resistance. Junction to Ambient Air	$R_{\theta JA}$	556	°C/W
Junction temperature	T_J	150	°C
Storage temperature range	T_{STG}	-55-150	°C

ELECTRICAL CHARACTERISTICS (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{(BR)R}$	$I_R = 5\mu\text{A}$	50		V
Reverse voltage leakage current	I_R	$VR=50\text{V}$		0.1	μA
Forward voltage	V_F	$I_F=100\text{mA}$		1	V
Diode Capacitance	C_D	$V_R=0, f=1\text{MHz}$		2	pF
Reveres recovery time	t_{rr}	$I_F=I_R=10\text{mA}, R_L=100\Omega, I_{rr}=0.1 \times I_R$		4	nS

Typical Characteristics

BAV74




Figure 1. Forward Voltage




Figure 2. Leakage Current





Figure 3. Capacitance

PACKAGE OUTLINE

Plastic surface mounted package; 3 leads

SOT-23



UNIT	A	B	b _p	C	D	E	H _E	A ₁	L _p
mm	1.40 0.95	2.04 1.78	0.50 0.35	0.19 0.08	3.10 2.70	1.65 1.20	3.00 2.20	0.100 0.013	0.50 0.20