

Surface Mount Fast Switching Diodes


BAV99DW

FEATURES

- Fast switching speed.
- For general purpose switching application.
- Ultra-small surface mount package.
- High conductance.
- Two “BAV99”circuits in one package.



Lead-free



APPLICATIONS

- For general purpose switching application.

ORDERING INFORMATION

Type No.	Marking	Package Code
BAV99DW	KJG	SOT-363

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Symbol	Characteristic	Value	Unit
V_{RM}	Non-repetitive peak reverse voltage	100	V
V_{RRM} V_{RWM} V_R	Peak repetitive reverse voltage Working peak reverse voltage DC reverse voltage	75	V
$V_{R(RMS)}$	RMS Reverse voltage	53	V
I_{FM}	Forward continuous current	215	mA
I_{FSM}	Non-repetitive peak forward surge current @t=1.0μs @t=1.0ms @t=1.0s	2.0 1.0 0.5	A
P_D	Power Dissipation	200	mW
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	625	°C/W
T_j, T_{stg}	Junction and Storage Temperature	-65 to +150	°C



Surface Mount Fast Switching Diodes

BAV99DW

ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{(BR)R}$	$I_R=2.5\mu A$	75		V
Forward voltage	V_F	$I_F=1.0mA$ $I_F=10mA$ $I_F=50mA$ $I_F=150mA$		0.715 0.855 1.0 1.25	V
Reverse Current	I_R	$V_R=75V$ $V_R=75V, T_j=150^\circ C$ $V_R=25V, T_j=150^\circ C$ $V_R=20V$		2.5 50 30 25	μA μA μA nA
Total Capacitance	C_T	$V_R=0V, f=1.0MHz$		2.0	pF
Reverse Recovery time	t_{rr}	$I_F=I_R=10mA, I_{rr}=0.1 \cdot I_R,$ $R_L=100\Omega$		4.0	ns

TYPICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified




Fig. 1 Forward Characteristics




Fig. 2 Typical Reverse Characteristics




Fig. 3 Typical Capacitance vs. Reverse Voltage




Fig. 4 Power Derating Curve


Surface Mount Fast Switching Diodes

BAV99DW


PACKAGE OUTLINE

Plastic surface mounted package

SOT-363



SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
BAV99DW	SOT-363	3000/Tape&Reel