


SOT-363


Dimensions in inches and (millimeters)

Features

- ✧ Fast switching speed.
- ✧ For general purpose switching application.
- ✧ Ultra-small surface mount package.
- ✧ High conductance.

Applications

- ✧ For general purpose switching application.

Ordering Information

Type No.	Marking	Package Code
BAW567DW	KAC	SOT-363

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Symbol	Characteristic	Value	Unit
V_R	DC reverse voltage	75	V
I_F	Forward continuous current	150	mA
P_D	Power Dissipation	200	mW
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	625	°C/W
T_j, T_{stg}	Junction and Storage Temperature	-55 to +150	°C

ELECTRICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{(BR)R}$	$I_R=2.5\mu\text{A}$	75	-	V
Forward voltage	V_F	$I_F=1.0\text{mA}$ $I_F=10\text{mA}$ $I_F=50\text{mA}$ $I_F=150\text{mA}$	-	0.715 0.855 1.0 1.25	V
Reverse voltage leakage current	I_R	$V_R=75\text{V}$ $V_R=20\text{V}$	-	2.5 0.025	μA
Junction Capacitance	C_J	$V_R=0\text{V}, f=1.0\text{MHz}$	-	2.0	pF
Reverse Recovery time	t_{rr}	$I_F=I_R=10\text{mA}, I_{rr}=0.1*I_R,$ $R_L=100\Omega$	-	4.0	ns

TYPICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified
