


**BAW56W****Pb RoHS**

Plastic-Encapsulate Diodes

SWITCHING DIODE

FEATURES

- Fast Switching Speed
- For General Purpose Switching Applications
- High Conductance
- MARKING: KJC

**SOT-323****Maximum Ratings @Ta=25°C**

Parameter	Symbol	Limit	Unit
Non-Repetitive Peak Reverse Voltage	V_{RM}	100	V
Peak Repetitive Peak Reverse Voltage	V_{RRM}		
Working Peak Reverse Voltage	V_{RWM}	75	V
DC Blocking Voltage	V_R		
RMS Reverse Voltage	$V_{R(RMS)}$	53	V
Forward Continuous Current	I_{FM}	300	mA
Average Rectified Output Current	I_O	150	mA
Peak Forward Surge Current @t=1.0μs @t =1.0s	I_{FSM}	2 1	A
Power Dissipation	P_d	200	mW
Thermal Resistance Junction to Ambient	$R_{θJA}$	625	°C / W
Junction Temperature	T_j	150	°C
Storage Temperature	T_{STG}	-55~+150	°C

Electrical Ratings @Ta=25°C

Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Reverse breakdown voltage	$V_{(BR)}$	75			V	$IR=100\mu A$
Forward voltage	V_{F1} V_{F2} V_{F3} V_{F4}			0.715 0.855 1.0 1.25	V	$IF=1mA$ $IF=10mA$ $IF=50mA$ $IF=150mA$
Reverse current	I_{R1} I_{R2}			2.5 25	uA nA	$VR=75V$ $VR=20V$
Capacitance between terminals	C_T			2	pF	$VR=0V, f=1MHz$
Reverse recovery time	trr			4	ns	$IF=IR=10mA$ $Irr=0.1XIR, RL=100Ω$