


Small Signal General Purpose Transistors (NPN)

Features

- NPN Silicon Epitaxial Transistor for Switching and Amplifier Applications
- RoHS Compliance



TO-92



Mechanical Data

Case:	TO-92, Plastic Package
Terminals:	Solderable per MIL-STD-202G, Method 208
Weight:	0.18 gram

Maximum Ratings *(T_{Ambient}=25°C unless noted otherwise)*

Symbol	Description	BC548A	BC548B	BC548C	Unit
V_{CEO}	Collector-Emitter Voltage	30			V
V_{CBO}	Collector-Base Voltage	30			V
V_{EBO}	Emitter-Base Voltage	5			V
I_C	Collector Current	100			mA
I_B	Base Current	20			mA
I_E	Emitter Current	-100			mA
P_C	Collector Power Dissipation	625			mW
T_J, T_{STG}	Operation and Storage Junction Temperature Range	-55 to +150			°C



Small Signal General Purpose Transistors (NPN)

BC548A/B/C

Electrical Characteristics ($T_{Ambient}=25^{\circ}C$ unless noted otherwise)

Symbol	Description	Min.	Typ.	Max.	Unit	Conditions
ICBO	Collector Cut-Off Current	-	-	15	nA	$V_{CB}=30V, I_E=0$
hFE	D.C. Current Gain	BC548A	110	-	220	$V_{CE}=5V, I_C=2mA$
		BC548B	200	-	450	
		BC548C	420	-	800	
VCE(sat)	Collector Emitter Saturation Voltage	-	-	0.6	V	$I_C=100mA, I_B=5mA$
VBE(sat)	Base Emitter Saturation Voltage	-	0.9	1.1	V	$I_C=100mA, I_B=5mA$
VBE(on)	Base Emitter On Voltage	0.58	-	0.7	V	$V_{CE}=5V, I_C=2mA$
		-	-	0.75	V	$V_{CE}=5V, I_C=10mA$
fT	Transition Frequency	-	150	-	MHz	$V_{CE}=5V, I_C=10mA, f=100MHz$
Cobo	Collector Output Capacitance	-	-	4.5	pF	$V_{CB}=10V, I_E=0, f=1MHz$
NF	Noise Figure	-	1.0	10	dB	$V_{CE}=6V, I_C=0.1mA, R_g=10K\Omega, f=1KHz$

Typical Characteristics Curves



Small Signal General Purpose Transistors (NPN)

BC548A/B/C

Fig.3- $V_{CE(sat)} - I_C$




Fig.4- $f_T - I_C$




Fig.5- $I_B - V_{BE}$






Fig.6- $P_c - T_a$



Small Signal General Purpose Transistors (NPN)

BC548A/B/C

Dimensions in mm



- 1. COLLECTOR
- 2. BASE
- 3. EMITTER

TO-92

Small Signal General Purpose Transistors (NPN)

BC548A/B/C

How to contact us:

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 824-8766 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.

42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

METROBANK PLAZA, 1160 WEST YAN' AN ROAD, SUITE 1503, SHANGHAI, 200052, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931