

PNP General Purpose Transistor		
<p>FEATURES</p> <ul style="list-style-type: none"> • Suitable for AF-Driver stages and low power output stages <p>MECHANICAL DATA</p> <ul style="list-style-type: none"> • Case: SOT-23 Plastic • Case material: “Green” molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl) • Lead Free in RoHS 2002/95/EC Compliant 		

Maximum Ratings @ T_A = 25°C


Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V _{CBO}	-30	V
Collector-Emitter Voltage	V _{CEO}	-25	V
Emitter-Base Voltage	V _{EBO}	-5	V
Collector Current -Continuous	I _C	-0.8	A
Collector Power Dissipation	P _C	300	mW
Junction Temperature	T _J	150	°C
Storage Temperature Range	T _{STG}	-65~+150	°C

Electrical Characteristics @ T_A = 25°C unless otherwise specified

Characteristic	Test Condition	Symbol	Min.	Typ.	Max.	Unit
Collector-base breakdown voltage	I _C =-100μA, I _E =0	V _{CBO}	-30			V
Collector-emitter breakdown voltage	I _C =-10mA, I _B =0	V _{CEO}	-25			V
Emitter-base breakdown voltage	I _E =-100μA, I _C =0	V _{EBO}	-5			V
Collector-base cut-off current	V _{CB} =-25V, I _E =0	I _{CBO}			-0.1	uA
Emitter-base cut-off current	V _{CB} =-4V, I _C =0	I _{EBO}			-0.1	uA
DC current gain	V _{CE} =-1V, I _C =-100mA	h _{FE1}	100		630	
	V _{CE} =-1V, I _C =-300mA	h _{FE1}	60			
Collector-emitter saturation voltage	I _C =-500mA, I _B =-50mA	V _{CE(sat)}			-0.7	V
Base-emitter voltage	V _{CE} =-1V, I _C =-300mA	V _{BE}			-1.2	V
Transition frequency	V _{CE} =-5V, I _C =-10mA, f=50MHz	f _T		100		MHz
Collector output capacitance	V _{CB} =-10V, f=1MHz	C _{ob}		12		pF

REV. 2, Jun-2012, KSPR03

SOT-23 Outline Dimension



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	6°

Device Marking :

Device P/N	Classification of h_{FE}	Marking code
BC808-16	100-250	5E
BC808-25	160-400	5F
BC808-40	250-630	5G

Electrical characteristic curves

Fig.1 Grounded Emitter Output Characteristics (I)




Fig.2 Grounded Emitter Output Characteristics (II)





Fig.3 DC Current Gain vs. Collector Current



**Fig.4 Collector emitter saturation voltage vs. collector current
Base emitter saturation voltage vs. collector current**





Fig.5 Base-Emitter On Voltage



**Fig.6 Collector output capacitance vs. collector-base voltage.
Emitter input capacitance vs. emitter -base voltage**





Fig.7 Gain bandwidth product vs. collector current



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.