



BC847BS

NPN SILICON TRANSISTOR

NPN GENERAL PURPOSE AMPLIFIER

■ DESCRIPTION

The UTC **BC847BS** is a dual NPN transistors; it uses UTC's advanced technology to provide customers high DC current gain, low power dissipation and low collector-emitter saturation voltage.

The UTC **BC847BS** is suitable for a high gain, low noise and general purpose amplifier.

■ FEATURES

- * Low saturation voltage
- * High DC current gain



■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment						Packing
Lead Free	Halogen Free		1	2	3	4	5	6	
BC847BSL-AL6-R	BC847BSG-AL6-R	SOT-363	E1	B1	C2	E2	B2	C1	Tape Reel
BC847BSL-AN6-R	BC847BSG-AN6-R	SOT-563	E1	B1	C2	E2	B2	C1	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

<p>BC847BSG-AL6-R</p> <p>(1)Packing Type</p> <p>(2)Package Type</p> <p>(3)Green Package</p>	<p>(1) R: Tape Reel</p> <p>(2) AL6: SOT-363, AN6: SOT-563</p> <p>(3) G: Halogen Free and Lead Free, L: Lead Free</p>
---	--

■ MARKING



BC847BS

NPN SILICON TRANSISTOR

■ ABSOLUTE MAXIMUM RATINGS (T_A=25°C, unless otherwise noted)

PARAMETER		SYMBOL	RATINGS	UNIT
Collector-Base Voltage		V _{CES}	50	V
Collector-Emitter Voltage		V _{CEO}	45	V
Emitter-Base Voltage		V _{EBO}	6.0	V
Continuous Collector Current		I _C	100	mA
Power Dissipation	SOT-363	P _D	200	mW
	SOT-563		150	mW
Junction Temperature		T _J	-55 ~ +150	°C
Storage Temperature Range		T _{STG}	-55 ~ +150	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	SOT-363	θ _{JA}	625	°C/W
	SOT-563		833	°C/W

■ ELECTRICAL CHARACTERISTICS (T_A=25°C, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector-Base Breakdown Voltage	BV _{CES}	I _C =10μA, I _E =0	50			V
Collector-Emitter Breakdown Voltage	BV _{CEO}	I _C =10mA, I _B =0	45			V
Emitter-Base Breakdown Voltage	BV _{EBO}	I _E =10μA, I _C =0	6.0			V
Collector Cut-Off Current	I _{CBO}	V _{CB} =30V			15	nA
		V _{CB} =30V, T _A =150°C			5.0	μA
Collector-Emitter Saturation Voltage	V _{CE(sat)}	I _C =10mA, I _B =0.5mA			0.25	V
		I _C =100mA, I _B =5.0mA			0.6	V
Base-Emitter Turn-On Voltage	V _{BE(on)}	I _C =2.0mA, V _{CE} =5.0V	0.58		0.70	V
		I _C =10mA, V _{CE} =5.0V			0.77	V
DC Current Gain	h _{FE}	I _C =2.0mA, V _{CE} =5.0V	200		450	
Transition Frequency	f _T	I _C =10mA, V _{CE} =5.0V, f=100MHz	100			MHz
Output Capacitance	C _{ob}	V _{CB} =10V, f=1.0MHz			4.5	pF
Noise Figure	NF	I _C =0.2mA, V _{CE} =5.0V, R _S =2.0kΩ, f=1.0kHz, BW=200Hz			10	dB

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.