



WILLAS



BC868

SOT-89 Plastic-Encapsulate Transistors

TRANSISTOR (NPN)


FEATURES

- High current
- Low voltage

MAXIMUM RATINGS ($T_a=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	32	V
V_{CEO}	Collector-Emitter Voltage	20	V
V_{EBO}	Emitter-Base Voltage	5	V
I_c	Collector Current -Continuous	1	A
P_c	Collector Power Dissipation	500	mW
T_J	Junction Temperature	150	°C
T_{stg}	Storage Temperature	-55~150	°C

SOT-89



1. BASE
2. COLLECTOR
3. Emitter

Pb-Free package is available

RoHS product for packing code suffix "G"

Halogen free product for packing code suffix "H"

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=100\mu\text{A}, I_E=0$	32			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=1\text{mA}, I_B=0$	20			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=100\mu\text{A}, I_C=0$	5			V
Collector cut-off current	I_{CBO}	$V_{CB}=25\text{V}, I_E=0$			0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=5\text{V}, I_C=0$			0.1	μA
DC current gain	$h_{FE(1)}$	$V_{CE}=1\text{V}, I_C=500\text{mA}$	85		375	
	$h_{FE(2)}$	$V_{CE}=1\text{V}, I_C=1\text{A}$	60			
	$h_{FE(3)}$	$V_{CE}=10\text{V}, I_C=5\text{mA}$	50			
Collector-emitter saturation voltage	$V_{CE(\text{sat})}$	$I_C=1\text{A}, I_B=100\text{mA}$			0.5	V
Base-emitter voltage	V_{BE1}	$V_{CE}=10\text{V}, I_C=5\text{mA}$		0.62		V
	V_{BE2}	$V_{CE}=1\text{V}, I_C=1\text{A}$			1	V
Transition frequency	f_T	$V_{CE}=5\text{V}, I_C=10\text{mA}, f=100\text{MHz}$	40			MHz

CLASSIFICATION OF $h_{FE(1)}$

Rank	BC868-10	BC868-16	BC868-25
Range	85-160	100-250	160-375
Marking	CBC	CCC	CDC

Outline Drawing

SOT-89



Dimensions in inches and (millimeters)

Rev.C