


**isc Triacs**
**BCR16PM14L**
**FEATURES**

- With TO-220F package
- Glass passivated triacs in a plastic envelope, for use in Applications requiring high bidirectional transient and blocking voltage capability and high thermal cycling performance. Typical applications include motor control, industrial and domestic lighting, heating and static switching.
- Minimum Lot-to-Lot variations for robust device performance and reliable operation


**ABSOLUTE MAXIMUM RATINGS(Ta=25°C)**

SYMBOL	PARAMETER	MIN	UNIT
V <sub>DRM</sub>	Repetitive peak off-state voltage	700	V
V <sub>RRM</sub>	Repetitive peak off-state voltage	700	V
I <sub>T(RMS)</sub>	RMS on-state current (full sine wave)	16	A
I <sub>TSM</sub>	Non-repetitive peak on-state current t <sub>p</sub> =20ms	160	A
P <sub>GM</sub>	Peak gate power dissipation	5	W
P <sub>G(AV)</sub>	Average gate power dissipation	1	W
T <sub>j</sub>	Operating junction temperature	150	°C
T <sub>stg</sub>	Storage temperature	-40~150	°C

**ELECTRICAL CHARACTERISTICS (T<sub>c</sub>=25°C unless otherwise specified)**

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
I <sub>RRM</sub>	Repetitive peak reverse current	V <sub>R</sub> =V <sub>RRM</sub> , V <sub>R</sub> =V <sub>RRM</sub> , T <sub>j</sub> =150°C		5 5	μA mA
I <sub>DRM</sub>	Repetitive peak off-state current	V <sub>D</sub> =V <sub>DRM</sub> , V <sub>D</sub> =V <sub>DRM</sub> , T <sub>j</sub> =150°C		5 5	μA mA
I <sub>GT</sub>	Gate trigger current	V <sub>D</sub> =12V; I <sub>T</sub> = 0.1A		30	mA
				30	
				30	
V <sub>TM</sub>	On-state voltage	I <sub>T</sub> = 25A		1.5	V
I <sub>H</sub>	Holding current	I <sub>GT</sub> = 0.1A		30	mA
V <sub>GT</sub>	Gate trigger voltage	V <sub>D</sub> =12V; I <sub>T</sub> = 0.1A		1.5	V

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.