

T-29-01

Pro Electron Series

PRO ELECTRON SERIES (Bipolar—see page 5-37 for JFET)

Type No.	Case Style	V _{CE0} [*] (V) Min	V _{CE0} [*] (V) Max	V _{BE0} (V) Min	V _{BE0} (V) Max	I _{CS0} [*] (mA) Max	I _{CS0} [*] (mA) Min	h _{FE} 1 kHz [*] Min	h _{FE} 1 kHz [*] Max	I _C (mA) @ 5 V	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V)		I _C (mA) @ 0.7 V	C _{ob} (pF) Max	f _T (MHz) Min	f _T (MHz) Max	τ _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
												Min	Max								
BC107	TO-18	45	50	6	50	15*	100	40	125	0.01	0.6	0.55	0.7*	100	4.5	150	10			1	04
BC107A	TO-18	45	50	6	50	15*	100	125	260*	2	0.6	0.55	0.7*	100	4.5	150	10			1	04
BC107B	TO-18	45	50	6	50	15*	100	40	240	0.01	0.6	0.55	0.7*	100	4.5	150	10			1	04
BC108	TO-18	20	30	5	30	15*	100	40	125	0.01	0.6	0.55	0.7*	100	4.5	150	10			1	04
BC108A	TO-18	20	30	5	30	15*	100	40	125	0.01	0.6	0.55	0.7*	100	4.5	150	10			1	04
BC108B	TO-18	20	30	5	30	15*	100	40	240	0.01	0.6	0.55	0.7*	100	4.5	150	10			1	04
BC108C	TO-18	20	30	5	30	15*	100	40	450	0.01	0.6	0.55	0.7*	100	4.5	150	10			1	04
BC109	TO-18	20	30	5	30	15*	100	100	240	0.01	0.6	0.55	0.7*	100	4.5	150	10			1	04
BC109B	TO-18	20	30	5	30	15*	100	100	500*	2	0.6	0.55	0.7*	100	4.5	150	10			1	04
BC109C	TO-18	20	30	5	30	15*	100	100	900*	2	0.6	0.55	0.7*	100	4.5	150	10			1	04
BC140	TO-39	40	80*	7	60	100*	100	40	250	100	1.0	1.8*	1.8*	50	25	50	50	850		2	14
BC140-6	TO-39	40	80*	7	60	100*	100	40	100	100	1.0	1.8*	1.8*	50	25	50	50	850		2	14
BC140-10	TO-39	40	80*	7	60	100*	100	63	160	100	1.0	1.8*	1.8*	50	25	50	50	850		2	14
BC140-16	TO-39	40	80*	7	60	100*	100	100	250	100	1.0	1.8*	1.8*	50	25	50	50	850		2	14
BC141	TO-39	60	100*	7	60	100*	100	40	250	100	1.0	1.8*	1.8*	50	25	50	50	850		2	14
BC141-6	TO-39	60	100*	7	60	100*	100	40	100	100	1.0	1.8*	1.8*	50	25	50	50	850		2	14
BC141-10	TO-39	60	100*	7	60	100*	100	63	160	100	1.0	1.8*	1.8*	50	25	50	50	850		2	14

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} [*] V _{CB} (V)		V _{CEO} (V) Min	V _{EB} (V) Min	I _{CS} [*] I _{CB} (mA)		HFE h _{FE} (1 kHz)		I _C & V _{CE} (mA, V)	V _{CE(SAT)} & V _{BE(ON)} [*] (V)		I _C (mA)	C _{ob} (pF) Max	f _T (MHz) Min	f _T (MHz) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
		Min	Max			Min	Max	Min	Max		Min	Max								
BC143	TO-5	60	40	60	5	50	40	20	100	200 2	1.5	1.5	500	20	60	50				63
BC146-1	TO-92 (94)	20	40	20	4	50	40	80	200	2 1	1.5	1.5	500	20	60	50				04
BC146-2	TO-92 (94)	20	40	20	4	50	40	140	350	2 1	1.5	1.5	500	20	60	50				04
BC146-3	TO-92 (94)	20	40	20	4	50	40	280	550	2 1	1.5	1.5	500	20	60	50				04
BC160	TO-39	40*	40	5	40	100	40	40	250	100 1	1.0	1.7*	1A	30	50	50	650		2	67
BC160-6	TO-39	40*	40	5	40	100	40	40	100	100 1	1.0	1.7*	1A	30	50	50	650		2	67
BC160-10	TO-39	40*	40	5	40	100	40	63	160	100 1	1.0	1.7*	1A	30	50	50	650		2	67
BC160-16	TO-39	40*	40	5	40	100	40	100	250	100 1	1.0	1.7*	1A	30	50	50	650		2	67
BC161	TO-39	60*	60	5	60	100	60	40	250	100 1	1.0	1.7*	1A	30	50	50	650		2	67
BC161-6	TO-39	60*	60	5	60	100	60	40	100	100 1	1.0	1.7*	1A	30	50	50	650		2	67
BC161-10	TO-39	60*	60	5	60	100	60	63	160	100 1	1.0	1.7*	1A	30	50	50	650		2	67
BC161-16	TO-39	60*	60	5	60	100	60	100	250	100 1	1.0	1.7*	1A	30	50	50	650		2	67
BC167	TO-92 (94)	60*	50	45	6	15*	50	110	500*	2 5	0.2	0.6	100	4.5	150	10			10	04
BC167A	TO-92 (94)	60*	50	45	6	15*	50	110	260*	2 5	0.2	0.6	100	4.5	150	10			10	04
BC167B	TO-92 (94)	60*	50	45	6	15*	50	110	500*	2 5	0.2	0.6	100	4.5	150	10			10	04
BC168	TO-92 (94)		30	20	5	15*	30	110	900*	2 5	0.2	0.6	100	4.5	150	10			10	04
BC168A	TO-92 (94)		30	20	5	15*	30	110	260*	2 5	0.2	0.6	100	4.5	150	10			10	04
BC168B	TO-92 (94)		30	20	5	15*	30	110	500*	2 5	0.2	0.6	100	4.5	150	10			10	04

T-29-01

TEST CONDITIONS:
 (1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

5

Pro Electron Series

Type No.	Case Style	V _{CE5} [*] V _{CB0} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CE5} [*] I _{CB0} (mA) Max	HFE h _{FE} 1 kHz [*] Min	HFE h _{FE} 1 kHz [*] Max	I _C & V _{CE} (mA) (V) Min	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min	I _C (mA) Min	C _{ob} (pF) Max	f _T (MHz) Min	I _C @ (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC168C	TO-92 (94)		20	5	15 [*]	110 450	2 900 [*]	2 5	0.2 0.6	0.55 0.70 [*]	10 100	4.5	150	10		10	1	04
BC169	TO-92 (94)		20	5	15 [*]	110 240	2 900 [*]	2 5	0.2 0.6	0.55 0.70 [*]	10 100	4.5	150	10		4	1	04
BC169B	TO-92 (94)		20	5	15 [*]	110 240	2 500 [*]	2 5	0.2 0.6	0.55 0.70 [*]	10 100	4.5	150	10		4	1	04
BC169C	TO-92 (94)		20	5	15 [*]	110 450	2 900 [*]	2 5	0.2 0.6	0.55 0.70 [*]	10 100	4.5	150	10		4	1	04
BC177	TO-18	50	45	5	100	110 125	2 500 [*]	2 5	0.18	0.78 0.75 [*] 1.0 [*]	10 10 100	4.5	150	10		10	1	71
BC177A	TO-18	50	45	5	100	110 125	2 260 [*]	2 5	0.18	0.78 0.75 [*] 1.0 [*]	10 10 100	4.5	150	10		10	1	71
BC177B	TO-18	50	45	5	100	110 240	2 500 [*]	2 5	0.18	0.78 0.75 [*] 1.0 [*]	10 10 100	4.5	150	10		10	1	71
BC177VI	TO-18	50	45	5	100	110 75	2 150 [*]	2 5	0.18	0.78 0.75 [*] 1.0 [*]	10 10 100	4.5	150	10		10	1	71
BC178	TO-18	30	25	5	100	110 125	2 900 [*]	2 5	0.18	0.78 0.75 [*] 1.0 [*]	10 10 100	4.5	150	10		10	1	71
BC178A	TO-18	30	25	5	100	110 125	2 260 [*]	2 5	0.18	0.78 0.75 [*] 1.0 [*]	10 10 100	4.5	150	10		10	1	71
BC178B	TO-18	30	25	5	100	110 240	2 500 [*]	2 5	0.18	0.78 0.75 [*] 1.0 [*]	10 10 100	4.5	150	10		10	1	71
BC179	TO-18	25	20	5	100	110 125	2 900 [*]	2 5	0.18	0.78 0.75 [*] 1.0 [*]	10 10 100	4.5	150	10		4	1	71
BC179A	TO-18	25	20	5	100	110 125	2 260 [*]	2 5	0.18	0.78 0.75 [*] 1.0 [*]	10 10 100	4.5	150	10		4	1	71

T-29-01

T-29-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE0} [*] (V) Min	V _{CE0} [*] (V) Min	V _{EB0} (V) Min	I _{CB0} [*] (mA) Max	I _{CB0} [*] (mA) Max	V _{CB} (V)	HFE		I _C & V _{CE} (mA) (V)	V _{CE(SAT)} & V _{BE(ON)} [*] (V) (V)		I _C (mA)	C _{ob} (pF) Max	f _T (MHz) Min Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.	
								Min	Max		Min	Max								Min
BC179B	TO-18	25	20	5	100	2	20	110	500*	2	5	0.18	0.78	10	4.5	150	10	4	1	71
BC182	TO-92 (97)	60	50	5	15	50	50	40	0.01	5	0.6	1.2	100	5	150	10	10	1	04	
								80	100	5	0.25	0.75*	10							1.0*
BC182A	TO-92 (97)	60	50	5	15	50	50	40	0.01	5	0.6	1.2	100	5	150	10	10	1	04	
								80	100	5	0.25	0.70*	10							0.70*
BC182B	TO-92 (97)	60	50	5	15	50	50	40	0.01	5	0.6	1.2	100	5	150	10	10	1	04	
								80	100	5	0.25	0.70*	10							0.70*
BC182L	TO-92 (94)	60	50	5	15	50	50	40	0.01	5	0.6	1.2	100	5	150	10	10	1	04	
								80	100	5	0.25	0.70*	10							0.70*
BC182LA	TO-92 (94)	60	50	5	15	50	50	40	0.01	5	0.6	1.2	100	5	150	10	10	1	04	
								80	100	5	0.25	0.70*	10							0.70*
BC182LB	TO-92 (94)	60	50	5	15	50	50	40	0.01	5	0.6	1.2	100	5	150	10	10	1	04	
								80	100	5	0.25	0.70*	10							0.70*
BC183	TO-92 (97)	45	30	5	15	30	30	40	0.01	5	0.6	1.2	100	5	150	10	10	1	04	
								80	100	5	0.25	0.70*	10							0.70*
BC183A	TO-92 (97)	45	30	5	15	30	30	40	0.01	5	0.6	1.2	100	5	150	10	10	1	04	
								80	100	5	0.25	0.70*	10							0.70*
BC183B	TO-92 (97)*	45	30	5	15	30	30	40	0.01	5	0.6	1.2	100	5	150	10	10	1	04	
								80	100	5	0.25	0.70*	10							0.70*
BC183C	TO-92 (97)	45	30	5	15	30	30	40	0.01	5	0.6	1.2	100	5	150	10	10	1	04	
								80	100	5	0.25	0.70*	10							0.70*

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

T-29-01

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V _{CE} * V _{CB0} (V) Min	V _{CEO} (V) Min	V _{EB0} (V) Min	I _{CE} * I _{CB0} (mA) Max	H _{FE} h _{FE} 1 kHz* Min	I _C & V _{CE} (mA) (V) Max	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)*} (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	f _T (MHz) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC183L	TO-92 (94)	45	30	5	15	40 80 125	0.01 100 900* 2	0.6 0.25	1.2 0.55	100 10 2	5	150	10		10	1	04
BC183LA	TO-92 (94)	45	30	5	15	40 80 125	0.01 100 260* 2	0.6 0.25	1.2 0.55	100 10 2	5	150	10		10	1	04
BC183LB	TO-92 (94)	45	30	5	15	40 80 240	0.01 100 500* 2	0.6 0.25	1.2 0.55	100 10 2	5	150	10		10	1	04
BC183LC	TO-92 (94)	45	30	5	15	40 80 460	0.01 100 900* 2	0.6 0.25	1.2 0.55	100 10 2	5	150	10		10	1	04
BC184	TO-92 (97)	45	30	5	15	100 130 240	0.01 100 900* 2	0.6 0.25	1.2 0.55	100 10 2	5	150	10		4	1	04
BC184B	TO-92 (97)	45	30	5	15	100 130 240	0.01 100 500* 2	0.6 0.25	1.2 0.55	100 10 2	5	150	10		4	1	04
BC184C	TO-92 (97)	45	30	50	15	100 130 460	0.01 100 900* 2	0.6 0.25	1.2 0.55	100 10 2	5	150	10		4	1	04
BC184L	TO-92 (94)	45	30	50	15	100 130 240	0.01 100 900* 2	0.6 0.25	1.2 0.55	100 10 2	5	150	10		4	1	04
BC184LB	TO-92 (94)	45	30	50	15	100 130 240	0.01 100 500* 2	0.6 0.25	1.2 0.55	100 10 2	5	150	10		4	1	04
BC184LC	TO-92 (94)	45	30	50	15	100 130 460	0.01 100 900* 2	0.6 0.25	1.2 0.55	100 10 2	5	150	10		4	1	04
BC204	TO-92 (92)	50	45	5	50	50	450 2	0.3		10					10	1	71
BC207	TO-92 (92)	50	45	5	15	110	450 2	0.25 0.6		10 100	6				10	1	04
BC212	TO-92 (97)	60	50	5	15	60	400* 2	0.6 0.25	1.1 0.6	100 10 2	10	200	10		10	1	63

T-29-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	VCES* VCBO (V) Min	VCEO (V) Min	VEBO (V) Min	ICES* ICBO (nA) Max	HFE hfe @ 1 kHz* Min Max	IC & VCE (mA) (V) Max	VCE(SAT) (V) Max	VBE(SAT) & VBE(ON)* (V)		Cob (pF) Max	fT (MHz) Min Max	toff (ns) Max	NF (dB) Max	Test Conditions	Process No.
									Min	Max						
BC212A	TO-92 (97)	60	50	5	15	100	300* 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	
BC212B	TO-92 (97)	60	50	5	15	200	400* 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	
BC212L	TO-92 (94)	60	50	5	15	40 60 80*	0.01 2 5 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	
BC212LA	TO-92 (94)	60	50	5	15	40 60 100	0.01 2 5 300* 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	
BC212LB	TO-92 (94)	60	50	5	15	40 60 200	0.01 2 5 400* 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	
BC213	TO-92 (97)	45	30	5	15	40 60 80	0.01 2 5 600* 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	
BC213A	TO-92 (97)	45	30	5	15	40 60 100	0.01 2 5 300* 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	
BC213B	TO-92 (97)	45	30	5	15	40 60 200	0.01 2 5 400* 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	
BC213C	TO-92 (97)	45	30	5	15	40 60 350	0.01 2 5 600* 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	
BC213L	TO-92 (94)	45	30	5	15	40 80 80*	0.01 2 5 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	
BC213LA	TO-92 (94)	45	30	5	15	40 80 100	0.01 2 5 300* 2 5	0.6 0.25	1.1 0.72* 2	100 10	200	10		1	63	

TEST CONDITIONS:

(1) IC = 200 μA, VCE = 5V, f = 1 kHz. (2) IC = 100 mA, VCC = 20V, IB1 = IB2 = 5 mA. (3) IC = 200 μA, VCE = 2V, f = 1 kHz. (4) IC = 100 mA, VCC = 10V, IB1 = IB2 = 10 mA. (5) IC = 10 mA, VCC = 3V, IB1 = IB2 = 1 mA. (6) IC = 100 μA, VCE = 5V, f = 1 kHz. (7) IC = 1 mA, VCE = 10V, f = 200 kHz. (8) IC = 1 mA, VCE = 5V, f = 1 kHz. (9) IC = 150 mA, VCC = 6V, IB1 = IB2 = 15 mA. (10) IC = 10 μA, VCE = 5V, f = WB.

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35517 D

T-29-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} [*] V _{CEO} (V) Min	V _{CE} (V) Min	V _{EB} (V) Min	I _{CE} [*] I _{CB} @ (mA) Max	V _{CB} (V)	HFE h _{fe} 1 kHz Min	HFE h _{fe} 1 kHz Max	I _C & V _{CE} (mA) (V)	V _{CE} (SAT) (V) Max	V _{BE} (SAT) & V _{BE} (ON) [*] (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	f _T (MHz) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC213LB	TO-92 (94)	45	30	5	15	30	40	400*	0.01 5 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC213LC	TO-92 (94)	45	30	5	15	30	40	350	0.01 5 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		10	1	63
BC214	TO-92 (97)	45	30	5	15	30	40	600*	0.01 5 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		2	1	63
BC214A	TO-92 (97)	45	30	5	15	30	40	600*	0.01 5 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		2	1	63
BC214B	TO-92 (97)	45	30	5	15	30	40	300*	0.01 5 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		2	1	63
BC214C	TO-92 (97)	45	30	5	15	30	40	400*	0.01 5 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		2	1	63
BC214L	TO-92 (94)	45	30	5	15	30	100	350	0.01 5 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		2	1	63
BC214LB	TO-92 (94)	45	30	5	15	30	100	400	0.01 5 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		2	1	63
BC214LC	TO-92 (94)	45	30	5	15	30	120	600*	0.01 5 2 5	0.6 0.25	1.1 0.72*	100 10 2	10	200	10		2	1	63
BC237-92	TO-92 (97)	50	45	6	50	20	100	140	0.01 5 2 5	0.25	0.77*	10	4.5				10	1	04
BC237A-92	TO-92 (97)	50	45	6	50	20	120	500*	0.01 5 2 5	0.25	0.55 0.70*	10	4.5				10	1	04



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	VCES* VCBO (V) Min	VCEO (V) Min	VEBO (V) Min	ICES* ICBO (nA) Max	HFE h _{FE} 1 kHz*	IC & VCE (mA) & (V)	VCE(SAT) & VBE(ON)* (V) & (V)	VBE(SAT) & VBE(ON)* (V) & (V)	C _{ob} (pF) Max	f _T (MHz) Min	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.		
																	Max	Min
BC237B-92	TO-92 (97)	50	45	6	50	100 140 120 240	0.01 2 100 500*	0.25	0.77* 0.6 0.55 0.70*	4.5				10	1	04		
																	10	100
																	2	5
BC238-92	TO-92 (97)	30	20	5	50	100 140 120 125	0.01 2 100 900*	0.25	0.77* 0.6 0.55 0.70*	4.5				10	1	04		
																	10	100
																	2	5
BC238A-92	TO-92 (97)	30	20	5	50	100 140 120 125	0.01 2 100 260*	0.25	0.77* 0.6 0.55 0.70*	4.5				10	1	04		
																	10	100
																	2	5
BC238B-92	TO-92 (97)	30	20	5	50	100 140 120 240	0.01 2 100 500*	0.25	0.77* 0.6 0.55 0.70*	4.5				10	1	04		
																	10	100
																	2	5
BC238C-92	TO-92 (97)	30	20	5	50	100 140 120 450	0.01 2 100 900*	0.25	0.77* 0.6 0.55 0.70*	4.5				10	1	04		
																	10	100
																	2	5
BC239-92	TO-92 (97)	30	20	5	50	100 140 120 240	0.01 2 100 900*	0.25	0.77* 0.6 0.55 0.70*	4.5				4	1	04		
																	10	100
																	2	5
BC239B-92	TO-92 (97)	30	20	5	50	100 140 120 240	0.01 2 100 500*	0.25	0.77* 0.6 0.55 0.70*	4.5				4	1	04		
																	10	100
																	2	5
BC239C-92	TO-92 (97)	30	20	5	50	100 140 120 450	0.01 2 100 900*	0.25	0.77* 0.6 0.55 0.70*	4.5				4	1	04		
																	10	100
																	2	5
BC261A	TO-18		45		50	100 140 120 125	0.01 2 100 260*	0.25 0.6	0.9 10 100	4.5				6	3	71		
																	10	100
																	2	5

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

5

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35519 D

T-29-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} [*] V _{CB0} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CB0} [*] (nA) Max	H _{FE} I _{hfe} 1 kHz Min	I _C & V _{CE} (mA) (V) Max	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC261B	TO-18		45		50	100 140 120 240	0.01 2 100 500*	0.25 0.6	0.9 100	10 100					6	3	71
BC262A	TO-18		20	5	50	100 140 120 125	0.01 2 100 260*	0.25 0.6	0.9 10	10 100					6	3	71
BC262B	TO-18		20	5	50	100 140 120 240	0.01 2 100 500*	0.25 0.6	0.9 10	10 100					6	3	71
BC263A	TO-18		20	5	50	100 140 120 125	0.01 2 100 260*	0.25 0.6	0.9 10	10 100					2.5	3	71
BC263B	TO-18		20	5	50	100 140 120 125	0.01 2 100 260*	0.25 0.6	0.9 10	10 100					2.5	3	71
BC307-92	TO-92 (97)	50	45	5	100	100 140 120 75	0.01 2 100 500*	0.18	0.78 1.0*	10 100					10	1	71
BC307A-92	TO-92 (97)	50	45	5	100	100 140 120 125	0.01 2 100 260*	0.18	0.78 1.0*	10 100					10	1	71
BC307B-92	TO-92 (97)	50	45	5	100	100 140 120 240	0.01 2 100 500*	0.18	0.78 1.0*	10 100					10	1	71
BC308-92	TO-92 (97)	30	25	5	100	100 140 120 125	0.01 2 100 900*	0.18	0.78 1.0*	10 100					10	1	71
BC308A-92	TO-92 (97)	30	25	5	100	100 140 120 125	0.01 2 100 260*	0.18	0.78 1.0*	10 100					10	1	71

6501130 NATL SEMICOND, (DISCRETE)

28C 35520

D

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} [*] VCBO (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CB0} [*] (mA) Max	H _{FE} h _{FE} 1 kHz [*] Min	H _{FE} h _{FE} 1 kHz [*] Max	I _C & V _{CE} (mA) & (V) Min	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	f _T (MHz) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC308B-92	TO-92 (97)	30	25	5	100	100	400	0.01	0.18	0.78	10					10	1	71
BC308C-92	TO-92 (97)	30	25	5	100	100	400	0.01	0.18	0.78	10					10	1	71
BC309-92	TO-92 (97)	25	20	5	100	100	400	0.01	0.18	0.78	10					4	1	71
BC308B-92	TO-92 (97)	25	20	5	100	100	400	0.01	0.18	0.78	10					4	1	71
BC309C-92	TO-92 (97)	25	20	5	100	100	400	0.01	0.18	0.78	10					4	1	71
BC317	TO-92 (92)	50	45	6	30	110	450	2	0.2	0.77*	10	4				6	1	04
BC317A	TO-92 (92)	50	45	6	30	125	500*	2	0.5	0.72*	2	4				6	1	04
BC317B	TO-92 (92)	50	45	6	30	110	220	2	0.2	0.77*	10	4				6	1	04
BC318	TO-92 (92)	30	20	5	30	110	800	2	0.2	0.77*	10	4				6	1	04
BC318A	TO-92 (92)	30	20	5	30	125	900*	2	0.5	0.72*	2	4				6	1	04

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

T-29-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} [†] V _{CE0} (V) Min	V _{BE0} (V) Min	I _{CE} [†] I _{CE0} (mA) Max	V _{CB} (V)	H _{FE} h _{FE} 1 kHz* Min Max	I _C & V _{CE} (mA) (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC318B	TO-92 (92)	20	5	30	20	200 240	2 500*	0.2 0.5	0.77* 0.57	10 100	4			6	1	04
BC318C	TO-92 (92)	20	5	30	20	100 450	0.01 2	0.2 0.5	0.77* 0.57	10 100	4			6	1	04
BC319	TO-92 (92)	20	5	30	20	40 200	0.01 2	0.2 0.5	0.77* 0.57	10 100	4			4	1	04
BC319B	TO-92 (92)	20	5	30	20	200 240	2 500*	0.2 0.5	0.77* 0.57	10 100	4			4	1	04
BC319C	TO-92 (92)	20	5	30	20	100 420	0.01 2	0.2 0.5	0.77* 0.57	10 100	4			4	1	04
BC327	TO-92 (97)	45	5	100†	45	100 600	100 100	0.7	12*	500 300	4			4	1	67
BC327-10	TO-92 (97)	45	5	100†	45	40 63	300 100	0.7	1.2*	500 300	4			4	1	67
BC327-16	TO-92 (97)	45	5	100†	45	40 100	300 100	0.7	1.2*	500 300	4			4	1	67
BC327-25	TO-92 (97)	45	5	100†	45	160 400	100 100	0.7	1.2*	500 300	4			4	1	67
BC328	TO-92 (97)	25	5	100†	25	100 600	100 100	0.7	1.2	500 300	4			4	1	67
BC328-10	TO-92 (97)	25	5	100†	25	40 63	300 100	0.7	1.2	500 300	4			4	1	67
BC328-16	TO-92 (97)	25	5	100†	25	40 100	300 100	0.7	1.2	500 300	4			4	1	67
BC328-25	TO-92 (97)	25	5	100†	25	160 400	100 100	0.7	1.2	500 300	4			4	1	67
BC337	TO-92 (97)	45	5	100†	45	100 600	100 100	0.7	1.2*	500 300	4			4	1	14
BC337-10	TO-92 (97)	45	5	100†	45	40 63	300 100	0.7	1.2*	500 300	4			4	1	14
BC337-16	TO-92 (97)	45	5	100†	45	40 100	300 100	0.7	1.2*	500 300	4			4	1	14
BC337-25	TO-92 (97)	45	5	100†	45	160 400	100 100	0.7	1.2*	500 300	4			4	1	14

T-29-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} [*]		V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CS} [*]		HFE	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V)		C _{ob} (pF) Max	f _T (MHz)		I _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
		V _{CB0} (V) Min	I _{CB0} (mA) Max			I _C (mA)	V _{CE} (V)			Min	Max		Min	Max				
BC338	TO-92 (97)	30†	100†	25	5	100†	300	40	0.7	1.2*	500	4				4	1	14
BC338-10	TO-92 (97)	30†	100†	25	5	100†	300	40	0.7	1.2*	500	4				4	1	14
BC338-16	TO-92 (97)	30†	100†	25	5	100†	300	63	0.7	1.2*	300	4				4	1	14
BC338-25	TO-92 (97)	30†	100†	25	5	100†	300	40	0.7	1.2*	500	4				4	1	14
BC415	TO-92 (97)	45	15	35	5	15	0.01	40	0.25	1.2*	500					2	10	71
BC415A	TO-92 (97)	45	15	35	5	15	0.01	120	0.25	1.2*	100					2	10	71
BC415B	TO-92 (97)	45	15	35	5	15	0.01	100	0.25	1.2*	100					2	10	71
BC415C	TO-92 (97)	45	15	35	5	15	0.01	180	0.25	1.2*	100					2	10	71
BC485	TO-92 (97)	45	100	45	5	100	1A	15	0.5	1.2*	500	4				4	1	14
BC485A	TO-92 (97)	45	100	45	5	100	1A	40	0.5	1.2*	300	4				4	1	14
BC485B	TO-92 (97)	45	100	45	5	100	1A	100	0.5	1.2*	300	4				4	1	14
BC485L	TO-92 (97)	45	100	45	5	100	1A	160	0.5	1.2*	300	4				4	1	14
BC547	TO-92 (97)	50	10	45	6	10	2	125	0.25	0.77*	100	4.5				10	1	04
BC547A	TO-92 (97)	50	10	45	6	10	2	125	0.6	0.55	0.70*	4.5				10	1	04

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35523

D

T-29-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} * V _{CB} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CEB0} * I _{CB0} (mA) Max	HFE h _{FE} 1 kHz*	I _C & V _{CE} (mA) & (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} * (V)		C _{ob} (pF) Max	f _T (MHz) Min	I _C @ (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
									Min	Max							
BC547B	TO-92 (97)	50	45	6	10	240	500*	0.25 0.6	0.77*	100	4.5			10	1	04	
BC547C	TO-92 (97)	50	45	6	10	450	900*	0.25 0.6	0.77*	100	4.5			10	1	04	
BC548	TO-92 (97)	30	20	5	10	125	900*	0.25 0.6	0.77*	100	4.5			10	1	04	
BC548A	TO-92 (97)	30	20	5	10	125	260*	0.25 0.6	0.77*	100	4.5			10	1	04	
BC548B	TO-92 (97)	30	20	5	10	240	500*	0.25 0.6	0.77*	100	4.5			10	1	04	
BC548C	TO-92 (97)	30	20	5	10	450	900*	0.25 0.6	0.77*	100	4.5			10	1	04	
BC549	TO-92 (97)	30	20	5	10	240	900*	0.25 0.6	0.77*	100	4.5			4	1	04	
BC549B	TO-92 (97)	30	20	5	10	240	500*	0.25 0.6	0.77*	100	4.5			4	1	04	
BC549C	TO-92 (97)	30	20	5	10	450	900*	0.25 0.6	0.77*	100	4.5			4	1	04	
BC550	TO-92 (97)	50	45	5	10	240	900*	0.25 0.6	0.77*	100				3	1	04	
BC550B	TO-92 (97)	50	45	5	10	240	500*	0.25 0.6	0.77*	100				3	1	04	
BC550C	TO-92 (97)	50	45	5	10	450	900*	0.25 0.6	0.77*	100				3	1	04	
BC557	TO-92 (97)	50	45	5	100	75	260*	0.3 0.65	0.82* 0.6	100 0.75*				10	1	71	



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE0} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CE0} (mA) Max	HFE h _{FE} 1 kHz Min	HFE h _{FE} 1 kHz Max	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min	V _{BE(ON)} (V) Max	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC557A	TO-92 (97)	45	50	5	100	125	260*	0.3 0.65	0.82*	0.75*	10					10	1	71
BC557B	TO-92 (97)	45	50	5	100	240	500*	0.3 0.65	0.82*	0.75*	10					10	1	71
BC558	TO-92 (97)	25	30	5	100	75	500*	0.3 0.65	0.82*	0.75*	10					10	1	71
BC558A	TO-92 (97)	25	30	5	100	125	260*	0.3 0.65	0.82*	0.75*	10					10	1	71
BC558B	TO-92 (97)	25	30	5	100	240	500*	0.3 0.65	0.82*	0.75*	10					10	1	71
BC558C	TO-92 (97)	25	30	5	100	450	900*	0.3 0.65	0.82*	0.75*	10					10	1	71
BC559	TO-92 (97)	20	25	5	100	125	500*	0.3 0.65	0.82*	0.75*	10					4	1	71
BC559A	TO-92 (97)	20	25	5	100	125	260*	0.3 0.65	0.82*	0.75*	10					4	1	71
BC559B	TO-92 (97)	20	25	5	100	240	500*	0.3 0.65	0.82*	0.75*	10					4	1	71
BC559C	TO-92 (97)	20	25	5	100	450	900*	0.3 0.65	0.82*	0.75*	10					4	1	71
BC560	TO-92 (97)	45	50	5	100	125	500*	0.3 0.65	0.82*	0.75*	10					2	1	71

T-29-01

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35525

D

T-29-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} [*] (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CB0} [*] (mA) Max	V _{CB} (V)	HFE h _{FE} 1 kHz [*] Min Max	I _C (mA) Max	V _{CE} (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min Max	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min Max	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BC560A	TO-92 (97)	50	45	5	100	45	125 260*	2	5	0.3, 0.65	0.82* 0.6 0.75* 2	10 100					2	1	71
BC560B	TO-92 (97)	50	45	5	100	45	240 500*	2	5	0.3 0.65	0.82* 0.6 0.75* 2	10 100					2	1	71
BC560C	TO-92 (97)	50	45	5	100	45	450 900*	2	5	0.3 0.65	0.82* 0.6 0.75* 2	10 100					2	1	71
BCX56	TO-92 (97)		32	7	10	32	120 630 80 1000	2 10	5					125	10	800	6	3/4	04
BCX56-7	TO-92 (97)		32	7	10	32	120 220 80 400	2 10	5					125	10	800	6	3/4	04
BCX56-8	TO-92 (97)		32	7	10	32	20 310 180 400	0.01 2	5					125	10	800	6	3/4	04
BCX56-9	TO-92 (97)		32	7	10	32	40 460 250 630	0.01 2	5					125	10	800	6	3/4	04
BCX56-10	TO-92 (97)		32	7	10	32	100 630 380 1000	0.01 2	5					125	10	800	6	3/4	04
BCX59	TO-92 (97)		45	7			120 630 80 1000	2 10	5	0.5	1.0	100		125	10	800		5	04
BCX59-7	TO-92 (97)		45	7			120 220 80 400	2 10	5	0.5	1.0	100		125	10	800		5	04
BCX59-8	TO-92 (97)		45	7			20 310 180 400	0.01 2	5	0.5	1.0	100		125	10	800		5	04
BCX59-9	TO-92 (97)		45	7			40 460 250 630	0.01 2	5	0.5	1.0	100		125	10	800		5	04



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} [*] V _{CB} (V) Min	V _{CEO} (V) Min	V _{EB} (V) Min	I _{CS} [*] I _{CB} (mA) Max	HFE h _{FE} @ 1 kHz [*] Min Max	I _C & V _{CE} (V) (mA)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min Max	C _{ob} (pF) Max	f _T (MHz) Min Max	I _C (mA) @ I _C Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BCX55-10	TO-92 (97)		45	7		100 380 240 60	0.01 2 10 100	0.5	1.0		125	10	800		5	04
BCX78	TO-92 (97)		32	5		120 80 40	2 10 100	0.6	1.0							71
BCX78-7	TO-92 (97)		32	5		120 80 40	2 10 100	0.6	1.0							71
BCX78-8	TO-92 (97)		32	5		30 180 120 45	0.01 2 10 100	0.6	1.0							71
BCX78-9	TO-92 (97)		32	5		40 250 160 60	0.01 2 10 100	0.6	1.0							71
BCX78-10	TO-92 (97)		32	5		100 380 240 60	0.01 2 10 100	0.6	1.0							71
BCX79	TO-92 (97)		45	5		80 120 60	10 100 1	0.6	1.0							71
BCX79-7	TO-92 (97)		45	5		120 80 40	2 10 100	0.6	1.0							71
BCX79-8	TO-92 (97)		45	5		120 40 30 180	10 100 0.01 2 5	0.6	1.0							71
BCX79-9	TO-92 (97)		45	5		160 60 40 250	10 100 0.01 2 5	0.6	1.0							71

T-29-01

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CC} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CC} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CC} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CC} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

5

Pro Electron Series

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35527 D

T-29-01

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V _{CE0} [*] (V) Min	V _{CE0} [*] (V) Min	V _{EB0} (V) Min	I _{CE0} [*] (mA) Max	I _{CB0} (mA) Max	HFE h _{FE} 1 kHz [*]	I _C & V _{CE} (mA) & (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.	
																			Max
BCX79-10	TO-92 (97)	45	45	5			240 60 100 380	1000 100 0.01 5	0.6	1.0	100							71	
BCY56	TO-18	45	45	5	100		40 100 125 40	10 5 2 5	0.6	0.7*	2					5	1	04	
BCY57	TO-18	25	20	5	100		200 200 240 100	10 5 2 0.01		0.6	0.7*					5	1	04	
BCY58	TO-18		32	7	10 ¹		40 80 125	100 10 2	0.35 0.7	0.6 0.75 0.55	10 100 2	6	125	10	800		6	4/1	04
BCY58-7	TO-18		32	7	10 ¹		40 80 125	100 10 2	0.35 0.7	0.6 0.75 0.55	10 100 2	6	125	10	800		6	4/1	04
BCY58-8	TO-18		32	7	10 ¹		40 80 175	100 10 350*	0.35 0.7	0.6 0.75 0.55	10 100 2	6	125	10	800		6	4/1	04
BCY58-9	TO-18		32	7	10 ¹		40 80 250	100 10 500*	0.35 0.7	0.6 0.75 0.55	10 100 2	6	125	10	800		6	4/1	04
BCY58-10	TO-18		32	7	10 ¹		40 80 350	100 10 700*	0.35 0.7	0.6 0.75 0.55	10 100 2	6	125	10	800		6	4/1	04
BCY59	TO-18		45	7	10 ¹		40 80 125	100 10 700*	0.35 0.7	0.6 0.75 0.55	10 100 2	6	125	10	800		6	4/1	04
BCY59-7	TO-18		45	7	10 ¹		40 80 125	100 10 250*	0.35 0.7	0.6 0.75 0.55	10 100 2	6	125	10	800		6	4/1	04
BCY59-8	TO-18		45	7	10 ¹		40 80 175	100 10 350*	0.35 0.7	0.6 0.75 0.55	10 100 2	6	125	10	800		6	4/1	04
BCY59-9	TO-18		45	7	10 ¹		40 80 250	100 10 500*	0.35 0.7	0.6 0.75 0.55	10 100 2	6	125	10	800		6	4/1	04

6501130 NATL SEMICOND, (DISCRETE)

28C 35528



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	VCES* VCBO (V) Min	VCEO (V) Min	VEBO (V) Min	ICES* ICBO e (mA) Max	HFE		IC & VCE (mA) & (V)	VCE(SAT) & VBE(ON)* (V)		VBE(SAT) & VBE(ON)* e (mA)		Cob (pF) Max	fT (MHz)		toff (ns) Max	NF (dB) Max	Test Conditions	Process No.
						Min	Max		Min	Max	Min	Max		Min	Max				
BCY59-10	TO-18		45	7	10†	45	40 80 350	100 1000 700*	1 1 5	0.35 0.7	0.6 0.75 0.55	0.85 1.2 0.7*	6	125	10	800	6	4/1	04
BCY70	TO-18	50	40	5	10	40	40 45 50 15	0.1 1 10 50	1 1 1 1	0.25	0.6	0.9	6	250	10	420	6	5/6	71
BCY71	TO-18	45	45	5	500	45	40 80 90	0.01 0.1 1	1 1 1	0.25	0.6	0.9	6	200	10		2	6	71
BCY71A	TO-18	45	45	5	500	45	100	600	10	0.5	1.2	50		300	10	420	2	6	71
BCY72	TO-18	25	25	5	500	20	40	100	1	0.25	0.6	0.9	6	200	10	420	6	5/6	71
BD135	TO-126	45	45	5	100	30	25	500	2	0.5	1.2	50		50	50	420	6	5/6	37
BD135-6	TO-126	45	45	5	100	30	40	250	2	0.5	1.0*	500		50	50	420	6	5/6	37
BD135-10	TO-126	45	45	5	100	30	40	100	150	0.5	500	500		50	50				37
BD135-16	TO-126	45	45	5	100	30	40	250	2	0.5	500	500		50	50				37
BD136	TO-126	45	45	5	100	30	40	100	150	0.5	500	500		50	50				77
BD136-6	TO-126	45	45	5	100	30	40	250	2	0.5	500	500		50	50				77
BD136-10	TO-126	45	45	5	100	30	40	100	150	0.5	500	500		50	50				77
BD136-16	TO-126	45	45	5	100	30	40	250	2	0.5	500	500		50	50				77
BD137	TO-126	60	60	5	100	30	40	160	150	0.5	500	500		50	50				38

7-33-01

TEST CONDITIONS:

(1) IC = 200 μA, VCE = 5V, f = 1 kHz. (2) IC = 100 mA, VCC = 20V, IB1 = IB2 = 5 mA. (3) IC = 200 μA, VCE = 2V, f = 1 kHz. (4) IC = 100 mA, VCC = 10V, IB1 = IB2 = 10 mA. (5) IC = 10 mA, VCC = 3V, IB1 = IB2 = 1 mA. (6) IC = 100 μA, VCE = 5V, f = 1 kHz. (7) IC = 1 mA, VCE = 10V, f = 200 kHz. (8) IC = 1 mA, VCE = 5V, f = 1 kHz. (9) IC = 150 mA, VCC = 6V, IB1 = IB2 = 15 mA. (10) IC = 10 μA, VCE = 5V, f = WB.

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35529 D

T-33-01

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V _{CE0} [*] (V) Min	V _{CE0} [*] (V) Max	V _{BE0} (V) Min	V _{BE0} (V) Max	I _{CE0} [*] (mA) Min	I _{CE0} [*] (mA) Max	H _{FE} 1 kHz Min	H _{FE} 1 kHz Max	I _C & V _{CE} (mA) & (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Max	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	f _T (MHz) Max	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD137-6	TO-126	60	60	5	30	100	30	40	100	150	0.5		500		50	50	50				38
BD137-10	TO-126	60	60	5	30	100	30	63	160	150	0.5		500		50	50	50				38
BD138	TO-126	60	60	5	30	100	30	25	160	150	0.5		500		50	50	50				78
BD138-6	TO-126	60	60	5	30	100	30	25	160	150	0.5		500		50	50	50				78
BD138-10	TO-126	60	60	5	30	100	30	25	160	150	0.5		500		50	50	50				78
BD139	TO-126	80	80	5	30	100	30	25	160	150	0.5		500		50	50	50				39
BD139-6	TO-126	80	80	5	30	100	30	25	160	150	0.5	1.0*	500		50	50	50	420	6	5/6	39
BD139-10	TO-126	80	80	5	30	100	30	25	160	150	0.5	1.0*	500		50	50	50				39
BD140	TO-126	80	80	5	30	100	30	25	160	150	0.5	1.0*	500		50	50	50	420	6	5/6	79
BD157	TO-126	250	250	100	275	100	275	30	240	50											36
BD158	TO-126	300	300	100	325	100	325	30	240	50											36
BD159	TO-126	350	350	100	325	100	325	30	240	50											36
BD185	TO-126	30	30	100	40	100	40	40	500	2	1.0	1.2*	2A								4F
BD186	TO-126	30	30	100	40	100	40	40	500	2	1.0	1.5*	2A								5F
BD187	TO-126	45	45	100	55	100	55	40	500	2	1.0	1.5*	2A								4F
BD188	TO-126	45	45	100	55	100	55	40	500	2	1.0	1.5*	2A								5F
BD189	TO-126	60	60	100	70	100	70	40	500	2	1.0	1.5*	2A								4F
BD190	TO-126	60	60	100	70	100	70	40	500	2	1.0	1.5*	2A								5F
BD201	TO-220	60	60	5	40	10	40	30	3A	2	1.0	1.5*	3A		3		300	420	6	5/6	4A
BD202	TO-220	60	60	5	40	10	40	30	3A	2	1.0	1.5*	3A		3		300	420	6	5/6	5A

F-33-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} * V _{CB} (V) Min	V _{CE} (V) Min	V _{BO} (V) Min	I _{CB} * I _{CB} (mA) Max	HFE h _{FE} 1 kHz*	I _C & V _{CE} (V)	V _{CE} (SAT) (V) Max	V _{BE} (SAT) & V _{BE} (ON)* (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	f _T (MHz) Max	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD203	TO-220	60	60	5		30 30	2 1	2 2	1.0	3A		3		300				4A
BD204	TO-220	60	60	5	10 μA	30	2A 1A	2 1	1.0	1.5*								5A
BD220	TO-220		70			30	120 500	4 4	1.0	1.1*								4F
BD221	TO-220		40			30	120 1A	4 4	1.0	1.3*								4F
BD222	TO-220		60			20	80 1.5A	4 4	1.0	1.5*								4F
BD223	TO-220	70				30	120 300	4 4	1.0	1.1*								5F
BD224	TO-220		40			30	120 1A	4 4	1.0	1.3*								5F
BD225	TO-220		60			20	80 1.5A	4 4	1.0	1.5*								5F
BD233	TO-126	45	45		100 μA	25	1A 150	2 2	0.6	1.3*		3		250	420	6	5/6	4F
BD234	TO-126	45	45		100 μA	25	1A 150	2 2	0.6	1.3*		3		250	420	6	5/6	5F
BD235	TO-126	60	60		100 μA	25	1A 150	2 2	0.6	1.3*		3		250	420	6	5/6	4F
BD236	TO-126	60	60		100 μA	25	1A 150	2 2	0.6	1.3*		3		250	420	6	5/6	5F
BD237	TO-126	80	80		100 μA	25	1A 150	2 2	0.6	1.3*		3		250	420	6	5/6	4F
BD238	TO-126	80	80		100 μA	25	1A 150	2 2	0.6	1.3*		3		250	420	6	5/6	5F
BD239	TO-220		45		200 μA*	15 40	1A 200	4 4	0.7	1.3*		3		200	420	6	5/6	4F
BD239A	TO-220		60		200 μA*	15 40	1A 200	4 4	0.7	1.3*		3		200	420	6	5/6	4F
BD239B	TO-220		80		200 μA*	15 40	1A 200	4 4	0.7	1.3*		3		200	420	6	5/6	4F
BD239C	TO-220		100		200 μA*	15 40	1A 200	4 4	0.7	1.3*		3		200	420	6	5/6	4F
BD240	TO-220		45		200 μA*	15 40	1A 200	4 4	0.7	1.3*		3		200	420	6	5/6	5F
BD240A	TO-220	80	60		200 μA*	15 40	1A 200	4 4	0.7	1.3*		3		200	420	6	5/6	5F

TEST CONDITIONS:
 (1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = 50.

Pro Electron Series

5

Pro Electron Series

Type No.	Case Style	V _{CE} * V _{CB0} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CB0} * (mA) Max	I _{CB0} * (mA) Max	H _{FE} h _{FE} 1 kHz Min Max	I _C & V _{CE} (mA) (V) Min Max	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min Max	I _C (mA) Min Max	C _{ob} (pF) Max	f _T (MHz) Min Max	I _C (mA) Min Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD240B	TO-220	80	80		200 μA* 80	200 μA* 80	15 40	1A 4 200 4	0.7	1.3*	1A		3	200	420	6	5/6	5F
BD240C	TO-220	80	100		200 μA* 100	200 μA* 100	15 40	1A 4 200 4	0.7	1.3*	1A		3	200	420	6	5/6	5F
BD241	TO-220	80	45		200 μA* 45	200 μA* 45	10 25	3A 4 1A 4	1.3	1.8*	3A		3	500	420	6	5/6	4F
BD241A	TO-220	80	60		200 μA* 60	200 μA* 60	10 25	3A 4 1A 4	1.3	1.8*	3A		3	500	420	6	5/6	4F
BD241B	TO-220	80	80		200 μA* 80	200 μA* 80	10 25	3A 4 1A 4	1.3	1.8*	3A		3	500	420	6	5/6	4F
BD241C	TO-220	80	100		200 μA* 100	200 μA* 100	10 25	3A 4 1A 4	1.3	1.8*	3A		3	500	420	6	5/6	4F
BD242	TO-220	80	45		200 μA* 45	200 μA* 45	10 25	3A 4 1A 4	1.2	1.8*	3A		3	500	420	6	5/6	5E
BD242A	TO-220	80	60		200 μA* 60	200 μA* 60	10 25	3A 4 1A 4	1.2	1.8*	3A		3	500	420	6	5/6	5E
BD242B	TO-220	80	80		200 μA* 80	200 μA* 80	10 25	3A 4 1A 4	1.2	1.8*	3A		3	500	420	6	5/6	5E
BD242C	TO-220	80	100		200 μA* 100	200 μA* 100	10 25	3A 4 1A 4	1.2	1.8*	3A		3	500	420	6	5/6	5E
BD243	TO-220		45		400 μA* 45	400 μA* 45	30 15	300 4 3A 4					3	500				4A
BD243A	TO-220		60		400 μA* 60	400 μA* 60	30 15	300 4 3A 4					3	500				4A
BD243B	TO-220		80		400 μA* 80	400 μA* 80	30 15	300 4 3A 4					3	500				4A
BD243C	TO-220		100		400 μA* 100	400 μA* 100	30 15	300 4 3A 4					3	500				4A
BD244	TO-220		45		400 μA* 45	400 μA* 45	30 15	300 4 3A 4										4A
BD244A	TO-220		60		400 μA* 60	400 μA* 60	30 15	300 4 3A 4										5A
BD244B	TO-220		80		400 μA* 80	400 μA* 80	30 15	300 4 3A 4										5A
BD244C	TO-220		100		400 μA* 100	400 μA* 100	30 15	300 4 3A 4										5A
BD344	TO-126	60	60	5	500 60	500 60	60 40	50 1 200 1	0.4		200	20	50	50				78

PRO ELECTRON SERIES (Continued)

T-33-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE0} [*] (V)		V _{BE0} (V)	I _{CB0} (mA)	I _{CB0} @ (mA)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V)		I _C (mA)	C _{ob} (pF) Max	f _T (MHz)		t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
		Min	Max					Min	Max			Min	Max				
BD345	TO-126	60	60	5	500	50	0.4			200	20	50	50				38
BD346	TO-220	60	60		10 μA	140				250	200	4	250				5A
BD347	TO-220	60	60		10 μA	140				250	200	4	250				4A
BD348	TO-126	80	80	5	500	100	0.5			250	17	50	50				79
BD349	TO-126	80	80		500	100	0.5		1.5*	250	15	50	50				39
BD370A	TO-237 (91)	80	45		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370A-10	TO-237 (91)	80	45		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370A-16	TO-237 (91)	80	45		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370A-25	TO-237 (91)	80	45		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370B	TO-237 (91)	80	60		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370B-10	TO-237 (91)	80	60		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370B-16	TO-237 (91)	80	60		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370B-25	TO-237 (91)	80	60		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370C	TO-237 (91)	80	80		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370-6	TO-237 (91)	80	80		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370C-10	TO-237 (91)	80	80		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78
BD370C-16	TO-237 (91)	80	80		100	500	0.7		1.2*	1A	30	50	200	420	6	5/6	78

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

Type No.	Case Style	V _{CE} [*] V _{CE0} (V) Min	V _{BE0} (V) Min	I _{CE} [*] I _{CE0} (mA) Max	V _{CB} (V)	H _{FE} h _{FE} 1 kHz Min	H _{FE} h _{FE} 1 kHz Max	I _C & V _{CE} (mA) & (V) Min	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD370D	TO-237 (91)	80	100	100	80	25	40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	79
BD370D-6	TO-237 (91)	80	100	100	80	25	40	500 2 100 1	0.7	1.2*	1A	30	50	200	420	6	5/6	79
BD370D-10	TO-237 (91)	80	100	100	80	25	63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/6	79
BD371A	TO-237 (91)	80	45	100	45	25	40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371A-10	TO-237 (91)	80	45	100	45	25	63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371A-16	TO-237 (91)	80	45	100	45	25	100	500 2 250 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371A-25	TO-237 (91)	80	45	100	45	25	180	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371B	TO-237 (91)	80	60	100	60	25	40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371B-10	TO-237 (91)	80	60	100	60	25	63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371B-16	TO-237 (91)	80	60	100	60	25	100	500 2 250 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371B-25	TO-237 (91)	80	60	100	60	25	160	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371C	TO-237 (91)	80	80	100	80	25	40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371C-6	TO-237 (91)	80	80	100	80	25	40	500 2 100 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371C-10	TO-237 (91)	80	80	100	80	25	63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371C-16	TO-237 (91)	80	80	100	80	25	100	500 2 250 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38
BD371D	TO-237 (91)	80	100	100	100	25	40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	39
BD371D-6	TO-327 (91)	80	100	100	100	25	40	500 2 100 1	0.7	1.2*	1A	30	50	200	420	6	5/6	39
BD371D-10	TO-237 (91)	80	100	100	100	25	63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/6	39
BD372A	TO-237 (90)	80	45	100	45	25	40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	78

T-33-01

PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CEO} [*] (V) Min	V _{CE0} [*] (V) Min	V _{BE0} [*] (V) Min	I _{CS} [*] I _{CB0} (mA) Max	V _{CB} (V)	HFE		I _C & V _{CE}		V _{CE(SAT)} & V _{BE(ON)} [*]		C _{ob} (pF) Max	f _T		t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
							Min	Max	Min	Max	Min	Max		Min	Max				
BD372A-10	TO-237 (90)	45	80	45	100	45	25 63	500 160	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372A-16	TO-237 (90)	45	80	45	100	45	100	500 250	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372A-25	TO-237 (90)	45	80	45	100	45	160	500 400	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372B	TO-237 (90)	60	80	60	100	60	40	500 400	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372B-10	TO-237 (90)	60	80	60	100	60	25 63	500 160	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372B-16	TO-237 (90)	60	80	60	100	60	100	500 250	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372B-25	TO-237 (90)	60	80	60	100	60	25	500 400	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372C	TO-237 (90)	80	80	80	100	80	40	500 400	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372C-6	TO-237 (90)	80	80	80	100	80	25	500 100	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372C-10	TO-237 (90)	80	80	80	100	80	63	500 160	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372C-16	TO-237 (90)	100	80	100	100	100	25	500 250	2 1	0.7	1.2*	30	50 200	420	6	78			
BD372D	TO-237 (90)	100	80	100	100	100	40	500 400	2 1	0.7	1.2*	30	50 200	420	6	79			
BD372D-6	TO-237 (90)	100	80	100	100	100	25	500 100	2 1	0.7	1.2*	30	50 200	420	6	79			
BD372D-10	TO-237 (90)	100	80	100	100	100	40	500 100	2 1	0.7	1.2*	30	50 200	420	6	79			
BD373A	TO-237 (90)	45	80	45	100	45	25	500 160	2 1	0.7	1.2*	30	50 200	420	6	38			
BD373A-10	TO-237 (90)	45	80	45	100	45	40	500 400	2 1	0.7	1.2*	30	50 200	420	6	38			
BD373A-16	TO-237 (90)	45	80	45	100	45	25	500 160	2 1	0.7	1.2*	30	50 200	420	6	38			

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

Type No.	Case Style	VCES* VCBO (V) Min	VCEO (V) Min	VEBO (V) Min	ICES* ICBO @ (mA) Max	HFE I _{hfe} 1 kHz*	IC & VCE (mA) & (V)	VCE(SAT) & VBE(ON)* (V)		VBE(SAT) & VBE(ON)* (V)		Cob (pF) Max	f _T (MHz) Min Max	I _C (mA) @	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
								Max	Min	Max	Min							
BD373A-25	TO-237 (90)	80	45		100	25 160	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38	
BD373B	TO-237 (90)	80	80		100	25 40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38	
BD373B-10	TO-237 (90)	80	60		100	25 63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/8	38	
BD373B-16	TO-237 (90)	80	60		100	25 100	500 2 250 1	0.7	1.2*	1A	30	50	200	420	6	5/8	38	
BD373B-25	TO-237 (90)	80	60		100	25 160	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38	
BD373C	TO-237 (90)	80	80		100	25 40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38	
BD373C-5	TO-237 (90)	80	80		100	25 40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38	
BD373C-10	TO-237 (90)	80	80		100	25 63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38	
BD373C-16	TO-237 (90)	80	80		100	25 100	500 2 250 1	0.7	1.2*	1A	30	50	200	420	6	5/6	38	
BD373D	TO-237 (90)	80	100		100	25 40	500 2 400 1	0.7	1.2*	1A	30	50	200	420	6	5/6	39	
BD373D-6	TO-237 (90)	80	100		100	25 40	500 2 100 1	0.7	1.2*	1A	30	50	200	420	6	5/6	39	
BD373D-10	TO-237 (90)	80	100		100	25 63	500 2 160 1	0.7	1.2*	1A	30	50	200	420	6	5/6	39	
BD375	TO-126	50	45		2 μA	20 40	1A 2 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38	
BD375-6	TO-126	50	45		2 μA	20 40	1A 2 100 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38	
BD375-10	TO-126	50	45		2 μA	20 63	1A 2 160 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38	
BD375-16	TO-126	50	45		2 μA	20 100	1A 2 250 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38	
BD375-25	TO-126	50	45		2 μA	20 150	1A 2 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38	
BD376	TO-126	50	45		2 μA	20 40	1A 2 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78	
BD376-6	TO-126	50	45		2 μA	20 40	1A 2 100 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78	

T-33-01

T-33-01

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V _{CE0} [*] V _{CB0} (V) Min	V _{EB0} (V) Min	I _{CB0} [*] (mA) Max	V _{CB} (V)	HFE h _{FE} 1 kHz [*] Min Max	I _C & V _{CE} (mA) & (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min Max	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min Max	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD376-10	TO-126	50	45	2 μA	45	20 63	1A 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78
BD376-16	TO-126	50	45	2 μA	45	100	1A 200 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78
BD376-25	TO-126	50	45	2 μA	45	20 150	1A 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78
BD377	TO-126	75	60	2 μA	60	40	1A 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38
BD377-6	TO-126	75	60	2 μA	60	20 40	1A 100 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38
BD377-10	TO-126	75	60	2 μA	60	20 63	1A 160 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38
BD377-16	TO-126	75	60	2 μA	60	100	1A 250 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38
BD377-25	TO-126	75	60	2 μA	60	20 150	1A 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	38
BD378	TO-126	75	60	2 μA	60	20 40	1A 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78
BD378-6	TO-126	75	60	2 μA	60	20 40	1A 100 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78
BD378-10	TO-126	75	60	2 μA	60	20 63	1A 160 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78
BD378-16	TO-126	75	60	2 μA	60	20 100	1A 250 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78
BD378-25	TO-126	75	60	2 μA	60	20 150	1A 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	78
BD379	TO-126	100	80	2 μA	80	20 40	1A 375 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	39
BD379-6	TO-126	100	80	2 μA	80	20 40	1A 100 150 2	1.0	1.5*	1A	30	50	200	420	6	5/6	39

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

5

DataSheet4U.com

Pro Electron Series

Type No.	Case Style	V _{CE0} [*] V _{CE0} (V) Min	V _{BE0} (V) Min	ICES [*] I _{CB0} (mA) Max	HFE h _{fe} @ 1 kHz Min	HFE h _{fe} @ 1 kHz Max	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD379-10	TO-126	100	80	2 μA	20	150	1.0	1.5*	1A	30	50	200	420	6	5/6	39
BD379-16	TO-126	100	80	2 μA	63	150	1.0	1.5*	1A	30	50	200	420	6	5/6	39
BD379-25	TO-126	100	80	2 μA	100	250	1.0	1.5*	1A	30	50	200	420	6	5/6	39
BD380	TO-126	100	80	2 μA	150	375	1.0	1.5*	1A	30	50	200	420	6	5/6	79
BD380-6	TO-126	100	80	2 μA	40	375	1.0	1.5*	1A	30	50	200	420	6	5/6	79
BD380-10	TO-126	100	80	2 μA	40	100	1.0	1.5*	1A	30	50	200	420	6	5/6	79
BD380-16	TO-126	100	80	2 μA	20	160	1.0	1.5*	1A	30	50	200	420	6	5/6	79
BD380-25	TO-126	100	80	2 μA	63	250	1.0	1.5*	1A	30	50	200	420	6	5/6	79
BD433	TO-126	22†	5	100 μA	100	375	0.5	1.1*	2A	30	3	250	420	6	5/6	4E
BD434	TO-126	22†	5	100 μA	50	475	0.5	1.1*	2A	30	3	250	420	6	5/6	5E
BD435	TO-126	32†	5	100 μA	85	500	0.5	1.1*	2A	30	3	250	420	6	5/6	4E
BD436	TO-126	32†	5	100 μA	40	500	0.5	1.1*	2A	30	3	250	420	6	5/6	5E
BD437	TO-126	45†	5	100 μA	50	236	0.6	1.2*	2A	30	3	250	420	6	5/6	4E
BD438	TO-126	45†	5	100 μA	40	500	0.6	1.2*	2A	30	3	250	420	6	5/6	5E
BD439	TO-126	60†	5	100 μA	25	236	0.8	1.5*	2A	30	3	250	420	6	5/6	4E

T-33-01

PRO ELECTRON SERIES (Continued)



T=33-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE0} (V)		V _{BE0} (V)	I _{CB0} (mA)		h _{FE} @ 1 kHz		I _C & V _{CE} (V)		V _{CE(SAT)} & V _{BE(ON)} (V)		C _{ob} (pF) Max	f _T (MHz)		t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
		Min	Max		Min	Max	Min	Max	Min	Max	Min	Max		Min	Max				
BD440	TO-126	60†	60	5	100 μA	60	25 40 20	2A 500 10	1 1 5	0.8	1.5*	2A	80	3	250	420	6	5/6	5E
BD441	TO-126	80†	80	5	100 μA	80	15 40 15	2A 500 10	1 1 5	0.8	1.5*	2A	30	3	250	420	6	5/6	4E
BD442	TO-126	80†	80	5	100 μA	80	15 40 15	2A 500 10	1 1 5	0.8	1.5*	2A	30	3	250	420	6	5/6	5E
BD533	TO-220	80†	45	5	100 μA	45	25 40 20	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	4E
BD534	TO-220	80†	45	5	100 μA	45	25 40 20	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	5E
BD535	TO-220	80†	60	5	100 μA	60	25 40 20	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	4E
BD536	TO-220	80†	60	5	100 μA	60	25 40 20	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	5E
BD537	TO-220	80†	80	5	100 μA	80	15 40 15	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	4E
BD538	TO-220	80†	80	5	100 μA	80	15 40 15	2A 500 10	2 2 5	0.8	1.5*	2A	30	3	250	420	6	5/6	5E
BD633	TO-220	45	45	5	200 μA†	45	25 40	1A 25	2 2	0.6	1.3*	1A	30	3	250	420	6	5/6	4F
BD634	TO-220	45	45	5	200 μA†	45	25 40	1A 25	2 2	0.6	1.3*	1A	30	3	250	420	6	5/6	5F
BD635	TO-220	60	60	5	200 μA†	60	25 40	1A 25	2 2	0.6	1.3*	1A	30	3	250	420	6	5/6	4F

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

T-33-01

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V _{CE} * VCBO (V) Min	V _{CEO} (V) Min	V _{EB0} (V) Min	I _{CB0} * I _{CB} @ (mA) Max	HFE h _{fe} 1 kHz* Min Max	I _C & V _{CE} (mA) (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)*} (V) Min Max	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min Max	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD636	TO-220	60	60	5	200 μA†	25 40	1A 25	0.6	1.3* 1A	250	30	3	250	420	6	5/6	5F
BD637	TO-220	100	80	5	200 μA†	25	1A 25	0.6	1.3* 1A	250	30	3	250	420	6	5/6	4F
BD638	TO-220	100	80	5	200 μA†	25	1A 25	0.6	1.3 1A	250	30	3	250	420	6	5/6	5F
BD675	TO-126	45	45		200 μA	750	1.5A 3	2.5	2.5* 1.5A	1.5A		1	1.5A				4J
BD675A	TO-126	45	45		200 μA	750	2A 3	2.8	2.5* 2A	1.5A		1	1.5A				4J
BD676	TO-126	45	45		200 μA	750	1.5A 3V	2.5	2.5* 1.5A	1.5A		1	1.5A				5J
BD676A	TO-126	45	45		200 μA	750	2A 3V	2.8	2.5* 2A	1.5A		1	1.5A				5J
BD677	TO-126	60	60		200 μA	750	1.5A 3V	2.5	2.5* 1.5A	1.5A		1	1.5A				4J
BD677A	TO-126	60	60		200 μA	750	2A 3V	2.8	2.5* 2A	1.5A		1	1.5A				4J
BD678	TO-126	60	80		200 μA	750	1.5A 3V	2.5	2.5* 1.5A	1.5A		1	1.5A				5J
BD678A	TO-126	60	80		200 μA	750	2A 3V	2.8	2.5* 2A	1.5A		1	1.5A				5J
BD679	TO-126	80	80		200 μA	750	1.5A 3V	2.5	2.5* 1.5A	1.5A		1	1.5A				4J
BD679A	TO-126	80	80		200 μA	750	2A 3V	2.8	2.5* 2A	1.5A		1	1.5A				4J
BD680	TO-126	80	80		200 μA	750	1.5A 3V	2.5	2.5* 1.5A	1.5A		1	1.5A				5J
BD680A	TO-126	80	80		200 μA	750	2A 3V	2.8	2.5* 2A	1.5A		1	1.5A				5J
BD681	TO-126	100	100		200 μA	750	1.5A 3V	2.5	2.5* 1.5A	1.5A		1	1.5A				4J
BD682	TO-126	100	100		200 μA	750	1.5A 3V	2.5	2.5* 1.5A	1.5A		1	1.5A				5J
BD733	TO-220	25	25	5	200 μA†	50 40	2A 20	0.6	1.1* 2A	1.5A		1	1.5A				4F
BD734	TO-220	25	25	5	200 μA†	50 40	2A 20	0.6	1.1* 2A	1.5A		1	1.5A				5E
BD735	TO-220	35	35	5	200 μA†	40	2A 20	0.6	1.1* 2A	1.5A		1	1.5A				4F
BD736	TO-220	35	35	5	200 μA†	40	2A 20	0.6	1.1* 2A	1.5A		1	1.5A				5E
BD737	TO-220	45	45	5	200 μA†	40	2A 20	0.8	1.1* 2A	1.5A		1	1.5A				4F
BD738	TO-220	45	45	5	200 μA†	40	2A 20	0.8	1.1* 2A	1.5A		1	1.5A				5E
BD795	TO-220	45	45		100	40	1A 20	1.0	1.6* 3A	250	3	3	250				4E
BD796	TO-220	45	45		100	40	1A 20	1.0	1.6* 3A	250	3	3	250				5E
BD797	TO-220	60	60		100 μA	40 25	1A 3A	1.0	1.6* 3A	250	3	3	250				4E

T-33-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE0} [*] (V) Min	V _{CE0} (V) Min	V _{ES0} (V) Min	I _{CE0} [*] (mA) Max	V _{CB} (V)	h _{FE} 1 kHz [*] Min Max	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min Max	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min Max	I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BD798	TO-220		60		100 μA	60	40 25	1.0	1.6*	3A		3	250				5E
BD799	TO-220		80		100 μA	80	30 15	1.0	1.6*	3A		3	250				4E
BD800	TO-220		80		100 μA	80	30 15	1.0	1.6*	3A		3	250				5E
BD801	TO-220		100		100 μA	100	30 15	1.0	1.6*	3A		3	250				4E
BD802	TO-220		100		100 μA	100	30 15	1.0	1.6*	3A		3	250				5E
BD895	TO-220		45		200 μA	45	750		2.5*	3A		1	3A				4K
BD895A	TO-220		45		200 μA	45	750		2.5*	4A		1	3A				4K
BD896	TO-220		45		200 μA	45	750		2.5*	3A		1	3A				5K
BD896A	TO-220		45		200 μA	45	750		2.5*	4A		1	3A				5K
BD897	TO-220		60		200 μA	60	750		2.5*	3A		1	3A				4K
BD897A	TO-220		60		200 μA	60	750		2.5*	4A		1	3A				4K
BD898	TO-220		60		200 μA	60	750		2.5*	3A		1	3A				5K
BD898A	TO-220		60		200 μA	60	750		2.5*	4A		1	3A				5K
BD899	TO-220		80		200 μA	80	750		2.5*	3A		1	3A				4K
BD899A	TO-220		80		200 μA	80	750		2.5*	4A		1	3A				4K
BD900	TO-220		80		200 μA	80	750		2.5*	3A		1	3A				5K
BD900A	TO-220		80		200 μA	80	750		2.5*	4A		1	3A				5K
BD901	TO-220		100		200 μA	100	750		2.5*	3A		1	3A				4K
BD902	TO-220		100		200 μA	100	750		2.5*	4A		1	3A				4K
BDX33	TO-220		45		1 mA	45	750		2.5*	4A		20	1A				4K
BDX33A	TO-220		60		1 mA	60	750		2.5*	4A		20	1A				4K
BDX33B	TO-220		80		1 mA	80	750		2.5*	3A		20	1A				4K
BDX33C	TO-220		100		1 mA	100	750		2.5*	3A		20	1A				4K
BDX33D	TO-220		120		1 mA	120	750		2.5*	3A		20	1A				4K
BDX34	TO-220		45		1 mA	45	750		2.5*	4A		20	1A				5K
BDX34A	TO-220		60		1 mA	60	750		2.5*	4A		20	1A				5K
BDX34B	TO-220		80		1 mA	80	750		2.5*	3A		20	1A				5K

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = 10 kHz.

Pro Electron Series

5

Pro Electron Series

7-31-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} [*] V _{CB} (V) Min	V _{CE} [*] (V) Min	V _{EB} (V) Min	I _{CS} [*] I _{CB} (mA) Max	HFE h _{FE} 1 kHz Min	I _C & V _{CE}		V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min		C _{ob} (pF) Max	f _T (MHz) Min		I _C (mA) Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
							I _C (mA) Max	V _{CE} (V) Max		I _C (mA) Max	V _{BE} (V) Max		I _C (mA) Max	f _T (MHz) Max					
BDX34C	TO-220		100		1 mA	750	3A	3		2.5*	3A		20		1A				5K
BDX34D	TO-220		120		1 mA	750	3A	3		2.5*	3A		20		1A				5K
BF167	TO-72 (28)	40	30	4	100†	26	4	10		0.84*	4								45
BF180	TO-72 (25)	30	20	3	100	13	2	10											41
BF181	TO-72 (25)	30	20	3	100	13	2	10											41
BF194	TO-92 (98)	Same as BF254, see page 5-33 for explanation																	
BF195	TO-92 (98)	Same as BF255, see page 5-33 for explanation																	
BF196	TO-92 (98)	Same as BF198, see below for explanation																	
BF197	TO-92 (98)	Same as BF199, see below for explanation																	
BF198	TO-92 (98)	40	30	4	100	26	4	10		0.85*	4		26						45
BF199	TO-92 (98)	40	25	4	100	36	7	10					1100	typ	7				47
BF200	TO-72 (25)	30	20	3	100	15	3	10											41
BF233-2	TO-92 (96)	30	30	4	100	40	70	10		0.65	0.74*	1			1				49
BF233-3	TO-92 (96)	30	30	4	100	60	100	10		0.65	0.74*	1			1				49
BF233-4	TO-92 (96)	30	30	4	100	90	150	10		0.65	0.74*	1			1				49
BF233-5	TO-92 (96)	30	30	4	100	140	220	10		0.65	0.74*	1			1				49
BF237	TO-92 (98)	45	30	4	100					0.25		10							47
BF238	TO-92 (98)	45	30	4	100					0.25		10							47
BF240	TO-92 (98)	40	40	4	100	67	222	10		0.65	0.74*	1			1		3.5	7	47
BF241	TO-92 (98)	40	40	4	100	36	125	10		0.65	0.74*	1			1		3.5	7	47



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE0} [*] V _{CE0} (V) Min	V _{BE0} (V) Min	I _{CE0} [*] I _{CE0} (mA) Max	V _{CB} (V) Max	HFE h _{FE} 1 kHz Min Max	I _C & V _{CE} (mA) (V) Min Max	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min Max		I _C (mA) Min Max	C _{ob} (pF) Max	f _T (MHz) Min Max	I _C (mA) Min Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
									V _{CE(SAT)} (V) Max	V _{BE(ON)} (V) Min								
BF254	TO-92 (98)	30	5	100	20	67 6	1 12	10 7	0.65	0.74*	1	0.34				3.5	7	46
BF255	TO-92 (98)	30	-5	100	20	36 6	12 7	10 7	0.65	0.74*	1	0.34				3.5	7	46
BF257	TO-39	100	5	50	100	25 6	30 12	10 7	1.0	0.65	0.74*	0.34				3.5	7	48
BF258	TO-39	250	5	50	200	25 6	30 12	10 7	1.0	0.65	0.74*	0.34				3.5	7	48
BF259	TO-39	300	5	50	250	25 6	30 12	10 7	1.0	0.65	0.74*	0.34				3.5	7	48
BF457	TO-126	100	5	50	100	25 6	30 12	10 7	1.0	0.65	0.74*	0.34				3.5	7	48
BF458	TO-126	250	5	50	200	25 6	30 12	10 7	1.0	0.65	0.74*	0.34				3.5	7	48
BF459	TO-126	300	5	50	250	25 6	30 12	10 7	1.0	0.65	0.74*	0.34				3.5	7	48
BFX13	TO-18	20	5	50	15	10 50 18	100 10 1	2 0.35 2	0.2 0.25 1.5	0.78 0.7 1.5	1 10 100	6	150	10		10	8	66
BFX29	TO-5	20	5	50	50	40 50 50 40 20	150 50 10 1 0.1	10 10 10 10 10	0.4 0.4 0.4 0.4 0.4			12	100	50	150		9	63
BFX30	TO-5	65	5	50	50	10 20 50 40	150 50 10 1	0.4 0.4 0.4 0.4	0.4 0.4 0.4 0.4	0.9 1.3 0.9	30 150 30	12	290				4	63
BFX37	TO-18	60	6	20†	50	100 100 0.85 70	10 1 0.1 300	5 5 5 5	0.4 0.25 0.25	1.0 0.9 0.9	50 10 10	6	40	0.5		3	1	62
BFX65	TO-18	45	6	10*	40	100 100 100 40	10 1 0.1 0.01	5 5 5 5	0.25 0.25	0.9 10	10 10	6.5				3	1	62

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

6501130 NATL SEMICOND, (DISCRETE)

28C 35543 D

T-31-01

Type No.	Case Style	V _{CE} [*] V _{CB} [*] (V) Min	V _{CE} [*] (V) Min	V _{EB} [*] (V) Min	I _{CE} [*] I _{CB} [*] (mA) Max	HFE h _{fe} 1 kHz [*] Min Max	I _C & V _{CE} (mA) (V)	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min Max	I _C (mA) Min Max	C _{ob} (pF) Max	f _T (MHz) Min Max	I _C (mA) Min Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BFX84	TO-39	45	45	6	500	15 20 30 20	1A 500 150 10	0.15 0.35 1.0 1.6	1.2 1.3 1.5 2.0	10 150 500 1A	12	50	50	360		9	14
BFX85	TO-39	45	45	6	50	15 30 70 50	1A 500 150 10	0.15 0.35 1.0 1.6	1.2 1.3 1.5 2.0	10 150 500 1A	12	50	50	360		9	14
BFX86	TO-39	45	45	6	50	15 30 70 50	1A 500 150 10	0.15 0.35 1.0 1.6	1.2 1.3 1.5 2.0	10 150 500 1A	12	50	50	360		9	14
BFX87	TO-5	45	50	6	50	25 40 40 40	500 150 10 10	0.4 0.4 0.4 0.4	1.3 1.5 2.0 1A	150 150 30 30	12	100	50	150		9	63
BFX88	TO-5	45	40	6	50	25 40 40 40	500 150 10 10	0.4 0.4 0.4 0.4	1.3 1.5 2.0 1A	150 150 30 30	12	100	50	150		9	63
BFY39	TO-18	45	25	5	50	35	400	1.0	1.0	10		150	10				23
BFY39-1	TO-18	45	25	5	50	35	110	1.0	1.0	10		150	10				23
BFY39-2	TO-18	45	25	5	50	100	200	1.0	1.0	10		150	10				23
BFY39-3	TO-18	45	25	5	50	180	400	1.0	1.0	10		150	10				23
BFY50	TO-18	80	35	6	500	20 30 20 15	10 150 500 1A	0.1 0.1 0.1 0.1	1.2 1.2 1.2 1.2	10 10 10 10	12	60	50	360		9	14
BFY51	TO-39	60	30	6	500	30 40 25 15	10 150 500 1A	0.1 0.1 0.1 0.1	1.2 1.2 1.2 1.2	10 10 10 10	12	60	50	360		9	14
BFY52	TO-39	40	20	6	500	30 60 30 15	10 150 500 1A	0.1 0.1 0.1 0.1	1.2 1.2 1.2 1.2	10 10 10 10	12	60	50	360		9	14
BFY56	TO-39	80	45	5	50	15 20 30	1 500 150	0.3 1.2	1.5 2.5	150 1A	25	40	50				14

PRO ELECTRON SERIES (Continued)



Type No.	Case Style	V _{CE0} [*] V _{CB0} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CB0} [*] I _{CB0} (mA) Max	HFE h _{FE} 1 kHz Min Max	I _C & V _{CE} (mA) (V) Min Max	V _{CE(SAT)} (V) Max	V _{BE(SAT)} & V _{BE(ON)} [*] (V) Min Max	I _C (mA) Min Max	C _{ob} (pF) Max	f _T (MHz) Min Max	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
BFY72	TO-39	50	28	5	40*	15 20 30 40 15	0.1 1 10 10 150 500 10	0.25	1.2	150	8	50				19
BFY76	TO-18	45	45	6	20	30 80 140	0.01 0.5 5 5	0.35	1.6	500	6					
BSX21	TO-18	80	80	7	10*	20	4 3		0.9	4		60				07
BSX45-6	TO-39	80*	40	7	10*	40	100 1	1.0	2.0	1A	20	60				14
BSX45-10	TO-39	80*	40	7	10*	63	160 100 1	1.0	2.0	1A	20	60				14
BSX45-16	TO-39	80*	40	7	10*	100	250 100 1	1.0	2.0	1A	20	60				14
BSX46-6	TO-39	100*	60	7	10*	40	100 100 1	1.0	2.0	1A	25	60				12
BSX46-10	TO-39	100*	60	7	10*	63	160 100 1	1.0	2.0	1A	25	60				12
BSX46-16	TO-39	100*	60	7	10*	100	250 100 1	1.0	2.0	1A	25	60				12
BSX48	TO-18	50	25	5	120	17	100 1	1.5	1.5	500	6	250				19
BSX88	TO-18	40	15	5	25	15	45 100 1	0.6	0.72	0.8	6	300				21
BSY38	TO-18	20	12	5	100	30	60 10 0.35	0.25	0.7	0.85	5	200			16	21
BSY39	TO-18	20	12	5	100	40	120 10 0.35	0.25	0.7	0.85	5	200			16	21
BSY51	TO-18	60	35	5	100	40	120 150 10	1.0	1.3	150	9	130				19
BSY52	TO-18	60	25	5	100	100	300 150 10	1.0	1.3	150	9	130				19
BSY53	TO-18	75	30	7	10	20	0.1 10 10 150 10	0.6	1.3	150	9	150				19

T-31-01

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

Pro Electron Series

T-31-01



PRO ELECTRON SERIES (Continued)

Type No.	Case Style	V _{CE} [*] V _{CB0} (V) Min	V _{CE0} (V) Min	V _{EB0} (V) Min	I _{CB0} [*] (mA) Max	V _{CB} (V)	HFE		I _C & V _{CE}		V _{CE(SAT)} & V _{BE(ON)} [*]		f _T (MHz) Min	t _{off} (ns) Max	NF (dB) Max	Test Conditions	Process No.
							h _{FE} 1 kHz [*] Min	h _{FE} 1 kHz [*] Max	I _C (mA) Min	V _{CE} (V) Max	V _{CE(SAT)} (V) Max	V _{BE(ON)} [*] (V) Min					
BSY54	TO-18	75	30	7	10	60	35	0.1	10	0.6	1.3	150	50				19
							75	10	10								
BSY95A	TO-18	20	15	5	50	16	30	1	0.35	0.35	0.67	200	10				21
							50	10	0.35								

TEST CONDITIONS:

(1) I_C = 200 μA, V_{CE} = 5V, f = 1 kHz. (2) I_C = 100 mA, V_{CE} = 20V, I_B¹ = I_B² = 5 mA. (3) I_C = 200 μA, V_{CE} = 2V, f = 1 kHz. (4) I_C = 100 mA, V_{CE} = 10V, I_B¹ = I_B² = 10 mA. (5) I_C = 10 mA, V_{CE} = 3V, I_B¹ = I_B² = 1 mA. (6) I_C = 100 μA, V_{CE} = 5V, f = 1 kHz. (7) I_C = 1 mA, V_{CE} = 10V, f = 200 kHz. (8) I_C = 1 mA, V_{CE} = 5V, f = 1 kHz. (9) I_C = 150 mA, V_{CE} = 6V, I_B¹ = I_B² = 15 mA. (10) I_C = 10 μA, V_{CE} = 5V, f = WB.

6501130 NATL SEMICOND, (DISCRETE)

28C 35546

T-31-01

Pro Electron Series



PRO ELECTRON SERIES (JFET)

Type No.	Case Style	BV _{GSS} (V) @ I _G		I _{GSS} (mA) @ V _{GD}		V _P (V) @ V _{DS}		I _D (mA) @ V _{DS}		V _{GS} (V) @ V _{GS}		I _{DSS} (mA) @ V _{DS}		R _e (V _{FS}) (mmho) @ f		C _{iss} (pF) @ V _{DS}		V _{GS} (V)		C _{oss} (pF) @ V _{DS}		V _{GS} (V)		NF (dB) @ R _G = 1k @ f		Process No.	Pkg. No.	
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max			
BF244A	TO-92	30	1	5	20	.5	8	15	10	4	2.2	15	200	2	6.5	15	3	6.5	.001	4	20	1.1	20	-1	1.5	100	50	74
BF244B	TO-92	30	1	5	20	.5	8	15	10	1.6	3.8	15	200	6	15	15	3	6.5	.001	4	20	1.1	20	-1	1.5	100	50	74
BF244C	TO-92	30	1	5	20	.5	8	15	10	3.2	7.5	15	200	12	25	15	3	6.5	.001	4	20	1.1	20	-1	1.5	100	50	74
BF245A	TO-92	30	1	5	20	.5	8	15	10	4	2.2	15	200	2	6.5	15	3	6.5	.001	4	20	1.1	20	-1	1.5	100	50	77
BF245B	TO-92	30	1	5	20	.5	8	15	10	1.6	3.8	15	200	6	15	15	3	6.5	.001	4	20	1.1	20	-1	1.5	100	50	77
BF245C	TO-92	30	1	5	20	.5	8	15	10	3.2	7.5	15	200	12	25	15	3	6.5	.001	4	20	1.1	20	-1	1.5	100	50	77
BF246A	TO-92	25	1	5	15	.6	14.5	15	10	1.5	4.0	15	200	30	80	15	8	.001	11	15	0	3.5	15	0	3.5	15	50	77
BF246B	TO-92	25	1	5	15	.6	14.5	15	10	3.0	7.0	15	200	60	140	15	8	.001	11	15	0	3.5	15	0	3.5	15	51	74
BF246C	TO-92	25	1	5	15	.6	14.5	15	10	5.5	12	15	200	110	250	15	8	.001	11	15	0	3.5	15	0	3.5	15	51	74
BF247A	TO-92	25	1	5	15	.6	14.5	15	10	1.5	4.0	15	200	30	80	15	8	.001	11	15	0	3.5	15	0	3.5	15	51	77
BF247B	TO-92	25	1	5	15	.6	14.5	15	10	3.0	7.0	15	200	60	140	15	8	.001	11	15	0	3.5	15	0	3.5	15	51	77
BF247C	TO-92	25	1	5	15	.6	14.5	15	10	5.5	12	15	200	110	250	15	8	.001	11	15	0	3.5	15	0	3.5	15	51	77
BF256A	TO-92	30	1	5	20	.5	7.5	15	10	.5	7.5	15	200	3	7	15	4.5	.001	.7	20	-1	.7	20	-1	7.5	800	50	77
BF256B	TO-92	30	1	5	20	.5	7.5	15	10	.5	7.5	15	200	6	13	15	4.5	.001	.7	20	-1	.7	20	-1	7.5	800	50	77
BF256C	TO-92	30	1	5	20	.5	7.5	15	10	5	7.5	15	200	11	18	15	4.5	.001	.7	20	-1	.7	20	-1	7.5	800	50	77
BC264A	TO-92	30	1	10	20	.5	15	15	10	2	1.2	15	1000	2	4.5	15	2.5	.001	4.0	15	-1	1.2	15	-1	40*	10*	50	77
BC264B	TO-92	30	1	10	20	.5	15	15	10	4	1.4	15	1500	3.5	6.5	15	3.0	.001	4.0	15	-1	1.2	15	-1	40*	10*	50	77
BC264C	TO-92	30	1	10	20	.5	15	15	10	5	1.5	15	2500	5.0	8.0	15	3.5	.001	4.0	15	-1	1.2	15	-1	40*	10*	50	77
BC264D	TO-92	30	1	10	20	.5	15	15	10	6	1.6	15	3500	7.0	12.0	15	4.0	.001	4.0	15	-1	1.2	15	-1	40*	10*	50	77

5