

isc Silicon NPN Power Transistor

BD239/A/B/C

DESCRIPTION



- DC Current Gain $-h_{FE} = 40(\text{Min})@ I_C = 0.2\text{A}$
- Collector-Emitter Sustaining Voltage-
: $V_{CEO(\text{SUS})} = 45\text{V}(\text{Min})$ - BD239; $60\text{V}(\text{Min})$ - BD239A
80V(Min)- BD239B; $100\text{V}(\text{Min})$ - BD239C
- Complement to Type BD240/A/B/C
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Designed for medium power linear and switching applications.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT	
V_{CER}	Collector-Emitter Voltage	BD239	55	V
		BD239A	70	
		BD239B	90	
		BD239C	115	
V_{CEO}	Collector-Emitter Voltage	BD239	45	V
		BD239A	60	
		BD239B	80	
		BD239C	100	
V_{EBO}	Emitter-Base Voltage	5	V	
I_C	Collector Current-Continuous	2	A	
I_{CM}	Collector Current-Peak	4	A	
I_B	Base Current	0.6	A	
P_C	Collector Power Dissipation @ $T_C=25^\circ\text{C}$	30	W	
T_J	Junction Temperature	150	$^\circ\text{C}$	
T_{stg}	Storage Temperature Range	-65~150	$^\circ\text{C}$	



isc Silicon NPN Power Transistor
BD239/A/B/C
THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	4.17	$^{\circ}C/W$

ELECTRICAL CHARACTERISTICS
 $T_C=25^{\circ}C$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT	
$V_{CE(sus)}$	Collector-Emitter Sustaining Voltage	BD239	$I_C=30mA; I_B=0$	45	V	
		BD239A		60		
		BD239B		80		
		BD239C		100		
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=1A; I_B=0.2A$		0.7	V	
$V_{BE(on)}$	Base-Emitter On Voltage	$I_C=1A; V_{CE}=4V$		1.3	V	
I_{CES}	Collector Cutoff Current	BD239		0.2	mA	
		BD239A				$V_{CE}=60V; V_{BE}=0$
		BD239B				$V_{CE}=80V; V_{BE}=0$
		BD239C				$V_{CE}=100V; V_{BE}=0$
I_{CEO}	Collector Cutoff Current	BD239/A		0.3	mA	
		BD239B/C				$V_{CE}=60V; I_B=0$
I_{EBO}	Emitter Cutoff Current	$V_{EB}=5V; I_C=0$		1.0	mA	
h_{FE-1}	DC Current Gain	$I_C=0.2A; V_{CE}=4V$	40			
h_{FE-2}	DC Current Gain	$I_C=1A; V_{CE}=4V$	15			

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.