

**isc Silicon PNP Power Transistor**
**BD246/A/B/C**
**DESCRIPTION**

- Collector Current  $-I_C = -10A$
- Collector-Emitter Breakdown Voltage-  
:  $V_{(BR)CEO} = -45V(\text{Min})$ - BD246;  $-60V(\text{Min})$ - BD246A  
 $-80V(\text{Min})$ - BD246B;  $-100V(\text{Min})$ - BD246C
- Complement to Type BD245/A/B/C
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**APPLICATIONS**



- Designed for use in general purpose power amplifier and switching applications

**ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ\text{C}$ )**

SYMBOL	PARAMETER	VALUE	UNIT	
$V_{CER}$	Collector-Emitter Voltage ( $R_{BE} = 100 \Omega$ )	BD246	-55	V
		BD246A	-70	
		BD246B	-90	
		BD246C	-115	
$V_{CEO}$	Collector-Emitter Voltage	BD246	-45	V
		BD246A	-60	
		BD246B	-80	
		BD246C	-100	
$V_{EBO}$	Emitter-Base Voltage	-5	V	
$I_C$	Collector Current-Continuous	-10	A	
$I_{CM}$	Collector Current-Peak	-15	A	
$I_B$	Base Current	-3	A	
$P_C$	Collector Power Dissipation @ $T_a=25^\circ\text{C}$	3	W	
	Collector Power Dissipation @ $T_c=25^\circ\text{C}$	80		
$T_J$	Junction Temperature	150	$^\circ\text{C}$	
$T_{stg}$	Storage Temperature Range	-65~150	$^\circ\text{C}$	

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.56	$^\circ\text{C}/\text{W}$



DIM	mm	
	MIN	MAX
A	19.60	20.30
B	15.50	15.70
C	4.70	4.90
D	0.90	1.10
E	1.90	2.10
F	3.40	3.60
G	2.90	3.20
H	3.20	3.40
J	0.595	0.605
K	19.80	20.70
L	1.90	2.20
N	10.89	10.91
Q	4.90	5.10
R	3.35	3.45
S	1.995	2.100
U	5.90	6.20
Y	9.90	10.10

**isc Silicon PNP Power Transistor**
**BD246/A/B/C**
**ELECTRICAL CHARACTERISTICS**

 T<sub>C</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT	
V <sub>(BR)CEO</sub>	Collector-Emitter Breakdown Voltage	BD246	-45			V	
		BD246A	-60				
		BD246B	-80				
		BD246C	-100				
V <sub>CE(sat)-1</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = -3A; I <sub>B</sub> = -0.3A			-1.0	V	
V <sub>CE(sat)-2</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = -10A; I <sub>B</sub> = -2.5A			-4.0	V	
V <sub>BE(on)-1</sub>	Base-Emitter On Voltage	I <sub>C</sub> = -3A; V <sub>CE</sub> = -4V			-1.6	V	
V <sub>BE(on)-2</sub>	Base-Emitter On Voltage	I <sub>C</sub> = -10A; V <sub>CE</sub> = -4V			-3.0	V	
I <sub>CES</sub>	Collector Cutoff Current	BD246	V <sub>CE</sub> = -55V; V <sub>BE</sub> = 0			-0.4	mA
		BD246A	V <sub>CE</sub> = -70V; V <sub>BE</sub> = 0				
		BD246B	V <sub>CE</sub> = -90V; V <sub>BE</sub> = 0				
		BD246C	V <sub>CE</sub> = -115V; V <sub>BE</sub> = 0				
I <sub>CEO</sub>	Collector Cutoff Current	BD246/A	V <sub>CE</sub> = -30V; I <sub>B</sub> = 0			-0.7	mA
		BD246B/C	V <sub>CE</sub> = -60V; I <sub>B</sub> = 0				
I <sub>EBO</sub>	Emitter Cutoff Current	V <sub>EB</sub> = -5V; I <sub>C</sub> = 0			-1.0	mA	
h <sub>FE-1</sub>	DC Current Gain	I <sub>C</sub> = -1A; V <sub>CE</sub> = -4V	40				
h <sub>FE-2</sub>	DC Current Gain	I <sub>C</sub> = -3A; V <sub>CE</sub> = -4V	20				
h <sub>FE-3</sub>	DC Current Gain	I <sub>C</sub> = -10A; V <sub>CE</sub> = -4V	4				
f <sub>T</sub>	Current-Gain—Bandwidth Product	I <sub>C</sub> = -0.5A; V <sub>CE</sub> = -10V, f <sub>test</sub> = 1.0MHz	3.0			MHz	

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.