

**isc Silicon NPN Power Transistor**
**BD249/A/B/C**
**DESCRIPTION**

- Collector Current  $-I_C = 25A$
- Complement to Type BD250/A/B/C
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**APPLICATIONS**



- Designed for use in general purpose power amplifier and switching applications

**ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ C$ )**

SYMBOL	PARAMETER	VALUE	UNIT	
$V_{CER}$	Collector-Emitter Voltage ( $R_{BE} = 100 \Omega$ )	BD249	55	V
		BD249A	70	
		BD249B	90	
		BD249C	115	
$V_{CEO}$	Collector-Emitter Voltage	BD249	45	V
		BD249A	60	
		BD249B	80	
		BD249C	100	
$V_{EBO}$	Emitter-Base Voltage	5	V	
$I_C$	Collector Current-Continuous	25	A	
$I_{CM}$	Collector Current-Peak	40	A	
$I_B$	Base Current	5	A	
$P_C$	Collector Power Dissipation @ $T_a=25^\circ C$	3	W	
	Collector Power Dissipation @ $T_c=25^\circ C$	125		
$T_J$	Junction Temperature	150	$^\circ C$	
$T_{stg}$	Storage Temperature Range	-65~150	$^\circ C$	

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.0	$^\circ C/W$



DIM	mm	
	MIN	MAX
A	19.60	20.30
B	15.50	15.70
C	4.70	4.90
D	0.90	1.10
E	1.90	2.10
F	3.40	3.60
G	2.90	3.20
H	3.20	3.40
J	0.595	0.605
K	19.80	20.70
L	1.90	2.20
N	10.89	10.91
Q	4.90	5.10
R	3.35	3.45
S	1.995	2.100
U	5.90	6.20
Y	9.90	10.10

**isc Silicon NPN Power Transistor**
**BD249/A/B/C**
**ELECTRICAL CHARACTERISTICS**

 T<sub>C</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V <sub>(BR)CEO</sub>	Collector-Emitter Breakdown Voltage	BD249	I <sub>C</sub> = 30mA ; I <sub>B</sub> =0			V
		BD249A				
		BD249B				
		BD249C				
V <sub>CE(sat)-1</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = 15A; I <sub>B</sub> = 1.5A			1.8	V
V <sub>CE(sat)-2</sub>	Collector-Emitter Saturation Voltage	I <sub>C</sub> = 25A; I <sub>B</sub> = 5A			4.0	V
V <sub>BE(on)-1</sub>	Base-Emitter On Voltage	I <sub>C</sub> = 15A; V <sub>CE</sub> = 4V			2.0	V
V <sub>BE(on)-2</sub>	Base-Emitter On Voltage	I <sub>C</sub> = 25A; V <sub>CE</sub> = 4V			4.0	V
I <sub>CES</sub>	Collector Cutoff Current	BD249			0.7	mA
		BD249A				
		BD249B				
		BD249C				
I <sub>CEO</sub>	Collector Cutoff Current	BD249/A			1.0	mA
		BD249B/C				
I <sub>EBO</sub>	Emitter Cutoff Current	V <sub>EB</sub> = 5V; I <sub>C</sub> = 0			1.0	mA
h <sub>FE-1</sub>	DC Current Gain	I <sub>C</sub> = 1.5A; V <sub>CE</sub> = 4V	25			
h <sub>FE-2</sub>	DC Current Gain	I <sub>C</sub> = 15A; V <sub>CE</sub> = 4V	10			
h <sub>FE-3</sub>	DC Current Gain	I <sub>C</sub> = 25A; V <sub>CE</sub> = 4V	5			
Switching times						
t <sub>on</sub>	Turn-on Time	I <sub>C</sub> = 5A; I <sub>B1</sub> = -I <sub>B2</sub> = 0.5A; R <sub>L</sub> = 5 Ω ; V <sub>BE(off)</sub> = -5V		0.3		μ s
t <sub>off</sub>	Turn-off Time			0.9		μ s

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.