

isc Silicon NPN Power Transistors
BD751B/751C
DESCRIPTION

- Collector-Emitter Sustaining Voltage-
: $V_{CEO(SUS)} = 100V(\text{Min})$ - BD751B
= $130V(\text{Min})$ - BD751C
- High Power Dissipation
- Complement to Type BD750B/750C
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Designed for high voltage and high power amplifier applications.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT	
V_{CEV}	Collector-Emitter Voltage	BD751B	110	V
		BD751C	140	
$V_{CEO(SUS)}$	Collector-Emitter Voltage	BD751B	100	V
		BD751C	130	
V_{EBO}	Emitter-Base Voltage	7	V	
I_C	Collector Current-Continuous	20	A	
I_B	Base Current-Continuous	5	A	
P_C	Collector Power Dissipation@ $T_c=25^\circ\text{C}$	250	W	
T_J	Junction Temperature	200	$^\circ\text{C}$	
T_{stg}	Storage Temperature	-65~200	$^\circ\text{C}$	

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	0.875	$^\circ\text{C/W}$



isc Silicon NPN Power Transistors

BD751B/751C

ELECTRICAL CHARACTERISTICS

 $T_C=25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CE0(SUS)}$	Collector-Emitter Sustaining Voltage	BD751B	$I_C=50\text{mA}; I_B=0$	100			V
		BD751C		130			
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	BD751B	$I_C=7.5\text{A}; I_B=0.75\text{A}$			1.5	V
		BD751C	$I_C=5\text{A}; I_B=0.5\text{A}$			1.0	
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	BD751B	$I_C=7.5\text{A}; I_B=0.75\text{A}$			1.8	V
		BD751C	$I_C=5\text{A}; I_B=0.5\text{A}$			1.8	
I_{CEV}	Collector Cutoff Current	BD751B	$V_{CEV}=110\text{V}; V_{BE(off)}=1.5\text{V}$			0.5	mA
		BD751C	$V_{CEV}=140\text{V}; V_{BE(off)}=1.5\text{V}$			0.5	
I_{EBO}	Emitter Cutoff Current		$V_{EB}=7\text{V}; I_C=0$			1.0	mA
h_{FE}	DC Current Gain	BD751B	$I_C=7.5\text{A}; V_{CE}=2\text{V}$	15		60	
		BD751C	$I_C=5\text{A}; V_{CE}=2\text{V}$	25		100	

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.