

isc Silicon NPN Power Transistors
BDT29/A/B/C
DESCRIPTION

- DC Current Gain $-h_{FE} = 40(\text{Min})@ I_C = 0.4\text{A}$
- Collector-Emitter Sustaining Voltage-
: $V_{CEO(\text{SUS})} = 40\text{V}(\text{Min})$ - BDT29; $60\text{V}(\text{Min})$ - BDT29A
80V(Min)- BDT29B; $100\text{V}(\text{Min})$ - BDT29C
- Complement to Type BDT30/A/B/C
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Designed for use in output stages of audio and television amplifier circuits where high peak powers can occur.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT	
V_{CBO}	Collector-Base Voltage	BDT29	80	V
		BDT29A	100	
		BDT29B	120	
		BDT29C	140	
V_{CEO}	Collector-Emitter Voltage	BDT29	40	V
		BDT29A	60	
		BDT29B	80	
		BDT29C	100	
V_{EBO}	Emitter-Base Voltage	5	V	
I_C	Collector Current-Continuous	1	A	
I_{CM}	Collector Current-Peak	3	A	
I_B	Base Current	0.4	A	
P_C	Collector Power Dissipation $T_c=25^\circ\text{C}$	30	W	
T_j	Junction Temperature	150	$^\circ\text{C}$	
T_{stg}	Storage Temperature Range	-65~150	$^\circ\text{C}$	

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	4.17	$^\circ\text{C}/\text{W}$
$R_{th\ j-a}$	Thermal Resistance, Junction to Ambient	70	$^\circ\text{C}/\text{W}$



isc Silicon NPN Power Transistors

BDT29/A/B/C

ELECTRICAL CHARACTERISTICS

T_C=25°C unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO(SUS)}	Collector-Emitter Sustaining Voltage	BDT29	I _C = 30mA; I _B = 0	40			V
		BDT29A		60			
		BDT29B		80			
		BDT29C		100			
V _{CE(sat)}	Collector-Emitter Saturation Voltage		I _C = 1A; I _B = 0.125A			0.7	V
V _{BE(on)}	Base-Emitter On Voltage		I _C = 1A; V _{CE} = 4V			1.3	V
I _{CES}	Collector Cutoff Current		V _{CE} = V _{CEOmax} ; V _{BE} = 0			0.2	mA
I _{CEO}	Collector Cutoff Current	BDT29/A	V _{CE} = 30V; I _B = 0			0.1	mA
		BDT29B/C	V _{CE} = 60V; I _B = 0				
I _{EBO}	Emitter Cutoff Current		V _{EB} = 5V; I _C = 0			0.2	mA
h _{FE-1}	DC Current Gain		I _C = 0.2A ; V _{CE} = 4V	40			
h _{FE-2}	DC Current Gain		I _C = 1A ; V _{CE} = 4V	15		75	
f _T	Current-Gain—Bandwidth Product		I _C = 0.2A ; V _{CE} = 10V	3			MHz
Switching Times							
t _{on}	Turn-On Time		I _C = 1.0A; I _{B1} = -I _{B2} = 0.1A		0.3		μs
t _{off}	Turn-Off Time				1.0		μs

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.