



BDT65-A-B-C

SILICON DARLINGTON POWER TRANSISTORS

NPN epitaxial-base transistors in a monolithic Darlington circuit and housed in a TO-220 envelope. They are intended for output stages in audio equipment, general amplifiers, and analogue switching application.
 PNP complements are BDT64-A-B-C
 Compliance to RoHS.

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings		Value	Unit
V_{CBO}	Collector-Base Voltage	BDT65	60	V
		BDT65A	80	
		BDT65B	100	
		BDT65C	120	
V_{CEO}	Collector-Emitter Voltage	BDT65	60	V
		BDT65A	80	
		BDT65B	100	
		BDT65C	120	
V_{EBO}	Emitter-Base Voltage	BDT65	5	V
		BDT65A		
		BDT65B		
		BDT65C		
I_c	Collector Current	BDT65	12	A
		BDT65A		
		BDT65B		
		BDT65C		
I_{CM}	Collector Peak Current	BDT65	20	A
		BDT65A		
		BDT65B		
		BDT65C		

BDT65-A-B-C

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings			Value	Unit
I _B	Base Current		BDT65	500	mA
			BDT65A		
			BDT65B		
			BDT65C		
P _T	Power Dissipation	@ T _{mb} < 25°	BDT65	125	Watts
			BDT65A		
			BDT65B		
			BDT65C		
T _J	Junction Temperature		BDT65	150	°C
			BDT65A		
			BDT65B		
			BDT65C		
T _s	Storage Temperature range		BDT65	-65 to +150	
			BDT65A		
			BDT65B		
			BDT65C		

Limiting values in accordance with the Absolute Maximum System (IEC 134)

THERMAL CHARACTERISTICS

Symbol	Ratings	Value	Unit
R_{thj-c}	Thermal Resistance, Junction to Case	1	$^\circ\text{C}/\text{W}$

BDT65-A-B-C

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted

Symbol	Ratings	Test Condition(s)		Min	Typ	Max	Unit
I_{CBO}	Collector Cutoff Current	$I_E = 0$ $V_{CB} = V_{CBOmax}$	BDT65	-	-	0.4	mA
			BDT65A				
			BDT65B				
			BDT65C				
		$I_E = 0$ $V_{CB} = 1/2 V_{CBOmax}$ $T_J = 150\text{ }^{\circ}C$	BDT65	-	-	2	mA
			BDT65A				
			BDT65B				
			BDT65C				
I_{CEO}	Collector Cutoff Current	$I_E = 0$ $V_{CE} = 1/2 V_{CEOmax}$	BDT65	-	-	0.2	mA
			BDT65A				
			BDT65B				
			BDT65C				
I_{EBO}	Emitter Cutoff Current	$V_{EB} = 5\text{ V}$ $I_C = 0$	BDT65	-	-	5	mA
			BDT65A				
			BDT65B				
			BDT65C				
V_{CEO}	Collector-Emitter Breakdown Voltage	$I_C = 30\text{ mA}$ $I_B = 0$	BDT65	60	-	-	V
			BDT65A	80	-	-	
			BDT65B	100	-	-	
			BDT65C	120	-	-	
$V_{CE(SAT)}$	Collector-Emitter saturation Voltage (*)	$I_C = 5\text{ A}$ $I_B = 20\text{ mA}$	BDT65	-	-	2	V
			BDT65A				
			BDT65B				
			BDT65C				
		$I_C = 10\text{ A}$ $I_B = 100\text{ mA}$	BDT65	-	-	3	
			BDT65A				
			BDT65B				
			BDT65C				

BDT65-A-B-C

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted

Symbol	Ratings			Min	Typ	Max	Unit
$V_{BE(on)}$	Base-Emitter Voltage (*)	$I_C = 5\text{ A}$, $V_{CE} = 4\text{ V}$	BDT65	-	-	2.5	V
			BDT65A				
			BDT65B				
			BDT65C				
V_{ECF}	C-E Diode Forward Voltage	$I_F = 5\text{ A}$	BDT65		-	2	V
			BDT65A				
			BDT65B				
			BDT65C				
		$I_F = 12\text{ A}$	BDT65	-	2	-	
			BDT65A				
			BDT65B				
			BDT65C				
h_{FE}	DC Current Gain (*)	$V_{CE} = 4\text{ V}$, $I_C = 1\text{ A}$	BDT65	-	1500	-	-
			BDT65A				
			BDT65B				
			BDT65C				
		$V_{CE} = 4\text{ V}$, $I_C = 5\text{ A}$	BDT65	1000	-	-	
			BDT65A				
			BDT65B				
			BDT65C				
		$V_{CE} = 4\text{ V}$, $I_C = 12\text{ A}$	BDT65	-	1000	-	
			BDT65A				
			BDT65B				
			BDT65C				
C_{OB}	Output Capacitance	$I_E = 0$, $V_{CB} = 10\text{ V}$ $f_{test} = 1\text{ MHz}$	BDT65	-	200	-	pF
			BDT65A				
			BDT65B				
			BDT65C				

SWITCHING TIMES


Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit
t_{on}	turn-on time	$I_C = 5\text{ A}$, $V_{CC} = 30\text{ V}$ $I_{B1} = -I_{B2} = 20\text{ mA}$	-	1	2.5	μs
t_{off}	turn-off time		-	6	10	

(*) Pulse Width $\approx 300\text{ }\mu\text{s}$, Duty Cycle $\angle 2.0\%$

BDT65-A-B-C

MECHANICAL DATA CASE TO-220

DIMENSIONS (mm)		
	Min.	Max.
A	9,90	10,30
B	15,65	15,90
C	13,20	13,40
D	6,45	6,65
E	4,30	4,50
F	2,70	3,15
G	2,60	3,00
H	15,75	17,15
L	1,15	1,40
M	3,50	3,70
N	-	1,37
P	0,46	0,55
R	2,50	2,70
S	4,98	5,08
T	2,49	2,54
U	0,70	0,90



Pin 1 :	Base
Pin 2 :	Collector
Pin 3 :	Emitter
Package	Collector

Revised August 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may results from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.