

isc Silicon NPN Power Transistor

BDT91/93/95

DESCRIPTION

- DC Current Gain- $h_{FE} = 20 \sim 200 @ I_C = 4A$
- Collector-Emitter Sustaining Voltage-
: $V_{CEO(SUS)} = 60V(\text{Min})$ - BDT91; $80V(\text{Min})$ - BDT93;
100V(Min)- BDT95
- Complement to Type BDT92/94/96
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Designed for use in audio output stages and general amplifier and switching applications.

ABSOLUTE MAXIMUM RATINGS($T_a = 25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	BDT91 60	V
		BDT93 80	
		BDT95 100	
V_{CEO}	Collector-Emitter Voltage	BDT91 60	V
		BDT93 80	
		BDT95 100	
V_{EBO}	Emitter-Base Voltage	7	V
I_C	Collector Current-Continuous	10	A
I_{CM}	Collector Current-Peak	20	A
I_B	Base Current-Continuous	4	A
P_C	Collector Power Dissipation @ $T_C = 25^\circ\text{C}$	90	W
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-65~150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.4	$^\circ\text{C/W}$
$R_{th\ j-a}$	Thermal Resistance, Junction to Ambient	70	$^\circ\text{C/W}$



isc Silicon NPN Power Transistor

BDT91/93/95

ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage	BDT91	60			V
		BDT93	80			
		BDT95	100			
		$I_C=30\text{mA}; I_B=0$				
$V_{CE(sat)-1}$	Collector-Emitter Saturation Voltage	$I_C=4\text{A}; I_B=0.4\text{A}$			1	V
$V_{CE(sat)-2}$	Collector-Emitter Saturation Voltage	$I_C=10\text{A}; I_B=3.3\text{A}$			3	V
$V_{BE(on)}$	Base-Emitter On Voltage	$I_C=4\text{A}; V_{CE}=4\text{V}$			1.6	V
I_{CBO}	Collector Cutoff Current	$V_{CB}=V_{CB0max}; I_E=0$ $V_{CB}=1/2 V_{CB0max}; I_E=0, T_J=150^{\circ}\text{C}$			0.1 5	mA
I_{CEO}	Collector Cutoff Current	$V_{CE}=V_{CE0max} \text{ V}; I_B=0$			1	mA
I_{EBO}	Emitter Cutoff Current	$V_{EB}=7\text{V}; I_C=0$			1	mA
h_{FE-1}	DC Current Gain	$I_C=4\text{A}; V_{CE}=4\text{V}$	20		200	
h_{FE-2}	DC Current Gain	$I_C=10\text{A}; V_{CE}=4\text{V}$	5			
f_T	Current-Gain—Bandwidth Product	$I_C=500\text{mA}; V_{CE}=10\text{V}$	4			MHz
Switching times						
t_{on}	Turn-On Time	$I_C=4\text{A}; I_{B1}=-I_{B2}=0.4\text{A}$		0.5	1	μs
t_{off}	Turn-Off Time			2	4	μs

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.