

isc Silicon NPN Power Transistor
BDX35
DESCRIPTION

- High Current Capability- $I_C= 5A(DC)$
- DC Current Gain—
: $h_{FE} = 45-450(\text{Min}) @ I_C= 0.5 A$
- Collector-Emitter Breakdown Voltage-
: $V_{(BR)CEO}= 60V(\text{Min.})$
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- High-current switching in power applications.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	120	V
V_{CEO}	Collector-Emitter Voltage	60	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	5	A
I_{CM}	Collector Current-Peak	10	A
I_{BM}	Base Current-Peak	2	A
P_C	Collector Power Dissipation $T_a=25^\circ\text{C}$	1.25	W
	Collector Power Dissipation $T_C \leq 75^\circ\text{C}$	15	
T_j	Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-65~150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	5	$^\circ\text{C}/\text{W}$
$R_{th\ j-a}$	Thermal Resistance, Junction to Ambient	100	$^\circ\text{C}/\text{W}$



isc Silicon NPN Power Transistor
BDX35
ELECTRICAL CHARACTERISTICS
 $T_C=25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage	$I_C=10\text{mA}; I_B=0$	60		V
$V_{CE(sat)-1}$	Collector-Emitter Saturation Voltage	$I_C=5\text{A}; I_B=0.5\text{A}$		0.9	V
$V_{CE(sat)-2}$	Collector-Emitter Saturation Voltage	$I_C=7\text{A}; I_B=0.7\text{A}$		1.2	V
$V_{BE(sat)-1}$	Base-Emitter Saturation Voltage	$I_C=5\text{A}; I_B=0.5\text{A}$		1.7	V
$V_{BE(sat)-2}$	Base-Emitter Saturation Voltage	$I_C=7\text{A}; I_B=0.7\text{A}$		2.0	V
I_{CBO}	Collector Cutoff Current	$V_{CB}=80\text{V}; I_E=0$ $V_{CB}=80\text{V}; I_E=0; T_C=100^\circ\text{C}$		0.1 10	μA
I_{EBO}	Emitter Cutoff Current	$V_{EB}=5\text{V}; I_C=0$		0.1	μA
h_{FE}	DC Current Gain	$I_C=0.5\text{A}; V_{CE}=10\text{V}$	45	450	
f_T	Current-Gain—Bandwidth Product	$I_C=0.5\text{A}; V_{CE}=5\text{V}; f=100\text{MHz}$		100	MHz
C_{OB}	Collector Capacitance	$I_E=0; V_{CB}=10\text{V}; f_{\text{test}}=1\text{MHz}$		40	pF

Switching Times

t_{on}	Turn-On Time	$I_C=1\text{A}; I_{B1}=-I_{B2}=0.1\text{A}$			100	ns
t_{off}	Turn-Off Time				800	ns
t_{on}	Turn-On Time	$I_C=2\text{A}; I_{B1}=-I_{B2}=0.2\text{A}$			80	ns
t_{off}	Turn-Off Time				700	ns
t_{on}	Turn-On Time	$I_C=5\text{A}; I_{B1}=-I_{B2}=0.5\text{A}$			300	ns
t_{off}	Turn-Off Time				500	ns

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.