

# BM2300

N Channel Enhancement Mode MOSFET

4A


## DESCRIPTION

The BM2300 is the N-Channel logic enhancement mode power field effect transistor is produced using high cell density, DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance. These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management and other batter powered circuits, and low in-line power loss are needed in a very small outline surface mount package.

## PIN CONFIGURATION

### SOT-23-3L




1.Gate 2.Source 3.Drain

## FEATURE


- 20V/6.0A,  $R_{DS(ON)} = 27m\Omega$  (Typ.) @ $V_{GS} = 10V$
- 20V/5.0A,  $R_{DS(ON)} = 30m\Omega$  @ $V_{GS} = 4.5V$
- 20V/4.5A,  $R_{DS(ON)} = 34m\Omega$  @ $V_{GS} = 2.5V$
- 20V/4.0A,  $R_{DS(ON)} = 40m\Omega$  @ $V_{GS} = 1.8V$
- Super high density cell design for extremely low  $R_{DS(ON)}$
- Exceptional on-resistance and Maximum DC current capability
- SOT-23-3L package design

## PART MARKING

### SOT-23-3L



Y: Year Code A: Process Code



## ORDERING INFORMATION

Part Number	Package	Part Marking
BM2300	SOT-23-3L	42YA

※ Process Code : A ~ Z ; a ~ z

※ BM2300 : SOT23-3L R : Tape Reel ; G : Pb - Free

**BM2300**

N Channel Enhancement Mode MOSFET

4A

**ABSOLUTE MAXIMUM RATINGS (Ta = 25°C Unless otherwise noted )**

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V <sub>DSS</sub>	20	V
Gate-Source Voltage	V <sub>GSS</sub>	±12	V
Continuous Drain Current (T <sub>J</sub> =150°C)	I <sub>D</sub>	T <sub>A</sub> =25°C 4.0	A
		T <sub>A</sub> =70°C 3.0	
Pulsed Drain Current	I <sub>DM</sub>	13	A
Continuous Source Current (Diode Conduction)	I <sub>S</sub>	1.0	A
Power Dissipation	P <sub>D</sub>	T <sub>A</sub> =25°C 1.25	W
		T <sub>A</sub> =70°C 0.8	
Operation Junction Temperature	T <sub>J</sub>	150	°C
Storage Temperature Range	T <sub>STG</sub>	-55/150	°C
Thermal Resistance-Junction to Ambient	R <sub>θJA</sub>	140	°C/W

**BM2300**





N Channel Enhancement Mode MOSFET

4A





**ELECTRICAL CHARACTERISTICS ( Ta = 25°C Unless otherwise noted )**

Parameter	Symbol	Condition	Min	Typ	Max	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	20			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	0.4		1.0	V
Gate Leakage Current	$I_{GSS}$	$V_{DS}=0V, V_{GS}=\pm 20V$			$\pm 100$	nA
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=20V, V_{GS}=0V$			1	uA
		$V_{DS}=20V, V_{GS}=0V$ $T_J=85^\circ C$			10	
On-State Drain Current	$I_{D(on)}$	$V_{DS} \geq 5V, V_{GS}=4.5V$	6			A
Drain-source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=6.0A$ $V_{GS}=4.5V, I_D=5.0A$ $V_{GS}=2.5V, I_D=4.5A$ $V_{GS}=1.8V, I_D=4.0A$		0.027 0.030 0.034 0.040		$\Omega$
Forward Transconductance	$g_{fs}$	$V_{DS}=15V, I_D=5.0A$		30		S
Diode Forward Voltage	$V_{SD}$	$I_S=1.7A, V_{GS}=0V$		0.9	1.3	V
<b>Dynamic</b>						
Total Gate Charge	$Q_g$	$V_{DS}=10V$ $V_{GS}=4.5V$ $I_D=5A$		10	13	nC
Gate-Source Charge	$Q_{gs}$			1.4		
Gate-Drain Charge	$Q_{gd}$			2.1		
Input Capacitance	$C_{iss}$	$V_{DS}=10V$ $V_{GS}=0V$ $F=1MHz$		600		pF
Output Capacitance	$C_{oss}$			120		
Reverse Transfer Capacitance	$C_{rss}$			100		
Turn-On Time	$t_{d(on)}$ $t_r$	$V_{DD}=10V$ $R_L=10\Omega$ $I_D=1A$ $V_{GEN}=4.5V$ $R_G=6\Omega$		15	25	nS
				40	60	
Turn-Off Time	$t_{d(off)}$ $t_f$			45	65	
				30	40	


**TYPICAL CHARACTERISTICS (25°C Unless noted)**



**TYPICAL CHARACTERISTICS (25°C Unless noted)**




**TYPICAL CHARACTERISTICS**



**BM2300**

N Channel Enhancement Mode MOSFET

4A

**SOT-23-3L PACKAGE OUTLINE**

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.400	0.012	0.016
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.700REF		0.028REF	
L1	0.300	0.600	0.012	0.024
$\theta$	0°	8°	0°	8°