

1. MODEL NUMBER

MODEL NUMBER.	CUSTOMER PART NO.
BP65R1505S112	

2. TEST CONDITION

2-1 TYPICAL CONDITION : -TEMPERATURE : 20℃

-HUMIDITY : 65%RH

2-2 STANDARD CONDITION : -TEMPERATURE :-40℃ to +85℃

-HUMIDITY : 45%RH to 85%RH

3. COMPOSITION AND MATERIAL

NO.	NAME	COMPOSITION AND MATERIALS
3-1	RESONATOR	DIELECTRIC MATERIALS
3-2	NUMBER OF POLE	5 POLE
3-3	IN/OUTPUT TERMINALS	Ag or Sn PLATED
3-4	GROUND BASE	Ag or Sn PLATED

4. ELECTRICAL SPECIFICATIONS

NO.	ITEM	SPECIFICATIONS
4-1	CENTER FREQUENCY(f_0)	1505.0MHz
4-2	BAND WIDTH	± 56.0 MHz
4-3	INSERTION LOSS IN BW	2.0dB max.
4-4	RIPPLE	1.0dB max.
4-5	RETURN LOSS	15dB min.
4-6	ATTENUATION	70dB min. at 1182MHz 63dB min. at 1842MHz
4-7	INPUT POWER	1 W
4-8	NOMINAL CHARACTERISIC IMPEDANCE	50 Ω



SIPAT Co., Ltd.
 (CETC No. 26 Research Institute)
 Nanping Huayuan Road No. 14
 Chongqing, China, 400060


Part Number BP65R1505S112

Rev. Date 2005-9-21


Rev. 1.0

Page 1 / 3


5. DIMENSIONS



6. RECOMMENDED REFLOW PAD





7. REFLOW SOLDERING STANDARD CONDITIONS



SIPAT Co., Ltd.
 (CETC No. 26 Research Institute)
 Nanping Huayuan Road No. 14
 Chongqing, China, 400060

Part Number	BP65R1505S112	
Rev. Date	2005-9-21	
Rev.	1.0	Page 2/3

8.CHARACTERISTICS



SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060

Part Number	BP65R1505S112	
Rev. Date	2005-9-21	
Rev.	1.0	Page 3/3