

SOT89 PNP SILICON PLANAR HIGH VOLTAGE TRANSISTOR

LUCAS (Type) (P) (S) (E) (C) (T) (A) (M) (T)

BST15

ISSUE 3 – FEBRUARY 1996




FEATURES

- * High V_{CE0}
- * Low saturation voltage

COMPLEMENTARY TYPE – BST40

PARTMARKING DETAIL – BT1



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	-200	V
Collector-Emitter Voltage	V_{CEO}	-200	V
Emitter-Base Voltage	V_{EBO}	-4	V
Peak Pulse Current	I_{CM}	-1	A
Continuous Collector Current	I_C	-500	mA
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{tot}	1	W
Operating and Storage Temperature Range	$T_j; T_{stg}$	-65 to +150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-200			V	$I_C = -100\mu\text{A}$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-200			V	$I_C = -1\text{mA}$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-4			V	$I_E = -100\mu\text{A}$
Collector Cut-Off Current	I_{CBO}			-1	μA	$V_{CB} = -175\text{V}$
Collector Cut-Off Current	I_{CEO}			-50	μA	$V_{CB} = -150\text{V}$
Emitter Cut-Off Current	I_{EBO}			-20	μA	$V_{EB} = -4\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$			- 2.0 -0.5	V	$I_C = -50\text{mA}, I_B = -5\text{mA}^*$ $I_C = -30\text{mA}, I_B = -3\text{mA}^*$
Static Forward Current Transfer Ratio	h_{FE}	30		150		$I_C = -50\text{mA}, V_{CE} = -10\text{V}^*$
Transition Frequency	f_T	15			MHz	$I_C = -10\text{mA}, V_{CE} = -10\text{V}^*$ $f = 30\text{MHz}$
Output Capacitance	C_{obo}			15	pF	$V_{CB} = -10\text{V}, f = 1\text{MHz}$

*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$
For typical characteristics graphs see FMMTA92 datasheet.