


**PNP SILICON PLANAR EPITAXIAL TRANSISTORS**

**BSV15  
BSV16  
BSV17  
TO- 39**



**ABSOLUTE MAXIMUM RATINGS**

DESCRIPTION	SYMBOL	BSV15	BSV16	BSV17	UNIT
Collector -Emitter Voltage	VCEO	40	60	80	V
Collector -Emitter Voltage	VCES	40	60	90	V
Emitter -Base Voltage	VEBO	5.0	5.0	5.0	V
Collector Current (DC)	IC		1.0		A
Base Current (DC)	IB		200		mA
Power Dissipation up to Tamb=25 degC	Ptot		0.8		W
Power Dissipation up to Tcase=25 degC			5.0		W
Power Dissipation up to Tmb=50 degC			5.0		W
Operating And Storage Junction Temperature Range	Tj, Tstg		-65 to +200		deg C
<b>THERMAL RESISTANCE</b>					
Junction to Ambient	Rth(j-a)		220		K/W
Junction to Case	Rth(j-c)		35		K/W
Junction to Mounting Base	Rth(j-mb)		30		K/W

**ELECTRICAL CHARACTERISTICS (Ta=25 deg C Unless Otherwise Specified)**


DESCRIPTION	SYMBOL	TEST CONDITION	BSV15	BSV16	BSV17	UNIT	
Collector-Cut off Current	ICES	VBE=0, VCE=40V	<100	-	-	nA	
		VBE=0, VCE=60V	-	<100	-	nA	
		VBE=0, VCE=80V	-	-	<100	nA	
	ICEX	Tamb=150 deg C					
		VBE=0, VCE=40V	<50	-	-	uA	
		VBE=0, VCE=60V	-	<50	-	uA	
		VBE=0, VCE=80V	-	-	<50	uA	
Emitter-Cut off Current	IEBO	Tamb=100 deg C					
		VBE=0.2V, VCE=40V	<50	-	-	uA	
		VBE=0.2V, VCE=60V	-	<50	-	uA	
		VBE=0.2V, VCE=80V	-	-	<50	uA	
Collector -Emitter Voltage	VCEO*	IC=50mA, IB=0	>40	>60	>80	V	
		VCES	VBE=0, IC=10uA	>40	>60	>90	V
Emitter-Base Voltage	VEBO	IE=10uA, IC=0	>5.0	>5.0	>5.0	V	
Base Emitter on Voltage	VBE(on)	IC=100mA, VCE=1V	<b>ALL</b>	<1.0		V	
		IC=500mA, VCE=1V	<b>ALL</b>	0.7 to 1.4		V	
Collector Emitter Saturation Voltage	VCE(Sat)	IC=500mA, IB=25mA	<b>ALL</b>	<1.0		V	

**ELECTRICAL CHARACTERISTICS (Ta=25 deg C Unless Otherwise Specified)**

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT	
<b>DC Current</b>	hFE	IC=0.1mA, VCE=1V					
		<b>BSV15-10</b>	20	-	-		
		<b>BSV16-10</b>	20	-	-		
		<b>BSV17-10</b>	20	-	-		
		<b>BSV15-16</b>	30	-	-		
		<b>BSV16-16</b>	30	-	-		
		IC=100mA, VCE=1V					
		<b>BSV15-10</b>	63	-	160		
		<b>BSV16-10</b>	63	-	160		
		<b>BSV17-10</b>	63	-	160		
		<b>BSV15-16</b>	100	-	250		
		<b>BSV16-16</b>	100	-	250		
		IC=500mA, VCE=1V					
		<b>BSV15-10</b>	25	-	-		
		<b>BSV16-10</b>	25	-	-		
<b>BSV17-10</b>	25	-	-				
<b>BSV15-16</b>	35	-	-				
<b>BSV16-16</b>	35	-	-				
<b>Collector Capacitance</b>	Cc	IE=ie=0, VCB=10V, f=1MHz					
		<b>BSV15</b>	-	-	30	pF	
		<b>BSV16</b>	-	-	30	pF	
<b>Emitter Capacitance</b>	Ce	IC=Ic=0, VEB=0.5V, f=1MHz					
		<b>ALL</b>	-	180	-	pF	
<b>Transition Frequency</b>	ft	VCE=10V, IC=50mA, f=20MHz					
		<b>ALL</b>	50	-	-	MHZ	
<b>Small Signal Current Gain</b>	hfe	IC=1mA, VCE=5V, f=1kHz					
		<b>ALL</b>	20	-	-		
<b><u>Switching Time</u></b>							
<b>Turn off time</b>	ton		-	-	500	ns	
<b>Stroage time</b>	toff	IC=100mA, -IB=+IBM=5mA	-	-	650	ns	
<b>Fall time</b>	ts		-	-	500	ns	
	tf		-	-	150	ns	


\*Pulse time= 200us, duty cycle=1%

## TO-39 Metal Can Package



All dimensions are in mm

DIM	MIN	MAX
A	8.50	9.39
B	7.74	8.50
C	6.09	6.60
D	0.40	0.53
E	—	0.88
F	2.41	2.66
G	4.82	5.33
H	0.71	0.86
J	0.73	1.02
K	12.70	—
L	42 DEG	48 DEG



### PIN CONFIGURATION

1. EMITTER
2. BASE
3. COLLECTOR

### Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-39	500 pcs/polybag	540 gm/500 pcs	3" x 7.5" x 7.5"	20.0K	17" x 15" x 13.5"	32.0K	40 kgs

### Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of

**Continental Device India Limited**

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone + 91-11-579 6150 Fax + 91-11-579 9569, 579 5290

e-mail sales@cdil.com www.cdil.com