

PNP BSV15 – BSV16 – BSV17

MEDIUM POWER TRANSISTORS

They are silicon transistors mounted in TO-39 metal package.
They are intended for general industrial applications.
High current and low voltage.
Compliance to RoHS.

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings	Value	Unit	
V_{CBO}	Collector-Base Voltage $I_E = 0$	BSV15	-40	V
		BSV16	-60	
		BSV17	-90	
V_{CEO}	Collector-Emitter Voltage $I_B = 0$	BSV15	-40	V
		BSV16	-60	
		BSV17	-90	
V_{EBO}	Emitter-Base Voltage $I_C = 0$	-5	V	
I_C	Collector Current	-1	A	
I_{CM}	Peak Collector Current	-2	A	
I_{BM}	Peak Base Current	-0.2	A	
P_{tot}	Total Power Dissipation	@ $T_{case} = < 25^\circ$	0.8	W
		@ $T_{amb} = < 25^\circ$	5	
		@ $T_{mb} = < 50^\circ$	5	
T_J	Junction Temperature	200	$^\circ\text{C}$	
T_{Stg}	Storage Temperature Range	-65 to +150	$^\circ\text{C}$	
T_{amb}	Operating Ambient Temperature	-65 to +150	$^\circ\text{C}$	

THERMAL CHARACTERISTICS

Symbol	Ratings	Value	Unit
R_{thJ-c}	Thermal Resistance, Junction-case	35	K/ W
$R_{thJ-amb}$	Thermal Resistance, Junction-ambient in free air	220	K/ W
R_{thJ-mb}	Thermal Resistance, Junction to mounting base	30	K/ W

PNP BSV15 – BSV16 – BSV17

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted

Symbol	Ratings	Test Condition(s)		Min	Typ	Max	Unit	
I_{CBO}	Collector – Cutoff Current	$I_E = 0, V_{CB} = -40\text{ V}$		BSV15	-	-100	nA	
		$I_E = 0, V_{CB} = -60\text{ V}$		BSV16				
		$I_E = 0, V_{CB} = -80\text{ V}$		BSV17				
		$I_E = 0, V_{T_{amb}} = 150^\circ\text{C}$	$V_{CB} = -40\text{ V}$	BSV15	-	-	-50	μA
$V_{CB} = -60\text{ V}$	BSV16							
$V_{CB} = -80\text{ V}$	BSV17							
I_{EBO}	Emitter – Cutoff Current	$I_C = 0, V_{CE} = -4\text{ V}$		BSV15	-	-	-50	nA
		BSV16						
		BSV17						
$V_{CE(SAT)}$	Collector-Emitter saturation Voltage (*)	$I_C = -500\text{ mA}, I_B = -25\text{ mA}$		BSV15	-	-	-1	V
		BSV16						
		BSV17						
V_{BE}	Base-Emitter Voltage (*)	$I_C = -100\text{ mA}, V_{CE} = -1\text{ V}$		BSV15	-	-	-1	V
				BSV16				
				BSV17				
		$I_C = -500\text{ mA}, V_{CE} = -1\text{ V}$		BSV15	-	-	-1	V
BSV16								
BSV17								
h_{FE}	DC Current Gain (*)	$I_C = -100\ \mu\text{A}, V_{CE} = -1\text{ V}$	Gr.10	BSV15	20	75	-	-
				BSV16				
				BSV17				
			Gr.16	BSV15				
				BSV16				
				BSV17				
		$I_C = -100\text{ mA}, V_{CE} = -1\text{ V}$	Gr.10	BSV15	63	100	160	
				BSV16				
				BSV17				
			Gr.16	BSV15				
				BSV16				
				BSV17				
$I_C = -500\text{ mA}, V_{CE} = -1\text{ V}$	Gr.10	BSV15	25	55	-			
		BSV16						
		BSV17						
	Gr.16	BSV15						
		BSV16						
		BSV17						

PNP BSV15 – BSV16 – BSV17

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted

Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit	
f_T	Transition Frequency	$I_C = -50 \text{ mA}$, $V_{CE} = -10 \text{ V}$ $f = 100 \text{ MHz}$	50	-	-	MHz	
C_C	Collector Capacitance	$I_E = i_e = 0$, $V_{CB} = -10 \text{ V}$ $f = 1 \text{ MHz}$	BSV15	-	20	30	pF
			BSV16	-	15	25	
			BSV17	-	15	25	
C_E	Emitter Capacitance	$I_E = i_e = 0$, $V_{CB} = -10 \text{ V}$ $f = 1 \text{ MHz}$	-	180	-	pF	

SWITCHING TIME

Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit
t_{off}	Turn-off times	$I_C = -100 \text{ mA}$ — $I_{Bon} = -5 \text{ mA}$ $I_{Boff} = 5 \text{ mA}$	-	-	650	ns
t_{on}	Turn-on times		-	-	500	ns


(*) Pulsed : pulse duration = 300µs, duty cycle = 1%

PNP BSV15 – BSV16 – BSV17

MECHANICAL DATA CASE TO-39

DIMENSIONS (mm)		
	min	max
A	8.50	9.39
B	7.74	8.50
C	6.09	6.60
D	0.40	0.53
E	-	0.88
F	2.41	2.66
G	4.82	5.33
H	0.71	0.86
J	0.73	1.02
K	12.70	-
L	42°	48°

Pin 1 :	Emitter
Pin 2 :	Base
Pin 3 :	Collector
Case :	Collector



Revised October 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.