


OptiMOS™2 + OptiMOS™-P 2 Small Signal Transistor
Features

- Complementary P + N channel
- Enhancement mode
- Super Logic level (2.5V rated)
- Common drain
- Avalanche rated
- 175 °C operating temperature
- Qualified according to AEC Q101
- 100% lead-free; RoHS compliant
- Halogen-free according to IEC61246-21


Product Summary

		P	N	
V_{DS}		-20	20	V
$R_{DS(on),max}$	$V_{GS}=\pm 4.5\text{ V}$	150	55	mΩ
	$V_{GS}=\pm 2.5\text{ V}$	310	95	
I_D		-3.2	5.1	A



Type	Package	Marking	Lead Free	Halogen Free	Packing
BSZ215C H	PG-TSDSON-8 LTI	215C	Yes	Yes	Non dry

Maximum ratings, at $T_j=25\text{ °C}$, unless otherwise specified ¹⁾

Parameter	Symbol	Conditions	Value		Unit
			P	N	
Continuous drain current	I_D	$T_A=25\text{ °C}$	-3.2	5.1	A
		$T_A=100\text{ °C}$	-2.2	3.6	
Pulsed drain current	$I_{D,pulse}$	$T_A=25\text{ °C}$	-13	20	
Avalanche energy, single pulse	E_{AS}	P: $I_D=-3.2\text{ A}$, N: $I_D=5.1\text{ A}$, $R_{GS}=25\text{ Ω}$	11	11	mJ
Gate source voltage	V_{GS}		± 12		V
Power dissipation	$P_{tot}^{2)}$	$T_A=25\text{ °C}$	2.5		W
Operating and storage temperature	T_j, T_{stg}		-55 ... 175		°C
ESD class		JESD22-A114-HBM	0 (<250V)		
Soldering temperature	T_{solder}		260		°C
IEC climatic category; DIN IEC 68-1			55/175/56		

¹⁾ Remark: only one of both transistors active

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Thermal characteristics

Thermal resistance, junction - case	P	R_{thJC}		-	-	8	K/W
	N						
Device on PCB		R_{thJA}	6 cm ² cooling area ²⁾	-	-	60	K/W

Electrical characteristics, at $T_j=25\text{ °C}$, unless otherwise specified
Static characteristics

Drain-source breakdown voltage	P	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}, I_D=-250\text{ }\mu\text{A}$	-	-	-20	V
	N		$V_{GS}=0\text{ V}, I_D=250\text{ }\mu\text{A}$	20	-	-	
Gate threshold voltage	P	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-110\text{ }\mu\text{A}$	-1.4	-1.0	-0.7	
	N		$V_{DS}=V_{GS}, I_D=110\text{ }\mu\text{A}$	0.8	1.1	1.4	
Zero gate voltage drain current	P	I_{DSS}	$V_{DS}=-20\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ °C}$	-	-	-0.1	μA
	N		$V_{DS}=20\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ °C}$	-	-	0.1	
	P		$V_{DS}=-20\text{ V}, V_{GS}=0\text{ V}, T_j=175\text{ °C}$	-	-	-50	
	N		$V_{DS}=20\text{ V}, V_{GS}=0\text{ V}, T_j=175\text{ °C}$	-	-	50	
Gate-source leakage current	P	I_{GSS}	$V_{GS}=\pm 12\text{ V}, V_{DS}=0\text{ V}$	-	-	± 100	nA
	N						
Drain-source on-state resistance	P	$R_{DS(on)}$	$V_{GS}=-2.5\text{ V}, I_D=2.1\text{ A}$	-	144	310	m Ω
	N		$V_{GS}=2.5\text{ V}, I_D=1.9\text{ A}$	-	63	95	
	P		$V_{GS}=-4.5\text{ V}, I_D=-3.2\text{ A}$	-	95	150	
	N		$V_{GS}=4.5\text{ V}, I_D=5.1\text{ A}$	-	41	55	
Transconductance	P	g_{fs}	$ V_{DS} >2 I_D R_{DS(on)max}, I_D=-2.2\text{ A}$	4	7.9	-	S
	N		$ V_{DS} >2 I_D R_{DS(on)max}, I_D=3.6\text{ A}$	5.5	11	-	

²⁾ Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm² (one layer, 70 μm thick) copper area for drain connection. PCB is vertical in still air.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Dynamic characteristics

Input capacitance	P	C_{iss}	$V_{GS}=0\text{ V}$, P: $V_{DS}=-10\text{ V}$, N: $V_{DS}=10\text{ V}$, $f=1\text{ MHz}$	-	300	400	pF
	N			-	315	419	
Output capacitance	P	C_{oss}		-	92	120	
	N			-	114	152	
Reverse transfer capacitance	P	C_{rss}		-	92	140	
	N			-	16	24	
Turn-on delay time	P	$t_{d(on)}$	P: $V_{DD}=-10\text{ V}$, $V_{GS}=-4.5\text{ V}$, $R_G=6\text{ }\Omega$, $I_D=-3.2\text{ A}$ N: $V_{DD}=10\text{ V}$, $V_{GS}=4.5\text{ V}$, $R_G=6\text{ }\Omega$, $I_D=5.1\text{ A}$	-	7.4	-	ns
	N			-	4.9	-	
Rise time	P	t_r		-	3.7	-	
	N			-	2.0	-	
Turn-off delay time	P	$t_{d(off)}$		-	11.3	-	
	N			-	12.2	-	
Fall time	P	t_f		-	4.7	-	
	N			-	1.4	-	

Gate Charge Characteristics

Gate to source charge	P	Q_{gs}	$V_{DD}=-10\text{ V}$, $I_D=-3.2\text{ A}$, $V_{GS}=0\text{ to }-4.5\text{ V}$	-	-0.58	-0.8	nC
Gate to drain charge		Q_{gd}		-	-1.3	-1.7	
Switching charge		Q_g		-	-3.0	-4.6	
Gate plateau voltage		$V_{plateau}$		-	-1.9	-	
Gate to source charge	N	Q_{gs}	$V_{DD}=10\text{ V}$, $I_D=5.1\text{ A}$, $V_{GS}=0\text{ to }4.5\text{ V}$	-	0.7	1.0	
Gate to drain charge		Q_{gd}		-	0.4	-	
Switching charge		Q_g			2.1	2.8	
Gate plateau voltage		$V_{plateau}$			2.3		


Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Reverse Diode

Diode continuous forward current	P	I_S	$T_C=25\text{ }^{\circ}\text{C}$	-	-	-2.1	A
	N					2.3	
Diode pulse current	P	$I_{S,pulse}$		-	-	-13	
	N					20	
Diode forward voltage	P	V_{SD}	$V_{GS}=0\text{ V}, I_F=3.2\text{ A}, T_j=25\text{ }^{\circ}\text{C}$	-	-0.98	-1.2	V
	N		$V_{GS}=0\text{ V}, I_F=5.1\text{ A}, T_j=25\text{ }^{\circ}\text{C}$	-	0.9	1.2	
Reverse recovery time	P	t_{rr}	$V_R=\pm 10\text{ V}, I_F=I_S, di_F/dt=100\text{ A}/\mu\text{s}$		12.2		ns
	N			-	10.9	-	
Reverse recovery charge	P	Q_{rr}			4.6		nC
	N			-	3.4	-	


1 Power dissipation (P)

$$P_{\text{tot}} = f(T_A)$$



2 Power dissipation (N)


$$P_{\text{tot}} = f(T_A)$$



3 Drain current (P)

$$I_D = f(T_A)$$


parameter: $V_{GS} \leq -4.5$ V



4 Drain current (N)

$$I_D = f(T_A)$$


parameter: $V_{GS} \geq 4.5$ V



5 Safe operating area (P)

$$I_D = f(V_{DS}); T_A = 25^\circ\text{C}; D = 0$$


parameter: t_p



6 Safe operating area (N)

$$I_D = f(V_{DS}); T_A = 25^\circ\text{C}; D = 0$$


parameter: t_p



7 Max. transient thermal impedance (P)

$$Z_{thJA} = f(t_p)$$


parameter: $D = t_p/T$



8 Max. transient thermal impedance (N)


$$Z_{thJA} = f(t_p)$$

parameter: $D = t_p/T$




9 Typ. output characteristics (P)

 $I_D = f(V_{DS}); T_j = 25^\circ\text{C}$

parameter: V_{GS}



10 Typ. output characteristics (N)

 $I_D = f(V_{DS}); T_j = 25^\circ\text{C}$

parameter: V_{GS}



11 Typ. drain-source on resistance (P)

 $R_{DS(on)} = f(I_D); T_j = 25^\circ\text{C}$

parameter: V_{GS}


12 Typ. drain-source on resistance (N)


 $R_{DS(on)} = f(I_D); T_j = 25^\circ\text{C}$

parameter: V_{GS}


13 Typ. transfer characteristics (P)

$$I_D = f(V_{GS}); |V_{DS}| > 2 |I_D| R_{DS(on)max}$$


parameter: T_j



14 Typ. transfer characteristics (N)


$$I_D = f(V_{GS}); |V_{DS}| > 2 |I_D| R_{DS(on)max}$$

parameter: T_j




15 Drain-source on-state resistance (P)

$$R_{DS(on)} = f(T_j); I_D = -3.2 \text{ A}; V_{GS} = -4.5 \text{ V}$$




16 Drain-source on-state resistance (N)


$$R_{DS(on)} = f(T_j); I_D = 5.1 \text{ A}; V_{GS} = 4.5 \text{ V}$$




17 Typ. gate threshold voltage (P)

 $V_{GS(th)} = f(T_j); V_{GS} = V_{DS}; I_D = -110 \mu A$



18 Typ. gate threshold voltage (N)

 $V_{GS(th)} = f(T_j); V_{GS} = V_{DS}; I_D = 110 \mu A$


19 Typ. capacitances (P)

 $C = f(V_{DS}); V_{GS} = 0 V; f = 1 MHz$



20 Typ. capacitances (N)

 $C = f(V_{DS}); V_{GS} = 0 V; f = 1 MHz$


21 Forward characteristics of reverse diode (P)

$$I_F = f(V_{SD})$$


parameter: T_j



22 Forward characteristics of reverse diode (N)

$$I_F = f(V_{SD})$$


parameter: T_j



23 Avalanche characteristics (P)

$$I_{AS} = f(t_{AV}); R_{GS} = 25 \Omega$$


parameter: $T_{j(start)}$



24 Avalanche characteristics (N)


$$I_{AS} = f(t_{AV}); R_{GS} = 25 \Omega$$

parameter: $T_{j(start)}$




25 Typ. gate charge (P)

 $V_{GS}=f(Q_{gate}); I_D=-3.2A$ pulsed


parameter: V_{DD}


26 Typ. gate charge (N)


 $V_{GS}=f(Q_{gate}); I_D=5.1A$ pulsed

parameter: V_{DD}


27 Drain-source breakdown voltage (P)


 $V_{BR(DSS)}=f(T_j); I_D=-250 \mu A$


28 Drain-source breakdown voltage (N)

 $V_{BR(DSS)}=f(T_j); I_D=250 \mu A$


PG-TSDSON-8LTI

PG-TSDSON-8LTI : Outline



Dimensions in mm

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2010 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.