


## DESCRIPTION

The BT151S-800R of silicon controlled rectifier, with high ability to withstand the shock loading of large current, provide high dv/dt rate with strong resistance to electromagnetic interference. It is especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc.

## MAIN FEATURES

Symbol	Value	Unit
$V_{DRM}/V_{RRM}$	$\geq 800$	V
$I_{T(RMS)}$	$\geq 12$	A
$I_{GT}$	$\leq 15$	mA



## ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter		Value	Unit
$V_{DRM}$	Repe. tive peak off-state voltage	$T_J=25^\circ\text{C}$	800	V
$V_{RRM}$	Repetitive peak reverse voltage	$T_J=25^\circ\text{C}$	800	V
$I_{T(RMS)}$	RMS on-state current(360°conduction angle)	$T_C=98^\circ\text{C}$	12	A
$I_{TSM}$	Non repetitive surge peak on-state current	$T_P=10\text{ms}$	120	A
$I^2t$	$I^2t$ value for fusing	$T_P=10\text{ms}$	72	$\text{A}^2\text{s}$
$di_T/dt$	Repetitive rate of rise of on-state current	$I_G=2I_{GT}$	50	$\text{A}/\mu\text{s}$
$I_{GM}$	Peak gate current	$T_J=25^\circ\text{C}$	2	A
$P_{GM}$	Peak gate power	$T_J=25^\circ\text{C}$	5	W
$P_{G(AV)}$	Average gate power dissipation	$T_J=25^\circ\text{C}$	0.5	W
$T_{stg}$	Storage temperature range		$-40\sim+150$	$^\circ\text{C}$
$T_J$	Operating junction temperaturerange		$-40\sim+125$	$^\circ\text{C}$

## ELECTRICAL CHARACTERISTICS( $T_J=25^\circ\text{C}$ unless otherwise specified)

Symbol	Test Conditions	Value			Unit
		Min.	Typ.	Max.	
$I_{GT}$	$V_D=12\text{V } R_L=33\Omega$	-	4	15	V
$V_{GT}$	$V_D=12\text{V } R_L=33\Omega$	-	0.75	1.5	V
$V_{GD}$	$V_D=V_{DRM} R_L=33\text{K}\Omega T_J=125^\circ\text{C}$	0.2	-	-	V
$I_H$	$I_T=500\text{mA}$	-	12	30	mA
$I_L$	$I_G=1.2I_{GT}$	-	12	40	mA
	$V_D=2/3V_{DRM}$ Gate Open $T_J=125^\circ\text{C}$	200	400	-	$\text{V}/\mu\text{s}$








**STATIC CHARACTERISTICS**

Symbol	Parameter	Value	Unit
$V_{TM}$	$I_{TM}=23A$ $t_p=380\mu s$	$T_j=25^\circ C$	$\leq 1.7$ V
$I_{DRM}$	$V_D=V_{DRM}$ $V_R=V_{RRM}$	$T_j=25^\circ C$	$\leq 10$ uA
$I_{RRM}$	$V_D=V_{DRM}$ $V_R=V_{RRM}$	$T_j=125^\circ C$	$\leq 1.0$ mA


**THERMAL RESISTANCES**

Symbol	Parameter	Value	Unit
$R_{th(j-mb)}$	Junction to mounting base	2.0	$^\circ C/W$

**RATINGS AND CHARACTERISTIC CURVES ( $T_A=25^\circ C$  unless otherwise noted)**

**FIG.1: Maximum power dissipation versus RMS on-state current**

**FIG.2: RMS on-state current versus case temperature**

**FIG.3: Surge peak on-state current versus number of cycles**

**FIG.4: On-state characteristics (maximum values)**





**FIG.5:** Non-repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 10\text{ms}$ , and corresponding value of  $I(dv/dt < 50\text{A}/\mu\text{s})$



**FIG.6:** Relative variations of gate trigger current, holding current and latching current versus junction temperature

### TO-252 PACKAGE INFORMATION



## CONTACT US

### Headquarters

A Building Caohejing I&E Park Pujiang Minhang Shanghai  
China

### Hotline

400-021-5756

### Web

<http://www.semiware.com.cn>

### By Telephone

Sales: 86-21-3463-7345  
Customer Service: 86-21-3463-7172-8810/8826  
Technical Support: 86-21-3463-7173-8811

### By Email

Sales: [sales03@semiware.com.cn](mailto:sales03@semiware.com.cn)  
Customer Service: [sales17@semiware.com.cn](mailto:sales17@semiware.com.cn)  
Technical Support: [fae03@semiware.com.cn](mailto:fae03@semiware.com.cn)

### By Fax

General: 86-21-3965-0654  
Sales: 86-21-3463-7458

COPYRIGHT ©Semiware 2009 - This literature is subject to all applicable copyright laws and is not for resale in any manner.

SPECIFICATIONS: Semiware reserves the right to change the electrical and/or mechanical characteristics described herein without notice.

DESIGN CHANGES: Semiware reserves the right to discontinue product lines without notice and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, Semiware assumes no responsibility with respect to the selection or specifications of such products. Semiware makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Semiware assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability without limitation special, consequential or incidental damages.

LIFE SUPPORT POLICY: Semiware products are not authorized for use in life support systems without written consent from the factory.

