

# BTA08F

Rev.E Mar.-2016

## 描述 / Descriptions

TO-220F 塑封封装 双向可控硅。Triac in a TO-220F Plastic Package.

## 特征 / Features

中电流可控硅，低通态压降，高可靠性和稳定性，热敏电阻特性低，绝缘 BTA。

Medium current triac, Low on state voltage drop, High reliability and stability, Low thermal resistance, insulated BTA.

## 用途 / Applications

适用于一般用途交流开关。如固态继电器、加热调节、异步电动机起动电路、电机速度控制器等。

Suitable for general purpose AC switching .Such as static relays, heating regulation, induction motor starting circuits, motor speed controllers, etc.

## 内部等效电路 / Equivalent Circuit



## 引脚排列 / Pinning



PIN1 : Main Terminal 1    PIN 2 : Main Terminal 2    PIN 3: Gate

## 放大及印章代码 / $h_{FE}$ Classifications & Marking

见印章说明。See Marking Instructions.

**极限参数 / Absolute Maximum Ratings(Ta=25°C)**

参数 Parameter	符号 Symbol	数值 Rating	单位 Unit
Repetitive peak off-state voltages	$V_{DRM}/V_{RRM}$	600 and 800	V
RMS on-state current(full sine wave $T_C=105^{\circ}C$ )	$I_{T(RMS)}$	8.0	A
Non repetitive surge peak on-state current(full cycle, $T_i$ initial= $25^{\circ}C$ )	$I_{TSM}(F=50Hz$ $t=20ms)$	80	A
Non repetitive surge peak on-state current(full cycle, $T_i$ initial= $25^{\circ}C$ )	$I_{TSM}(F=60Hz$ $t=16.7ms)$	84	A
$I_t^2$ Value for fusing	$I^2t_{(tp=10ms)}$	36	$A^2s$
Critical rate of rise of on-state current $I_G$ $=2 \times I_{GT} t_r \leq 100 ns$ ( $F=120Hz$ $T_j=125^{\circ}C$ )	$di/dt$	50	$A/\mu s$
Peak gate current( $t_p = 20\mu s$ $T_j=125^{\circ}C$ )	$I_{GM}$	4.0	A
Average gate power dissipation( $T_j=125^{\circ}C$ )	$P_{G(AV)}$	1.0	W
Operating junction temperature range	$T_j$	-40~125	$^{\circ}C$
Storage junction temperature range	$T_{stg}$	-40~150	$^{\circ}C$
Junction to ambient	$R_{th(j-a)}$	60	$^{\circ}C/W$
Junction to case (AC)	$R_{th(j-c)}$	2.5	$^{\circ}C/W$

**电性能参数 / Electrical Characteristics(Ta=25°C)**

**免缓冲器和逻辑电平 (3象限) / Snubberless and logic level (3 quadrants)**

符号 Symbol	测试条件 Test Conditions	信号区 Quadrant		BTA08F				单位 Unit
				TW	SW	CW	BW	
$I_{GT}^{(1)}$	$V_D=12V$ $R_L=30\Omega$	I-II-III	Max.	5	10	35	50	mA
$V_{GT}$	$V_D=12V$ $R_L=30\Omega$	I-II-III	Max.	1.3				V
$V_{GD}$	$V_D=V_{DRM}$ $R_L=3.3K\Omega$ $T_j=125^{\circ}C$	I-II-III	Min.	0.2				V
$I_H^{(2)}$	$I_T=100mA$		Max.	10	15	35	50	mA
$I_L$	$I_G=1.2I_{GT}$	I-III	Max.	10	25	50	70	mA
		II		15	30	60	80	
$(dV/dt)^{(2)}$	$V_D=67\% V_{DRM}$ gate open $T_j=125^{\circ}C$		Min.	20	40	400	1000	$V/\mu s$
$(di/dt)_c^{(2)}$	$(dV/dt)_c=0.1V/\mu s$ $T_j=125^{\circ}C$		Min.	3.5	5.4	-	-	A/m s
	$(dV/dt)_c=10V/\mu s$ $T_j=125^{\circ}C$		Min.	1.5	2.98	-	-	
	Without snubber $T_j=125^{\circ}C$		Min.	-	-	4.5	7	

Note 1: minimum  $I_{GT}$  is guaranteed at 5% of  $I_{GT}$  max.

Note 2: for both polarities of A2 referenced to A1.

**电性能参数 / Electrical Characteristics(Ta=25°C)**  
**标准 (4象限) / Standard (4 quadrants)**

符号 Symbol	测试条件 Test Conditions	信号区 Quadrant		BTA08F		单位 Unit
				C	B	
$I_{GT}^{(1)}$	$V_D=12V R_L=30\Omega$	I-II-III IV	Max.	25 50	50 100	mA
$V_{GT}$	$V_D=12V R_L=30\Omega$	ALL	Max.	1.3		V
$V_{GD}$	$V_D=V_{DRM} R_L=3.3K\Omega$ $T_j=125^\circ C$	ALL	Min.	0.2		V
$I_H^{(2)}$	$I_T=500mA$		Max.	25	50	mA
$I_L$	$I_G=1.2I_{GT}$	I-III-IV	Max.	40	50	mA
		II		80	100	
$(dV/dt)^{(2)}$	$V_D=67\% V_{DRM}$ gate open $T_j=125^\circ C$		Min.	200	400	V/ $\mu s$
$(dI/dt)^{(2)}$	$(dI/dt)_c=5.3A/ms$ $T_j=125^\circ C$		Min.	5.0	10	







Note 1: minimum  $I_{GT}$  is guaranteed at 5% of  $I_{GT}$  max.  
Note 2: for both polarities of A2 referenced to A1.

**电性能参数 / Electrical Characteristics(Ta=25°C)**







符号 Symbol	测试条件 Test Conditions		数值 Value	单位 Unit	
$V_{TM}^{(2)}$	$I_{TM}=11A$ $t_p=380\mu s$ $T_j=25^\circ C$	Max.	1.55	V	
$V_{to}^{(2)}$	Threshold voltage $T_j=125^\circ C$	Max.	0.85	V	
$R_d^{(2)}$	Dynamic resistance $T_j=125^\circ C$	Max.	50	m $\Omega$	
$I_{DRM}$ $I_{RRM}$	$V_{DRM} = V_{RRM}$	$T_j=25^\circ C$	Max.	5.0	$\mu A$
		$T_j=125^\circ C$	Max.	1.0	mA

Note 2: for both polarities of A2 referenced to A1.

**电参数曲线图 / Electrical Characteristic Curve**




**电参数曲线图 / Electrical Characteristic Curve**




外形尺寸图 / Package Dimensions

T0-220F

单位: mm



印章说明 / Marking Instructions



说明：

BR： 为公司代码

BTA08： 为产品型号

60C： 为  $V_{RRM}$  和  $I_{GT}$  分档代码

\*\*\*\*： 为生产批号代码，随生产批号变化。

Note:


BR: Company Code

BTA08: Product Type.

60C:  $V_{RRM}$ 、 $I_{GT}$  Bracket code

\*\*\*\*: Lot No. Code, code change with Lot No.

**波峰焊温度曲线图(无铅) / Temperature Profile for Dip Soldering(Pb-Free)**



说明：

- 1、预热温度 25 ~ 150°C，时间 60 ~ 90sec；
- 2、峰值温度 255±5°C，时间持续为 5±0.5sec；
- 3、焊接制程冷却速度为 2 ~ 10°C/sec.

Note:

- 1.Preheating:25~150°C, Time:60~90sec.
- 2.Peak Temp.:255±5°C, Duration:5±0.5sec.
3. Cooling Speed: 2~10°C/sec.

**耐焊接热试验条件 / Resistance to Soldering Heat Test Conditions**

温度：270±5°C

时间：10±1 sec.

Temp.:270±5°C

Time:10±1 sec

**包装规格 / Packaging SPEC.**

散件包装 / BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm <sup>3</sup> )		
	Units/Bag 只/袋	Bags/Inner Box 袋/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Bag 袋	Inner Box 盒	Outer Box 箱
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

套管包装 / TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm <sup>3</sup> )		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-220/F	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180

**使用说明 / Notices**