

isc Silicon NPN Darlington Power Transistor
BU323Z
DESCRIPTION



- With TO-220 packaging
- Very high DC current gain
- Monolithic darlington transistor with integrated antiparallel collector-emitter diode
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- AC-DC motor control
- Electronic ignition
- Alternator regulator

ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{CBO}	Collector-Base Voltage	350	V
V _{CEO}	Collector-Emitter Voltage	200	V
V _{EBO}	Emitter-Base Voltage	6	V
I _C	Collector Current-Continuous	10	A
I _{CM}	Collector Current-Peak	20	A
I _B	Base Current- Continuous	3	A
P _C	Collector Power Dissipation	150	W
T _j	Junction Temperature	175	°C
T _{stg}	Storage Temperature Range	-65~175	°C



isc Silicon NPN Darlington Power Transistor
BU323Z
THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.0	$^{\circ}C/W$
$R_{th\ j-a}$	Thermal Resistance, Junction to Ambient	62.5	$^{\circ}C/W$

ELECTRICAL CHARACTERISTICS
 $T_C=25^{\circ}C$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
$V_{CE0(SUS)}$	Collector-Emitter Sustaining Voltage	$I_C=7A, I_B=0$	350		V
$V_{CE(sat)1}$	Collector-Emitter Saturation Voltage	$I_C=7A, I_B=70mA$		1.6	V
$V_{CE(sat)2}$	Collector-Emitter Saturation Voltage	$I_C=8A, I_B=0.1A$		1.8	V
$V_{CE(sat)3}$	Collector-Emitter Saturation Voltage	$I_C=10A, I_B=0.25A$		1.7	V
$V_{BE(sat)1}$	Base-Emitter Saturation Voltage	$I_C=8A, I_B=100mA$		2.2	V
$V_{BE(sat)2}$	Base-Emitter Saturation Voltage	$I_C=10A, I_B=0.25A$		2.5	V
$V_{BE(on)1}$	Base-Emitter On Voltage	$I_C=5A; V_{CE}=2V$		2.1	V
$V_{BE(on)2}$	Base-Emitter On Voltage	$I_C=8A; V_{CE}=5V$		2.3	V
I_{CBO}	Collector Cutoff Current	$V_{CB}=-350V, I_E=0$		100	μA
I_{CEO}	Collector Cutoff Current	$V_{CE}=200V, I_B=0$		100	μA
I_{EBO}	Emitter Cutoff Current	$V_{EB}=5V, I_C=0$		50	mA
h_{FE-1}	DC Current Gain	$I_C=6.5A; V_{CE}=1.5V$	150		
h_{FE-2}	DC Current Gain	$I_C=5.0A; V_{CE}=4.6V$	500	3400	

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.