

# BUK652R7-30C

N-channel TrenchMOS intermediate level FET

Rev. 01 — 5 July 2010

Objective data sheet

## 1. Product profile

### 1.1 General description

Intermediate level gate drive N-channel enhancement mode Field-Effect Transistor (FET) in a plastic package using advanced TrenchMOS technology. This product has been designed and qualified to the appropriate AEC Q101 standard for use in high performance automotive applications.

### 1.2 Features and benefits

- AEC Q101 compliant
- Suitable for intermediate level gate drive sources
- Suitable for thermally demanding environments due to 175 °C rating

### 1.3 Applications

- 12 V Automotive systems
- Electric and electro-hydraulic power steering
- Motors, lamps and solenoid control
- Start-Stop micro-hybrid applications
- Transmission control
- Ultra high performance power switching

### 1.4 Quick reference data

**Table 1. Quick reference data**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$V_{DS}$	drain-source voltage	$T_j \geq 25^\circ\text{C}; T_j \leq 175^\circ\text{C}$	-	-	30	V
$I_D$	drain current	$V_{GS} = 10\text{ V}; T_{mb} = 25^\circ\text{C};$ [1] see <a href="#">Figure 1</a>	-	-	100	A
$P_{tot}$	total power dissipation	$T_{mb} = 25^\circ\text{C};$ see <a href="#">Figure 2</a>	-	-	204	W
<b>Static characteristics</b>						
$R_{DSon}$	drain-source on-state resistance	$V_{GS} = 10\text{ V}; I_D = 25\text{ A};$ $T_j = 25^\circ\text{C};$ see <a href="#">Figure 13</a> ; see <a href="#">Figure 14</a>	-	2.72	3.2	mΩ



**Table 1.** Quick reference data ...continued

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>Avalanche ruggedness</b>						
$E_{DS(AL)S}$	non-repetitive drain-source avalanche energy	$I_D = 100 \text{ A}$ ; $V_{\text{sup}} \leq 30 \text{ V}$ ; $R_{GS} = 50 \Omega$ ; $V_{GS} = 10 \text{ V}$ ; $T_{j(\text{init})} = 25^\circ\text{C}$ ; unclamped	-	-	501	mJ
<b>Dynamic characteristics</b>						
$Q_{GD}$	gate-drain charge	$I_D = 25 \text{ A}$ ; $V_{DS} = 24 \text{ V}$ ; $V_{GS} = 10 \text{ V}$ ; see <a href="#">Figure 15</a> ; see <a href="#">Figure 16</a>	-	33.3	-	nC

[1] Continuous current is limited by package.

## 2. Pinning information

**Table 2.** Pinning information

Pin	Symbol	Description	Simplified outline	Graphic symbol
1	G	gate		
2	D	drain		
3	S	source		
mb	D	mounting base; connected to drain		
SOT78A (TO-220AB)				

## 3. Ordering information

**Table 3.** Ordering information

Type number	Package		
	Name	Description	Version
BUK652R7-30C	TO-220AB	plastic single-ended package; heatsink mounted; 1 mounting hole; 3-lead TO-220AB	SOT78A

## 4. Limiting values

**Table 4. Limiting values**

In accordance with the Absolute Maximum Rating System (IEC 60134).


Symbol	Parameter	Conditions	Min	Max	Unit	
$V_{DS}$	drain-source voltage	$T_j \geq 25^\circ\text{C}; T_j \leq 175^\circ\text{C}$	-	30	V	
$V_{GS}$	gate-source voltage	Pulsed; Accumulated pulse duration not to exceed 168 hours.	-20	20	V	
$I_D$	drain current	$T_{mb} = 25^\circ\text{C}; V_{GS} = 10\text{ V}$ ; see <a href="#">Figure 1</a> [1]	-	100	A	
		$T_{mb} = 100^\circ\text{C}; V_{GS} = 10\text{ V}$ ; see <a href="#">Figure 1</a> [1]	-	100	A	
$I_{DM}$	peak drain current	$T_{mb} = 25^\circ\text{C}; t_p \leq 10\ \mu\text{s}$ ; pulsed; see <a href="#">Figure 4</a>	-	733	A	
$P_{tot}$	total power dissipation	$T_{mb} = 25^\circ\text{C}$ ; see <a href="#">Figure 2</a>	-	204	W	
$T_{stg}$	storage temperature		-55	175	°C	
$T_j$	junction temperature		-55	175	°C	
$V_{GS}$	gate-source voltage	DC	-16	16	V	
<b>Source-drain diode</b>						
$I_S$	source current	$T_{mb} = 25^\circ\text{C}$	[1]	-	100	A
$I_{SM}$	peak source current	$t_p \leq 10\ \mu\text{s}$ ; pulsed; $T_{mb} = 25^\circ\text{C}$	-	733	A	
<b>Avalanche ruggedness</b>						
$E_{DS(AL)S}$	non-repetitive drain-source avalanche energy	$I_D = 100\text{ A}; V_{sup} \leq 30\text{ V}; R_{GS} = 50\ \Omega$ ; $V_{GS} = 10\text{ V}; T_{j(init)} = 25^\circ\text{C}$ ; unclamped	-	501	mJ	
$E_{DS(AL)R}$	repetitive drain-source avalanche energy	see <a href="#">Figure 3</a>	[2][3][4]	-	-	J

[1] Continuous current is limited by package.


[2] Single-pulse avalanche rating limited by maximum junction temperature of 175 °C.

[3] Repetitive avalanche rating limited by an average junction temperature of 170 °C.


[4] Refer to application note AN10273 for further information.

 $V_{GS} \geq 10$  V

(1) capped at 100 A due to package




$$P_{der} = \frac{P_{tot}}{P_{tot}(25^{\circ}\text{C})} \times 100 \%$$

**Fig 1.** Continuous drain current as a function of mounting base temperature**Fig 2.** Normalized total power dissipation as a function of mounting base temperature(1) Single pulse,  $T_j = 25$  °C(2) Single pulse,  $T_j = 125$  °C

(3) Repetitive pulse

**Fig 3.** Single-pulse and repetitive avalanche rating; avalanche current as a function of avalanche time




$T_{mb} = 25^\circ\text{C}$ ;  $I_{DM}$  is a single pulse

Fig 4. Safe operating area; continuous and peak drain currents as a function of drain-source voltage

## 5. Thermal characteristics

**Table 5. Thermal characteristics**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j\text{-mb})}$	thermal resistance from junction to mounting base	see <a href="#">Figure 5</a>	-	-	0.7	K/W
$R_{th(j\text{-a})}$	thermal resistance from junction to ambient	vertical in free air	-	60	-	K/W



**Fig 5. Transient thermal impedance from junction to mounting base as a function of pulse duration**


## 6. Characteristics

**Table 6. Characteristics**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>Static characteristics</b>						
$V_{(BR)DSS}$	drain-source breakdown voltage	$I_D = 250 \mu A; V_{GS} = 0 V; T_j = 25^\circ C$ $I_D = 250 \mu A; V_{GS} = 0 V; T_j = -55^\circ C$	30	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	$I_D = 1 mA; V_{DS} = V_{GS}; T_j = 25^\circ C;$ see <a href="#">Figure 11</a> ; see <a href="#">Figure 12</a> $I_D = 1 mA; V_{DS} = V_{GS}; T_j = -55^\circ C;$ see <a href="#">Figure 11</a> $I_D = 1 mA; V_{DS} = V_{GS}; T_j = 175^\circ C;$ see <a href="#">Figure 11</a>	1.8	2.3	2.8	V
$I_{DSS}$	drain leakage current	$V_{DS} = 30 V; V_{GS} = 0 V; T_j = 25^\circ C$ $V_{DS} = 30 V; V_{GS} = 0 V; T_j = 175^\circ C$	-	0.02	1	$\mu A$
$I_{GSS}$	gate leakage current	$V_{DS} = 0 V; V_{GS} = 20 V; T_j = 25^\circ C$ $V_{DS} = 0 V; V_{GS} = -20 V; T_j = 25^\circ C$	-	2	100	nA
$R_{DSon}$	drain-source on-state resistance	$V_{GS} = 10 V; I_D = 25 A; T_j = 25^\circ C;$ see <a href="#">Figure 13</a> ; see <a href="#">Figure 14</a> $V_{GS} = 4.5 V; I_D = 25 A; T_j = 25^\circ C;$ see <a href="#">Figure 13</a> ; see <a href="#">Figure 14</a> $V_{GS} = 5 V; I_D = 25 A; T_j = 25^\circ C;$ see <a href="#">Figure 13</a> $V_{GS} = 10 V; I_D = 25 A; T_j = 175^\circ C;$ see <a href="#">Figure 13</a>	-	2.72	3.2	$m\Omega$
<b>Dynamic characteristics</b>						
$Q_{G(tot)}$	total gate charge	$I_D = 25 A; V_{DS} = 24 V; V_{GS} = 10 V;$ see <a href="#">Figure 15</a> ; see <a href="#">Figure 16</a> $I_D = 25 A; V_{DS} = 24 V; V_{GS} = 5 V;$ see <a href="#">Figure 15</a> ; see <a href="#">Figure 16</a>	-	115	-	nC
$Q_{GS}$	gate-source charge	$I_D = 25 A; V_{DS} = 24 V; V_{GS} = 10 V;$ see <a href="#">Figure 15</a> ; see <a href="#">Figure 16</a>	-	18	-	nC
$Q_{GD}$	gate-drain charge	see <a href="#">Figure 15</a> ; see <a href="#">Figure 16</a>	-	33.3	-	nC
$C_{iss}$	input capacitance	$V_{GS} = 0 V; V_{DS} = 25 V; f = 1 MHz; T_j = 25^\circ C;$	-	5216	-	pF
$C_{oss}$	output capacitance	see <a href="#">Figure 17</a>	-	896	-	pF
$C_{rss}$	reverse transfer capacitance		-	537	-	pF
$t_{d(on)}$	turn-on delay time	$V_{DS} = 25 V; R_L = 1 \Omega; V_{GS} = 10 V;$	-	118	-	ns
$t_r$	rise time	$R_{G(ext)} = 10 \Omega$	-	484	-	ns
$t_{d(off)}$	turn-off delay time		-	244	-	ns
$t_f$	fall time		-	269	-	ns
$L_D$	internal drain inductance	from drain lead 6 mm from package to centre of die ; $T_j = 25^\circ C$	-	4.5	-	nH
$L_S$	internal source inductance	from source lead to source bond pad ; $T_j = 25^\circ C$	-	7.5	-	nH


**Table 6. Characteristics ...continued**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>Source-drain diode</b>						
$V_{SD}$	source-drain voltage	$I_S = 25 \text{ A}; V_{GS} = 0 \text{ V}; T_j = 25^\circ\text{C}$ ; see <a href="#">Figure 18</a>	-	0.8	1.2	V
$t_{rr}$	reverse recovery time	$I_S = 20 \text{ A}; dI_S/dt = -100 \text{ A}/\mu\text{s}; V_{GS} = 0 \text{ V}; V_{DS} = 25 \text{ V}$	-	[tbd]	-	ns
$Q_r$	recovered charge		-	[tbd]	-	nC




$T_j = 25^\circ\text{C}; V_{DS} = 25 \text{ V}$

**Fig 6. Forward transconductance as a function of drain current; typical values**




$T_j = 25^\circ\text{C}$  and  $t_p = 300 \mu\text{s}$

**Fig 7. Output characteristics: drain current as a function of drain-source voltage; typical values**




$V_{DS} = 25 \text{ V}$

**Fig 8. Transfer characteristics: drain current as a function of gate-source voltage; typical values**




$T_j = 25^\circ\text{C}; I_D = 25 \text{ A}$

**Fig 9. Drain-source on-state resistance as a function of gate-source voltage; typical values**




$V_{DS} = 0 \text{ V}; f = 1 \text{ MHz}$

**Fig 10. Input and reverse transfer capacitances as a function of gate-source voltage, typical values**




$I_D = 1 \text{ mA}; V_{DS} = V_{GS}$

**Fig 11. Gate-source threshold voltage as a function of junction temperature**




$T_j = 25^\circ\text{C}; V_{DS} = 5\text{V}$

**Fig 12. Sub-threshold drain current as a function of gate-source voltage**




$$a = \frac{R_{DSon}}{R_{DSon}(25^\circ\text{C})}$$

**Fig 13. Normalized drain-source on-state resistance factor as a function of junction temperature**




$T_j = 25^\circ\text{C}$ ;  $t_p = 300 \mu\text{s}$

**Fig 14. Drain-source on-state resistance as a function of drain current; typical values**




**Fig 15. Gate charge waveform definitions**




$T_j = 25^\circ\text{C}$  and  $I_D = 25 \text{ A}$

**Fig 16. Gate-source voltage as a function of gate charge; typical values**



$V_{GS} = 0 \text{ V}$ ;  $f = 1 \text{ MHz}$

**Fig 17. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values**




$V_{GS} = 0\text{ V}$

Fig 18. Source (diode forward) current as a function of source-drain (diode forward) voltage; typical values

## 7. Package outline

Plastic single-ended package; heatsink mounted; 1 mounting hole; 3-lead TO-220AB

SOT78A



0 5 10 mm  
scale

### DIMENSIONS (mm are the original dimensions)

UNIT	A	A <sub>1</sub>	b	b <sub>1</sub>	c	D	D <sub>1</sub>	E	e	L	L <sub>1(1)</sub>	L <sub>2</sub> max.	p	q	Q
mm	4.5 4.1	1.39 1.27	0.9	1.3 1.0	0.7 0.4	15.8 15.2	6.4 5.9	10.3 9.7	2.54	15.0 13.5	3.30 2.79	3.0	3.8 3.6	3.0 2.7	2.6 2.2

### Note

1. Terminals in this zone are not tinned.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT78A		3-lead TO-220AB	SC-46			-03-01-22- 05-03-14

Fig 19. Package outline SOT78A (TO-220AB)

## 8. Revision history

**Table 7. Revision history**

Document ID	Release date	Data sheet status	Change notice	Supersedes
BUK652R7-30C v.1	20100705	Objective data sheet	-	-

## 9. Legal information

### 9.1 Data sheet status

Document status <sup>[1][2]</sup>	Product status <sup>[3]</sup>	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

### 9.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between NXP Semiconductors and its customer, unless NXP Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the NXP Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet.

### 9.3 Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of NXP Semiconductors.

**Right to make changes** — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use in automotive applications** — This NXP Semiconductors product has been qualified for use in automotive applications. The product is not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on a weakness or default in the customer application/use or the application/use of customer's third party customer(s) (hereinafter both referred to as "Application"). It is customer's sole responsibility to check whether the NXP Semiconductors product is suitable and fit for the Application planned. Customer has to do all necessary testing for the Application in order to avoid a default of the Application and the product. NXP Semiconductors does not accept any liability in this respect.

**Quick reference data** — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding. **Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Adelante, Bitport, Bitsound, CoolFlux, CoReUse, DESFire, EZ-HV, FabKey, GreenChip, HiPerSmart, HITAG, I<sup>2</sup>C-bus logo,ICODE, I-CODE, ITEC, Labelution, MIFARE, MIFARE Plus, MIFARE Ultralight, MoReUse, QLPAK, Silicon Tuner, SiliconMAX, SmartXA, STARplug, TOPFET, TrenchMOS, TriMedia and UCODE — are trademarks of NXP B.V.

## 9.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

HD Radio and HD Radio logo — are trademarks of iBiquity Digital Corporation.

## 10. Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

## 11. Contents

---

<b>1</b>	<b>Product profile</b>	<b>1</b>
1.1	General description	1
1.2	Features and benefits	1
1.3	Applications	1
1.4	Quick reference data	1
<b>2</b>	<b>Pinning information</b>	<b>2</b>
<b>3</b>	<b>Ordering information</b>	<b>2</b>
<b>4</b>	<b>Limiting values</b>	<b>3</b>
<b>5</b>	<b>Thermal characteristics</b>	<b>6</b>
<b>6</b>	<b>Characteristics</b>	<b>7</b>
<b>7</b>	<b>Package outline</b>	<b>12</b>
<b>8</b>	<b>Revision history</b>	<b>13</b>
<b>9</b>	<b>Legal information</b>	<b>14</b>
9.1	Data sheet status	14
9.2	Definitions	14
9.3	Disclaimers	14
9.4	Trademarks	15
<b>10</b>	<b>Contact information</b>	<b>15</b>

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© NXP B.V. 2010.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

Date of release: 5 July 2010

Document identifier: BUK652R7-30C