

isc Silicon NPN Power Transistor
BUT100
DESCRIPTION



- Collector-Emitter Sustaining Voltage-
: $V_{CEO(SUS)} = 125V$ (Min.)
- High Current Capability
- High Ruggedness
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Motor Control
- Uninterruptable Power Supply

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}C$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	200	V
V_{CEO}	Collector-Emitter Voltage	125	V
V_{EBO}	Emitter-Base Voltage	7	V
I_C	Collector Current-Continuous	50	A
I_{CM}	Collector Current-Peak Repetitive	150	A
P_C	Collector Power Dissipation @ $T_C=75^{\circ}C$	300	W
T_J	Junction Temperature	200	$^{\circ}C$
T_{stg}	Storage Temperature Range	-55~200	$^{\circ}C$



isc Silicon NPN Power Transistor**BUT100****ELECTRICAL CHARACTERISTICS** $T_C=25^\circ\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage	$I_C=50\text{mA}; I_B=0$	125			V
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage	$I_C=1\text{mA}; I_E=0$	200			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	$I_E=1\text{mA}; I_C=0$	7			V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=50\text{A}; I_B=2.5\text{A}$ $I_C=50\text{A}; I_B=2.5\text{A}; T_j=100^\circ\text{C}$			0.9 1.2	V
$V_{BE(sat)}$ *	Base-Emitter Saturation Voltage	$I_C=50\text{A}; I_B=2.5\text{A}$ $I_C=50\text{A}; I_B=2.5\text{A}; T_j=100^\circ\text{C}$			1.4 1.4	V
h_{FE}	DC Current Gain	$I_C=1\text{A}; V_{CE}=5\text{V}$	50			
I_{CBO}	Collector Cutoff Current	$V_{CB}=200\text{V}; I_E=0$			10	μA
I_{CEO}	Collector Cut-off Current	$V_{CE}=125\text{V}; I_E=0$ $V_{CE}=125\text{V}; T_C=100^\circ\text{C}$			1 5	mA
I_{EBO}	Emitter Cutoff Current	$V_{EB}=5\text{V}; I_C=0$			10	μA

* Pulsed: Pulse duration = $3\mu\text{s}$, duty cycle = 2 %**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.