

isc Silicon NPN Power Transistor
BUV48A
DESCRIPTION

- High Voltage Capability
- High Current Capability
- Fast Switching Speed

APPLICATIONS

Designed for high-voltage, high-speed, power switching in inductive circuits where fall time is critical. They are particularly suited for line-operated switchmode applications such as:



- Switching regulators
- Inverters
- Solenoid and relay drivers
- Motor controls
- Deflection circuits

Absolute maximum ratings(Ta=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{CEX}	Collector-Emitter Voltage (V _{BE} = -1.5V)	1000	V
V _{CEO}	Collector-Emitter Voltage	450	V
V _{EBO}	Emitter-Base Voltage	7	V
I _c	Collector Current-Continuous	15	A
I _{CM}	Collector Current-Peak	30	A
I _B	Base Current-Continuous	5	A
I _{BM}	Base Current-peak	20	A
P _C	Collector Power Dissipation @T _C =25°C	150	W
T _j	Junction Temperature	150	°C
T _{stg}	Storage Temperature Range	-65~150	°C

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{thj-c}	Thermal Resistance, Junction to Case	1.0	°C/W



isc Silicon NPN Power Transistor
BUV48A
ELECTRICAL CHARACTERISTICS
T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
V _{CEO(SUS)}	Collector-Emitter Sustaining Voltage	I _c = 30mA ; I _B = 0	450		V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = 10mA; I _C = 0	7		V
V _{CE(sat)-1}	Collector-Emitter Saturation Voltage	I _c = 8A; I _B = 1.6A		1.5	V
V _{CE (sat)-2}	Collector-Emitter Saturation Voltage	I _c = 12A ;I _B = 2.4A		5.0	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _c = 8A; I _B = 1.6A		1.6	V
I _{CEO}	Collector Cutoff Current	V _{CE} =450V, I _B =0		0.5	mA
I _{CBO}	Collector Cutoff Current	V _{CB} =850V I _E =0		0.2	mA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C = 0		0.1	mA
h _{FE}	DC Current Gain	I _c = 8A ; V _{CE} = 5V	8		

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.