



NPN BUX12

HIGH CURRENT, HIGH SPEED , HIGH POWER TRANSISTOR

The BUX12 is silicon multiepitaxial planar NPN transistors in Jedec TO-3. They are intended for use in switching and linear applications in military and industrial equipment.
Compliance to RoHS

ABSOLUTE MAXIMUM RATINGS

| Symbol | | | Unit |
|-----------|---------------------------|--------------------|----------------|
| V_{CEO} | Collector-Emitter Voltage | $I_B = 0$ | 250 V |
| V_{CBO} | Collector-Base Voltage | $I_E = 0$ | 300 V |
| V_{EBO} | Emitter-Base Voltage | $I_C = 0$ | 7.0 V |
| V_{CEX} | Collector-Emitter Voltage | $V_{BE} = -1.5V$ | 300 V |
| I_C | Collector Current | | 20 A |
| I_{CM} | Collector Peak Current | $t_p = 10ms$ | 25 A |
| I_B | Base Current | | 4 A |
| P_t | Total Power Dissipation | @ $T_C = 25^\circ$ | 150 W |
| T_J | Junction Temperature | | 200 °C |
| T_{Stg} | Storage Temperature | | -65 to +200 °C |

THERMAL CHARACTERISTICS

| Symbol | Ratings | Value | Unit |
|------------|--------------------------------------|-------|------|
| R_{thJC} | Thermal Resistance, Junction to Case | 1.17 | °C/W |

NPN BUX12

ELECTRICAL CHARACTERISTICS

TC=25°C unless otherwise noted


| Symbol | Ratings | Test Condition(s) | Min | Typ | Max | Unit |
|----------------|--|---|------|------|-----|---------------|
| $V_{CE0(SUS)}$ | Collector-Emitter Sustaining Voltage (*) | $I_C=200\text{ mA}$ | 250 | - | - | V |
| $V_{EB0(SUS)}$ | Emitter-Base Breakdown Voltage (*) | $I_C=0\text{A}, I_E=50\text{ mA}$ | 7 | - | - | V |
| I_{CEO} | Collector Cutoff Current | $V_{CE}=200\text{ V}, I_B=0\text{A}$ | - | - | 1.5 | mA |
| I_{CEX} | Collector Cutoff Current | $V_{CE}=V_{CEX}, V_{BE}=-1.5\text{V}$ | - | - | 1.5 | mA |
| | | $V_{CE}=V_{CEX}, V_{BE}=-1.5\text{V}$ $T_{case}=125^\circ\text{C}$ | - | - | 6 | |
| I_{EBO} | Emitter Cutoff Current | $V_{EB}=5.0\text{ V}, I_C=0$ | - | - | 1 | mA |
| h_{FE} | DC Current Gain (*) | $I_C=5\text{ A}, V_{CE}=4.0\text{ V}$ | 20 | - | 60 | - |
| | | $I_C=10\text{ A}, V_{CE}=4.0\text{ V}$ | 10 | - | - | |
| $V_{CE(SAT)}$ | Collector-Emitter saturation Voltage (*) | $I_C=5\text{ A}, I_B=0.5\text{ A}$ | - | 0.22 | 1 | V |
| | | $I_C=10\text{ A}, I_B=1.25\text{ A}$ | - | 0.5 | 1.5 | |
| $V_{BE(SAT)}$ | Base-Emitter saturation Voltage (*) | $I_C=10\text{ A}, I_B=1.25\text{ A}$ | - | 1.23 | 1.5 | |
| $I_{S/B}$ | Second breakdown collector current | $V_{CE}=30\text{ V}, t_s=1\text{ s}$ | 5 | - | - | A |
| | | $V_{CE}=140, t_s=1\text{ s}$ | 0.15 | - | - | |
| $E_{S/B}$ | Clamped $E_{S/B}$ Collector current | $V_{clamp}=250\text{ V}, L=500\text{ }\mu\text{H}$ | 10 | - | - | A |
| f_T | Transition frequency | $V_{CE}=15\text{ V}, I_C=1\text{ A}$ $f=10\text{ MHz}$ | 8 | - | - | MHz |
| t_{on} | Turn-on time | $I_C=10\text{ A}, I_B=1.25\text{ A}$ $V_{CC}=150\text{ V}$ | - | 0.28 | 1 | μs |
| t_s | Storage time | $I_C=10\text{ A}, V_{CC}=150\text{ V}$ | - | 1.45 | 2 | |
| t_f | File time | $I_{B1}=-I_{B2}=1.25\text{ A}$ | - | 0.23 | 0.5 | |

(*) Pulse Duration = 300 μs , Duty Cycle $\leq 2\%$


NPN BUX12

MECHANICAL DATA CASE TO-3

| DIMENSIONS (mm) | | |
|-----------------|-------|-------|
| | min | max |
| A | 11 | 13.10 |
| B | 0.97 | 1.15 |
| C | 1.5 | 1.65 |
| D | 8.32 | 8.92 |
| F | 19 | 20 |
| G | 10.70 | 11.1 |
| N | 16.50 | 17.20 |
| P | 25 | 26 |
| R | 4 | 4.09 |
| U | 38.50 | 39.30 |
| V | 30 | 30.30 |



| | |
|---------|-----------|
| Pin 1 : | Base |
| Pin 2 : | Emitter |
| Case : | Collector |



Revised September 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.