

isc Silicon NPN Power Transistor
BUY72
DESCRIPTION

- Collector-Emitter Breakdown Voltage-
: $V_{(BR)CEO} = 200V(\text{Min.})$
- Low Collector Saturation Voltage-
: $V_{CE(sat)} = 1.5V @ I_c = 7A$
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Designed for general switching applications at higher outputs.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	MAX	UNIT
V_{CBO}	Collector-Base Voltage	280	V
V_{CES}	Collector-Emitter Voltage	280	V
V_{CEO}	Collector-Emitter Voltage	200	V
V_{EBO}	Emitter-Base Voltage	6	V
I_c	Collector Current-Continuous	10	A
I_{CM}	Collector Current-Peak	15	A
I_B	Base Current-Continuous	2	A
P_C	Collector Power Dissipation @ $T_c \leq 75^\circ\text{C}$	60	W
T_j	Junction Temperature	175	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-65~175	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.66	$^\circ\text{C}/\text{W}$



isc Silicon NPN Power Transistor

BUY72

ELECTRICAL CHARACTERISTICS

T_C=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 20mA; I _B = 0	200			V
V _{(BR)CBO}	Collector-Base Breakdown Voltage	I _C = 1mA; I _E = 0	280			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = 1mA; I _C = 0	6			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 7A; I _B = 0.875A			1.5	V
V _{BE(on)}	Base-Emitter On Voltage	I _C = 7A; V _{CE} = 1.5V			1.6	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 280V; I _E = 0 V _{CB} = 280V; I _E = 0; T _C = 150°C			1.0 10	mA
I _{CES}	Collector Cutoff Current	V _{CE} = 280V; V _{BE} = 0 V _{CE} = 280V; V _{BE} = 0; T _C = 150°C			1.0 10	mA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 6V; I _C = 0			1.0	mA
h _{FE-1}	DC Current Gain	I _C = 2A; V _{CE} = 1.5V	25		160	
h _{FE-2}	DC Current Gain	I _C = 7A; V _{CE} = 1.5V	8			

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.