

isc Silicon NPN Power Transistors
BUY79
DESCRIPTION

- Collector-Emitter Breakdown Voltage-
: $V_{(BR)CEO} = 350V(\text{Min.})$
- Low Collector-Emitter Saturation Voltage-
: $V_{CE(sat)} = 1.5V(\text{Max.}) @ I_C = 5A$
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Designed for use as high-speed power switches at high voltages.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	750	V
V_{CES}	Collector-Emitter Voltage	750	V
V_{CEO}	Collector-Emitter Voltage	350	V
V_{EBO}	Emitter-Base Voltage	7	V
I_C	Collector Current-Continuous	8	A
I_{CM}	Collector Current-peak	10	A
P_C	Collector Power Dissipation @ $T_C \leq 75^\circ\text{C}$	60	W
T_j	Junction Temperature	175	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-65~175	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.66	$^\circ\text{C/W}$



isc Silicon NPN Power Transistors

BUY79

ELECTRICAL CHARACTERISTICS

T_c=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = 50mA; I _B = 0	350			V
V _{(BR)CES}	Collector-Emitter Breakdown Voltage	I _C = 1mA; I _E = 0	750			V
V _{(BR)CEV}	Collector-Emitter Breakdown Voltage	I _C = 1mA; V _{BE} = -3.5V	750			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = 1mA; I _C = 0	7			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 5A; I _B = 1.25A			1.5	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = 5A; I _B = 1.25A			1.7	V
I _{CBO}	Collector Cutoff Current	V _{CB} = 400V; I _E = 0			1.0	mA
h _{FE}	DC Current Gain	I _C = 5A; V _{CE} = 1.5V	4			
f _T	Current-Gain—Bandwidth Product	I _C = 0.5A; V _{CE} = 10V		15		MHz
t _f	Fall Time	I _C = 3A; I _{B1} = -I _{B2} = 0.6A			1.0	μs

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.