

### FEATURES

- Available as “HR” (high reliability) screened per MIL-PRF-19500, JANTX level. Add “HR” suffix to base part number.
- Available as non-RoHS (Sn/Pb plating), standard, and as RoHS by adding “-PBF” suffix.

### MAXIMUM RATINGS

Symbol	Parameter		Value	Unit
$I_{FRM}$	Repetitive peak forward current	$t_p \leq 20\mu S$	50	A
$I_{F(AV)}$	Average forward current *	$T_A = 55^\circ C$ $\delta = 0.5$	3	A
$I_{FSM}$	Surge non-repetitive forward current	$t_p = 10ms$ sinusoidal	100	A
$P_{tot}$	Power dissipation *	$T_A = 55^\circ C$	3.75	W
$T_{stg}$ $T_J$	Storage and junction temperature range		-40 to +150	$^\circ C$
$T_L$	Maximum lead temperature for soldering during 10s at 4mm from case		230	$^\circ C$
$R_{th(j-a)}$	Junction-ambient *		25	$^\circ C/W$

Symbol	Parameter	BYT13-			Unit
		600	800	1000	
$V_{RRM}$	Repetitive peak reverse voltage	600	800	1000	V

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ C$ unless otherwise specified)

Symbol	Test Conditions	Min.	Typ.	Max.	Unit
$I_R$	$T_J = 25^\circ C$ $V_R = V_{RRM}$			20	$\mu A$
$V_F$	$T_J = 25^\circ C$ $I_F = 3A$			1.3	V

### RECOVERY CHARACTERISTICS

symbol	Test Conditions				Min.	Typ.	Max.	Unit
$t_{rr}$	$T_J = 25^\circ C$	$I_F = 0.5A$	$I_R = 1A$	$I_{rr} = 0.25A$			150	ns




High-reliability discrete products  
and engineering services since 1977

## BYT13-600 – BYT13-1000

FAST RECOVERY RECTIFIER DIODES

### MECHANICAL CHARACTERISTICS

<b>Case</b>	DO-201AD
<b>Marking</b>	Body painted, alpha-numeric
<b>Polarity</b>	Cathode band



	DO-201AD			
	Inches		Millimeters	
	Min	Max	Min	Max
BD	0.190	0.209	4.826	5.309
BL	0.285	0.375	7.240	9.530
LD	0.048	0.052	1.219	1.321
LL	1.000	-	25.400	-

Figure 1. Maximum average power dissipation versus average forward current.




Figure 2. Average forward current versus ambient temperature.




Figure 3. Thermal resistance versus lead length.




Figure 4. Transient thermal impedance junction-ambient for mounting n<sup>2</sup> versus pulse duration (L = 10 mm).




Figure 5. Peak forward current versus peak forward voltage drop (maximum values).




Figure 6. Capacitance versus reverse applied voltage




Figure 7. Non repetitive surge peak current versus number of cycles

